

DAFTAR PUSTAKA

- [1] J. C. Brody and J. W. Gillespie, “The effects of a thermoplastic polyester preform binder on vinyl ester resin,” *J. Thermoplast. Compos. Mater.*, vol. 18, no. 3, pp. 157–179, 2005, doi: 10.1177/0892705705043535.
- [2] S. Lubis and K. Nataniel, “Kajian Eksperimental Kekasaran Permukaan Polymer Ertalone 6SA Pada Proses Milling,” *J. Energi Dan Manufaktur*, vol. 7, no. 2, pp. 149–154, 2015.
- [3] F. J. Arenas Cabello, *Eco sostenible*, no. 41. 2015.
- [4] D. Eko Prasetyo, “Analisis Perbandingan Metode Pengujian Kekasaran Permukaan pada Material Polimer Dan Komposit - Review,” *J. Rekayasa Mesin*, vol. 6, no. 3, pp. 171–175, 2015, doi: 10.21776/ub.jrm.2015.006.03.6.
- [5] M. H. Banna, J. Shirokoff, and J. Molgaard, “Effects of two aqueous acidic solutions on polyester and bisphenol A epoxy vinyl ester resins,” *Mater. Sci. Eng. A*, vol. 528, no. 4–5, pp. 2137–2142, 2011, doi: 10.1016/j.msea.2010.11.049.
- [6] M. C. Seghini *et al.*, “Effects of oxygen and tetravinylsilane plasma treatments on mechanical and interfacial properties of flax yarns in thermoset matrix composites,” *Cellulose*, vol. 27, no. 1, pp. 511–530, 2020, doi: 10.1007/s10570-019-02785-3.
- [7] T. Serra, M. Ortiz-Hernandez, E. Engel, J. A. Planell, and M. Navarro, “Relevance of PEG in PLA-based blends for tissue engineering 3D-printed scaffolds,” *Mater. Sci. Eng. C*, vol. 38, no. 1, pp. 55–62, 2014, doi: 10.1016/j.msec.2014.01.003.
- [8] B. Atedi and D. Agustono, “STANDAR KEKASARAN PERMUKAAN BIDANG PADA YOKE FLANGE MENURUT ISO R.1302 dan DIN 4768 DENGAN MEMPERHATIKAN NILAI KETIDAKPASTIANNYA,” *Media Mesin Maj. Tek. Mesin*, vol. 6, no. 2, pp. 63–69, 2015, doi: 10.23917/mesin.v6i2.2897.
- [9] A. Zubaidi, M. Fcd, P. Mesin, and I. Syafa, “Terhadap Kekasaran Permukaan,” vol. 8, no. 1, pp. 40–47, 2012.
- [10] K. Palanikumar, “Application of Taguchi and response surface methodologies for surface roughness in machining glass fiber reinforced plastics by PCD tooling,” *Int. J.*

Adv. Manuf. Technol., vol. 36, no. 1–2, pp. 19–27, 2008, doi: 10.1007/s00170-006-0811-0.

- [11] H. Van Hoten, A. R. Nanda, and Zuliantoni, “OPTIMASI PARAMETER PROSES UNTUK MENINGKATKAN PRODUKTIVITAS No Side Rake Angle Side Clearance Angle,” vol. 8, no. 1, pp. 704–708, 2017.
- [12] R. Teti, “Machining of composite materials,” *CIRP Ann. - Manuf. Technol.*, vol. 51, no. 2, pp. 611–634, 2002, doi: 10.1016/S0007-8506(07)61703-X.
- [13] H. Ardhyananta *et al.*, “Mechanical and Thermal Properties of Unsaturated Polyester/Vinyl Ester Blends Cured at Room Temperature,” in *IOP Conference Series: Materials Science and Engineering*, 2017, vol. 202, no. 1, doi: 10.1088/1757-899X/202/1/012088.
- [14] A. Z. Muttaqin, “Laporan Penelitian Hibah Bersaing (Dipa Unej),” no. November, 2010.

