

DAFTAR PUSTAKA

- [1] H. el Hofy, *Fundamentals of Machining Processes*, 3rd ed. 2019.
- [2] P. E. Putra, “PENERAPAN METODA HIGH PRESSURE JET COOLANT (HPC) DENGAN PENDEKATAN MINIMUM QUALITY LUBRICATION (MQL) PADA PROSES MENGGURDI ALUMINIUM ALLOY (AA 5052),” *J. Chem. Inf. Model.*, vol. 53, no. 9, pp. 1689–1699, 2013.
- [3] E. García-Martínez, V. Miguel, A. Martínez-Martínez, M. C. Manjabacas, and J. Coello, “Sustainable Lubrication Methods for the Machining of Titanium Alloys: An Overview,” *Materials (Basel)*, vol. 12, no. 23, p. 3852, 2019, doi: 10.3390/ma12233852.
- [4] W. Liew and Y. Hsien, *SPRINGER BRIEFS IN MOLECULAR SCIENCE Towards Green Lubrication in Machining*. 2015.
- [5] B. Sen, M. Mia, G. M. Krolczyk, U. K. Mandal, and S. P. Mondal, *Eco-Friendly Cutting Fluids in Minimum Quantity Lubrication Assisted Machining: A Review on the Perception of Sustainable Manufacturing*, vol. 8, no. 1. Korean Society for Precision Engineering, 2021.
- [6] V. P. Astakhov and S. Joksch, *Metalworking fluids (MWFs) for cutting and grinding: Fundamentals and recent advances*. 2012.
- [7] R. Rizaldi, “EVALUASI UNJUK KERJA TIGA JENIS HASIL EKSTRAKSI ALUASI UNJUK KERJA TIGA JENIS HASIL EKSTRAKSI SANTAN KELAPA SEBAGAI CAIRAN PENDINGIN SANTAN KELAPA SEBAGAI CAIRAN PENDINGIN TERHADAP KEKASARAN PERMUKAAN TERHADAP KEKASARAN PERMUKAAN PADA PROSES BUBUT PADA PR,” vol. 87, no. 1,2, pp. 149–200, 2017.
- [8] T. P. Sarit K. Das , Stephen U. S. Choi , Wenhua Yu, *Nanofluids Science and Technology*. 2007.

- [9] M. Hosokawa, K. Nogi, M. Naito, and T. Yokoyama, *Nanoparticle Technology Handbook*. 2008.
- [10] M. S. Najiha, M. M. Rahman, and K. Kadirgama, "Performance of water-based TiO₂ nanofluid during the minimum quantity lubrication machining of aluminium alloy, AA6061-T6," *J. Clean. Prod.*, vol. 135, pp. 1623–1636, 2016, doi: 10.1016/j.jclepro.2015.12.015.
- [11] P. Rapeti, V. K. Pasam, K. M. Rao Gurramp, and R. S. Revuru, "Performance evaluation of vegetable oil based nano cutting fluids in machining using grey relational analysis-A step towards sustainable manufacturing," *J. Clean. Prod.*, vol. 172, pp. 2862–2875, 2016, doi: 10.1016/j.jclepro.2017.11.127.
- [12] Franky Adrianus, "Optimasi Proses Pengeringan Serat Nata de Coco Sebagai Kandidat Serat dalam Bahan Komposit untuk Panel Anti Peluru," 2009.
- [13] M. Algayri, "PENGARUH PEMANASAN KEMBALI TERHADAP SIFAT TARIK DAN THERMAL DISCOLORATION FILM BIOPOLIMER BAKTERI SELULOSA SERAT NATA DE COCO MENGGUNAKAN METODE PEMBUATAN DENGAN DAN TANPA PEMBEBANAN TEKAN," no. 1, 2020.
- [14] C. Anam, "Mengungkap Senyawa pada Nata De Coco sebagai Pangan Fungsional," *J. Ilmu Pangan dan Has. Pertan.*, vol. 3, no. 1, pp. 42–53, 2019, doi: 10.26877/jiphp.v3i1.3453.
- [15] A. K. Sharma, R. K. Singh, A. R. Dixit, and A. K. Tiwari, "Characterization and experimental investigation of Al₂O₃ nanoparticle based cutting fluid in turning of AISI 1040 steel under minimum quantity lubrication (MQL)," *Mater. Today Proc.*, vol. 3, no. 6, pp. 1899–1906, 2016, doi: 10.1016/j.matpr.2016.04.090.
- [16] Chetan, B. C. Behera, S. Ghosh, and P. V. Rao, "Application of nanofluids

during minimum quantity lubrication: A case study in turning process,” *Tribol. Int.*, vol. 101, pp. 234–246, 2016, doi: 10.1016/j.triboint.2016.04.019.

- [17] P. I. P. SARI, “PENGARUH VARIASI SERAT TKKS DAN GERAK MAKAN TERHADAP KEKASARAN PERMUKAAN DAN KEAUSAN TEPI HASIL PROSES PEMESINAN BUBUT PADA MATERIAL KOMPOSIT,” 2019.
- [18] Widarto, *Teknik Pemesinan*. 2008.
- [19] T. Rochim, *Proses Pemesinan*. Jakarta: Erlangga, 1993.
- [20] R. Rayza, “PENGARUH BENTUK MATA POTONG DAN NILAINYA TERHADAP SIFAT MAMPU MESIN PADA BAJA ST 42,” 2019.
- [21] D. Noerhamzah, “PENGARUH GERAK MAKAN DAN PUTARAN SPINDEL TERHADAP KEAUSAN PAHAT HSS PADA PROSES PEMESINAN END MILLING KOMPOSIT BERPENGUAT SERAT NENAS Diajukan,” 2019.
- [22] Nathbeke, “Tool wear Mechanism Adhesive Wear cont . Diffusion cont .,” pp. 1–8, 2013.
- [23] I. Hakim, *Tugas Akhir Tugas Akhir IDENTIFIKASI LAJU KEAUSAN TEPI PAHAT HSS DAN KARBIDA DENGAN VARIASI PENDINGINAN PADA PROSES MEMBUBUT MATERIAL METAL Matrik Komposit*, vol. 2, no. 1. 2020.
- [24] L. Čerče, F. Pušavec, and J. Kopač, “3D cutting tool-wear monitoring in the process,” *J. Mech. Sci. Technol.*, vol. 29, no. 9, pp. 3885–3895, 2015, doi: 10.1007/s12206-015-0834-2.
- [25] N. Halib, M. C. I. M. Amin, and I. Ahmad, “Physicochemical Properties and Characterization of Nata de Coco from Local Food Industries as a Source of Cellulose,” *Sains Malaysiana*, vol. 41, no. 2, pp. 205–211, 2012.

- [26] T. Saito *et al.*, “Individualization of nano-sized plant cellulose fibrils by direct surface carboxylation using TEMPO catalyst under neutral conditions,” *Biomacromolecules*, vol. 10, no. 7, pp. 1992–1996, 2009, doi: 10.1021/bm900414t.
- [27] Mitsubishi, “EFFECTS OF CUTTING CONDITIONS FOR TURNING.” http://www.mitsubishicarbide.net/contents/mmus/enus/html/product/technical_information/information/eikyo.html (accessed Dec. 20, 2021).

