

## DAFTAR PUSTAKA

- [1] BMKG. 2019. *Data Aktivitas Gempa Bumi di Indonesia*.  
<http://dataonline.bmkg.go.id> (Februari 2019)
- [2] BNPB. 2018. *Data Korban Gempa Bumi di Indonesia selama 2004-2018*.
- [3] Komuro, T., Nishikawa, Y., Kimura, Y.Ishiki, Y.(2004)  
“Development and Realization of Base System for High-Rise  
Buildings”.Japan
- [4] Infometrik.(2009), “ Konsep Dasar Finite Element Method”.  
<https://www.infometrik.com/2009/07/konsep-dasar-finite-element-method/>. Diakses pada 5 Oktober 2019
- [5] Zhang, X.T; Zhou, H.W ; dkk, “Design of n Experimental Research on a New Type of Steel Damper”, Tongji University.
- [6] Tatemichi, I., Kawaguchi, M. (2000), “ A new Approach to Seismic Isolation : Possible Application in Space Struktures”, International Jurnal in Spaces Structures, May, Vol. 15(2),pp. 145-154
- [7] Hitomi, Y., Osawa, K., Kanagawa, K., Saitoh, M. (2001), “Structural Design of Yamaguchi Dome”, International Symposium on Theory, Design and Realization of Shell and Spatial Structures, Nagoya, Japan, October, pp. 292-293.
- [8] Fan, F., Shen, S.Z, Parke, G.A.R (2004), “Theoritical and Experimental Study of Vibration Reduction in Braced Domes Using a Viscous Damper System”, International Journal of Space Structures, December, Vol 19(4), pp. 195-202.
- [9] Kato, S., Kim, Y.B., Nakazawa, S., Ohya, T (2006), “Simulation of the Cyclic Behavior of J-Shaped Steel Hysterisis Devices and Study on the Efficiency for Reducing Earthquake Responses of

- Space Structures”, Journal of Constructional Steel Research, October, Vol. 61(10), pp. 1457-1473.
- [10] Kato, S., Yun-Beom, K. (2005), “Simulation of the Cyclic Behavior of J-Shaped Steel Hysterisis Devices and Study on the Efficiency for Reducing Earthquake Responses of Space Structures”, Journal of Constructional Steel Research, 61, 1457-1473,2005.
- [11] Kato, S., Nakazawa, S., (2000), “Seismic Design Method og Single Layer Reticular Domes with Braces Subjected tp Severe Earthquake Motions”, Sixth Asian Pasific Conference on Shell and Spatial Structures, Seoul, Korea, October, pp. 131-140.
- [12] Kato, S., Konishi, Y. (2001), “A Study on Behavior of A Double Layer Dome with VED Installed in the Braces of the Sub-Structures under Severe Earthquake Motions”, International Symposium on Theory, Design and Realization of Shell and Spatial Structures, Nagoya, Japan, October, pp. 264-265
- [13] Fujita, M., Sedo, H., Iwata, M. (2002), “ Flat System Truss with Axial Hysteretic Dampers as Damage-Controlled Structure”, Journal of Structural and Construction Engineering, AIJ, September, Vol. 559, pp. 165-172 (in Japanese)
- [14] Ciampi, V., Ferreti, S.A. (1990), “Energy Dissipation in Building using Special Bracing System”, Proceeding of 19<sup>th</sup> European Conference on Earthquake Engineering, Vol. 3, Moskow, pp. 9-18.
- [15] Jurukovski, D., Petskovski, M., Rakicevic, Z. (1995), “Energy Absorbing in Regular and Composite Steel Frame Structures”, Engineering Structures, June, Vol. 17(5), pp. 319-333.

- [16] Aghlara, Reza., Tahir, Mahmood., Adnan, Azlan. (2018) “Experimental Study of Pipe-Fuse Damper for Passive Energy Dissipation in Structures”. Journal of Constructional Steel Research, pp. 351-360.
- [17] Sastranegara, A.(2009),“Mengenal Uji Tarik dan Sifat-sifat Material”,  
<http://www.infometrik.com/wpcontent/uploads/2009/09/mengenajujitarik.pdf>. Diakses pada 10 Oktober 2019

