

DAFTAR PUSTAKA

- [1] E. Georgantzia, M. Gkantou, and G. S. Kamaris, “Aluminium alloys as structural material: A review of research,” *Engineering Structures*, vol. 227, p. 111372, 2021, doi: 10.1016/j.engstruct.2020.111372.
- [2] B. Denkena and D. Biermann, “CIRP Annals - Manufacturing Technology Cutting edge geometries,” *CIRP Annals - Manufacturing Technology*, vol. 63, no. 2, pp. 631–653, 2014, doi: 10.1016/j.cirp.2014.05.009.
- [3] H. K. Tönshoff and B. Denkena, *Gear Grinding*. 2013. doi: 10.1007/978-3-642-33257-9_14.
- [4] P. K. Basuray, B. K. Misra, and G. K. Lal, “Transition from ploughing to cutting during machining with blunt tools,” *Wear*, vol. 43, no. 3, pp. 341–349, 1977, doi: 10.1016/0043-1648(77)90130-2.
- [5] P. Albrecht, “New Development in the Theory of the Metal-Cutting Process Part II The Theory of Chip Formation,” 2016.
- [6] C. Technology, *Cut faster. Run longer. improve quality. save money.* repeat, 2017.
- [7] Mardiansyah A, “Program StudiTeknik Mesin Fakultas Teknik Universitas Bengkulu 2014,” pp. 1–14, 2014.
- [8] T.rochim, *teori dan proses pemesinan*. bandung, 1993.
- [9] A. Herlambang, *PENGARUH RADIUS MATA POTONG PAHAT HSS*. andalas, 2018.
- [10] and M. L. K. . Vernaza-Pena, J. . Mason, T. Ovaert, *Temperature Generation in Cutting of Aluminium at Low and Negative Rake Angles*. 2003.
- [11] and E. H. K. Kurihara, K. Shosaku, *Cutting Temperature of Commercial Aluminium Alloys: Studies on Cutting Temperature of Aluminium Alloys*. Japan Institutue Light Met, 1968.
- [12] N. Fang and W. Q, “the effect of chamfered and honed tool edge geometry in machining of three alumunium alloys,” *Int. J. Mach. tools Manuf*, 2005.
- [13] Z. J. Yuan, M. Zhou, and S. Dong, “Effect of diamond tool sharpness on minimum cutting thickness and cutting surface integrity in ultraprecision machining,” *Journal of Materials Processing Technology*, vol. 62, no. 4, pp. 327–330, 1996, doi: 10.1016/S0924-0136(96)02429-6.
- [14] Paridawati, “P. Kecepatan dan Sudut Potong Terhadap Kekasaran Benda Kerja Pada and P. KECEPATAN DAN SUDUT POTONG TERHADAP KEKASARAN BENDA KERJA PADA MESIN BUBUT,” 2015.
- [15] jumli, *pengaruh radius mata potong pahat HSS terhadap konsumsi energi listrik pada saat proses pembubutan alumunium*. andalas, 2019.
- [16] C. Rodríguez, *Cutting edge preparation of precision cutting tools by applying micro-abrasive jet machining and brushing*. 2009. [Online]. Available:

<http://books.google.com/books?hl=en&lr=&id=NfRFEgFRmD4C&oi=fnd&pg=PA1&dq=Cutting+edge+preparation+of+precision+cutting+tools+by+applying+micro-abrasive+jet+machining+and+brushing&ots=GgzYmpGzY&sig=q4ztuTawKtjrVKvtbx4ZHTPCho4%5Cnhttp://books.google.com/bo>

- [17] L. A. Denguir, A. Besnard, G. Fromentin, G. Poulachon, and X. Zhu, “Flank wear prediction in milling AISI 4140 based on cutting forces PCA for different cutting edge preparations,” *International Journal of Machining and Machinability of Materials*, vol. 18, no. 3, pp. 273–287, 2016, doi: 10.1504/IJMMM.2016.076278.
- [18] S. Kalpakjian and S. Schmid, “Manufacturing engineering and technology, SI 6th Edition,” Pearson, p. 1216, 2013.
- [19] N. Semioshkinina and G. Voigt, “An overview on Taguchi Method,” *Journal Of Radiation Research*, vol. 47 Suppl A, no. 2, pp. A95–A100, 2006, [Online]. Available: <http://www.ncbi.nlm.nih.gov/pubmed/19879888>
- [20] A. A. Dar and S. Qadir, “Jarak ke default dan probabilitas default : studi eksperimental,” vol. 6, 2019.
- [21] V. PA and D. J.p, “tools (geometry and material) and tool wear,” *Mach. Fundam. Recent Adv*, 2008.

