

DAFTAR PUSTAKA

- [1] Jesudoss, “General Machinist Theory,” 2011.
- [2] H. Mohit and V. A. M. Selvan, “Effect of a Novel Chemical Treatment on Nanocellulose Fibers for Enhancement of Mechanical, Electrochemical and Tribological Characteristics of Epoxy Bio-nanocomposites,” *Fibers Polym.*, vol. 20, no. 9, pp. 1918–1944, 2019, doi: 10.1007/s12221-019-1224-7.
- [3] M. Asrofi *et al.*, “Isolation of Nanocellulose from Water Hyacinth Fiber (WHF) Produced via Digester-Sonication and Its Characterization,” *Fibers Polym.*, vol. 19, no. 8, pp. 1618–1625, 2018, doi: 10.1007/s12221-018-7953-1.
- [4] V. P. Astakhov and S. Joksch, “Metalworking fluids (MWFs) for cutting and grinding,” *Fundam. Recent Adv.*, 2012.
- [5] R. Rizaldi, *EVALUASI UNJUK KERJA TIGA JENIS HASIL EKSTRAKSI ALUASI UNJUK KERJA TIGA JENIS HASIL EKSTRAKSI SANTAN KELAPA SEBAGAI CAIRAN PENDINGIN SANTAN KELAPA SEBAGAI CAIRAN PENDINGIN TERHADAP KEKASARAN PERMUKAAN TERHADAP KEKASARAN PERMUKAAN PADA PROSES BUBUT PADA PR*, vol. 87, n. 2017.
- [6] W. Liew and Y. Hsien, “SPRINGER BRIEFS IN MOLECULAR SCIENCE Towards Green Lubrication in Machining,” 2015.
- [7] W. Y. T. P. Sarit K. Das , Stephen U. S. Choi, “Nanofluids Science and Technolog,” 2007.
- [8] and T. Y. M. Hosokawa, K. Nogi, M. Naito, “Nanoparticle Technology Handbook,” 2008.
- [9] and K. K. M. S. Najiha, M. M. Rahman, “Performance of water-based TiO₂ nanofluid during the minimum quantity lubrication machining of aluminium alloy, AA6061-T6,” in *J. Clean. Prod.*, 2016, pp. 1623–1636.
- [10] and R. S. R. P. Rapeti, V. K. Pasam, K. M. Rao Gurram, “Performance evaluation of vegetable oil based nano cutting fluids in machining using grey relational analysis-A step towards sustainable manufacturing,” in *J. Clean. Prod.*, 2016, pp. 2862–2875.
- [11] and A. K. T. A. K. Sharma, R. K. Singh, A. R. Dixit, “Characterization and experimental investigation of Al₂O₃ nanoparticle based cutting fluid in turning of AISI 1040 steel under minimum quantity lubrication (MQL),” in *Mater. Today Proc.*, 2016, pp. 1899–1906.
- [12] and P. V. R. Chetan, B. C. Behera, S. Ghosh, “Application of nanofluids during minimum quantity lubrication: A case study in turning process,” in *Tribol. Int.*, 2016, pp. 234–246.
- [13] H. el Hofy, “Fundamentals of Machining Processes,” *3rd ed*, 2019.
- [14] P. I. P. SARI, “PENGARUH VARIASI SERAT TKKS DAN GERAK MAKAN

TERHADAP KEKASARAN PERMUKAAN DAN KEAUSAN TEPI HASIL PROSES PEMESINAN BUBUT PADA MATERIAL KOMPOSIT,” 2019.

- [15] Widarto, “Teknik Pemesinan,” 2008.
- [16] T. Rochim, “Proses Pemesinan,” in *Jakarta: Erlangga*, 1993.
- [17] D. Noerhamzah, “PENGARUH GERAK MAKAN DAN PUTARAN SPINDEL TERHADAP KEAUSAN PAHAT HSS PADA PROSES PEMESINAN END MILLING KOMPOSIT BERPENGUAT SERAT NENAS,” 2019.
- [18] Nathbeke, “Tool wear Mechanism Adhesive Wear cont . Diffusion cont,” 2013, pp. 1–8.
- [19] I. Hakim, “Tugas Akhir Tugas Akhir IDENTIFIKASI LAJU KEAUSAN TEPI PAHAT HSS DAN KARBIDA DENGAN VARIASI PENDINGINAN PADA PROSES MEMBUBUT MATERIAL METAL Matrik KOMPOSIT,” 2020.
- [20] M. Asrofi et al, “Isolation of Nanocellulose from Water Hyacinth Fiber (WHF) Produced via Digester-Sonication and Its Characterization,” 2018.
- [21] and and Z. F. D. Rahmadiawan, H. Abral, N. Nasruddin, “Stability, Viscosity, and Tribology Properties of Polyol Ester Oil-Based Biolubricant Filled with TEMPO-Oxidized Bacterial Cellulose Nanofiber,” 2021.

