

DAFTAR PUSTAKA

- [1] Jesudoss. 2011. “*General Machinist Theory*”.
- [2] Wawan. 2017. “Deformasi yang Terjadi Memperpendek Umur Pahat”. Bandung.
- [3] P. Ketelitian, F. T. Industri, and U. I. Indonesia, “Mesin gurdi pahat jamak.”
- [4] A. Ilmi. 2014. “BAB II Teori Dasar” pp. 6–18, 2014. Surabaya.
- [5] K. Ummurani, S. Fathi, and I. Tanjung. 2021. “Barium Karbonat Terhadap Permukaan Pahat Bubut” vol. 2, no. 3, pp. 120–128.
- [6] A. Y. Nasution, S. Yulianto, and N. Ikhsan. 2018. “Implementasi Metode *Quality Control Circle* Untuk Peningkatan Kapasitas Produksi” vol. 12, no. 1, pp. 33–39.
- [7] S. Sibghatullah, M. dan Alam. 2015. “To Study The Surface Roughness And Chip Thickness During Machining Of Mild Steel (AISI-1008) Using Vegetable Based Oil As a Cutting Fluid”.
- [8] J. Mechanical dkk. 2013. “Penerapan Penilaian Kekasaran Permukaan (*Surface Roughness Assessment*) Berbasis Visi Pada Proses Pembubutan Baja S45C” vol. 4, pp. 22–29.
- [9] S. Harmanto. 2018. “Permukaan Bahan Aluminium , Kayu Jati , dan Mahoni,” vol. 50275.
- [10] I. Microscopes. 1997. “*Surface Roughness Measurement Parameters*” pp. 1–14.
- [11] B. Atedi, P. Kim, and S. Serpong. 2005. “Standar Kekasaran Permukaan Bidang Pada Yoke Flange Menurut Iso R.1302 dan Din 4768 dengan Memperhatikan Nilai Ketidakpastiannya” vol. 6, no. 2, pp. 63–69.

- 
- [12] I. S. Aisyah, Y. I. Widyawati, D. Kurniawati, T. Sewoyo, and P. V. Tanaman. 2018. "Investigasi Potensi Jarak Pagar" pp. 167–173.
- [13] J. C. E. García-Martínez, V. Miguel, A. Martínez-Martínez, M. C. Manjabacas. 2019. "*Sustainable Lubrication Methods for the Machining of Titanium Alloys: An Overview, Materials (Basel)*".
- [14] Arismunandar. Wiranto, and Kuchi. Tsuda. 2004. "Pemeliharaan Sistem Pendingin". Jakarta.
- [15] T. Rochim. 1993. "Teori dan Teknologi Proses Pemesinan" 2nd. Bandung.
- [16] Panjiades. 2017. "Minyak Nabati Sebagai Cutting Fluid Saat Proses Pemesinan". *Manufaktur dan Energi FT-UMSU*, vol. 3, no. 1, pp. 16–22.
- [17] I. Priyahapsara dkk. 2016. "Efektifitas Pahat Terhadap Jarak Potong.
- [18] I. Mikroselulosa, E. Gondok, M. Bleaching-alkalinasi, J. Hermayanti, R. Lailatul, and A. Amalia. 2019. "Isolasi Mikroselulosa dari Limbah Eceng Gondok (*Eichhornia crassipes*) dengan Metode Bleaching -Alkalinas".
- [19] Ahmed, A. F., Moahmed A, Abdel Naby. 2012. "*Pretreatment And Enzymic Saccharification Of Water Hyacinth Cellulose*".
- [20] M. Asrofi dkk. 2018. "*Isolation of Nanocellulose from Water Hyacinth Fiber (WHF) Produced via Digester-Sonication and Its Characterization*".
- [21] D. Rahmadiawan, H. Abral, N. Nasruddin, and Z. Fuadi. 2021. "*Stability, Viscosity, and Tribology Properties of Polyol Ester Oil-Based Biolubricant Filled with TEMPO-Oxidized Bacterial Cellulose Nanofiber*".
- [22] T. Mang and W. Dresel. 2007. "*Lubricants and Lubrication Edited by Theo Mang and Wilfried Dresel*".
- [23] M. Kamruzzaman and N. Dhar. 1970. "*The Effect of Applying High-Pressure Coolant (HPC) Jet in Machining of 42crmo4 Steel by Uncoated Carbide*

Inserts” J. Mech. Eng., vol. 39, no. 2, pp. 71–77.

- [24] E. E. Susanto. 2018. “Pengaruh Kekasaran Pemesinan Terhadap Kerusakan Permukaan Rol Pada Proses Pembuatan *Cooper Rod* Dengan Metode *Hot Roll*” vol. 9, no. September, pp. 30–37.

