

DAFTAR PUSTAKA

- [1] T. Rochim, *Teori dan Teknologi Proses Pemesinan*. Bandung : Institut Teknologi Bandung, 1993.
- [2] G. Kurimoto, B.L. and Barrow, "The influence of aqueous fluids on the wear characteristics and life of carbide cutting tools," *Ann. CIRP*, vol. Vol. 31 No, pp. 19-23., 1982.
- [3] T. H. C. Childs, "Friction modelling in metal cutting," *Wear*, vol. 260, no. 3, pp. 310–318, 2006, doi: 10.1016/j.wear.2005.01.052.
- [4] D. N. Rao and R. R. Srikant, "Influence of emulsifier content on cutting fluid properties," *Proc. Inst. Mech. Eng. Part B J. Eng. Manuf.*, vol. 220, no. 11, pp. 1803–1806, 2006, doi: 10.1243/09544054JEM564.
- [5] S. K. B. H. Bagchi, N.P. Mukharjee, "Investigation of metal cutting using molybdenum disulphide as a cutting fluid, *Industrial Lubrication and Tribology*," pp. 239–243, 1972.
- [6] S. K. B. G.S. Lathkar, "Clean Metal Cutting Process Using Solid Lubricants," *Narosa Pub., Madras*, pp. 15–31, 2000.
- [7] P. V. Krishna and D. N. Rao, "Performance evaluation of solid lubricants in terms of machining parameters in turning," vol. 48, pp. 1131–1137, 2008, doi: 10.1016/j.ijmachtools.2008.01.012.
- [8] U. Heisel and M. Lutz, "Application of minimum quantity cooling lubrication technology in cutting processes," *Prod. Eng. II*, pp. 49–54, 1994.
- [9] P. S. Paul and A. S. Varadarajan, "Performance evaluation of hard turning of AISI 4340 steel with minimal fluid application in the presence of semi-solid lubricants," vol. 227, no. 7, pp. 738–748, 2013, doi: 10.1177/1350650112468376.
- [10] A. R. Marta, "Prototype alat Feeder Grease untuk pengaplikasian Semi-Solid Lubricant pada Proses Pemesinan," Padang: Universitas Andalas, 2020.
- [11] ASM Metals Handbook, "Friction, Lubrication, Wear Technology," vol. 18.
- [12] T. A. Stolarski, "Tribology in Machine Design," 2000.
- [13] K. Meyer, "Book Review: Lubricants and Lubrication," *Ed. by Theo Mang Wilfried Dresel*, vol. 40, p. 20, 2001.

- [14] W. Bock, "Encyclopedia of Lubricants and Lubrication," 2014.
- [15] I. Justina and S. Modi, "Types of Lubrication Liquid (Mineral Oils , Synthetic Oils , and Vegetable Oils) Semi-Solid (Grease) Solid (Graphite , Molybdenum)," 2018.
- [16] A. K. T. A. K. Sharma, R. K. Singh, A. R. Dixit, "Novel uses of alumina-MoS₂ hybrid nanoparticle enriched cutting fluid in hard turning of AISI 304 steel," *J. Manuf. Process.*, vol. 30, pp. 467–482, 2017.
- [17] G. W. Stachowiak, "Engineering Tribology," 2005.
- [18] L. Shandong Futu Petrochemical Co, "Lithium Complex Grease With Molybdenum Disulfide (MoS₂)," 2018.
- [19] Peterson M B and Winer W O, "Wear control handbook," ASME, 1980.
- [20] Viktor P. Astakhov, "Metal Cutting Mechanics," in *1st Edition*, Engineering & Technology, Physical Sciences, 1998, p. 320. doi: <https://doi.org/10.1201/9781466571778>.
- [21] P. K. GUPTA, "An Investigation of Crater Wear of Cemented Carbide Tools," *M.Sc. Thesis, Massachusetts Inst. Technol.*, 1967.
- [22] Bailey JA, "Friction in metal machining—mechanical aspects," *Wear*, vol. 31, pp. 243–75, 1975.
- [23] Trent EM, *Metal cutting*. London: Butterworths, 1989.
- [24] J. Yan, Z. Zhang, and T. Kuriyagawa, "Effect of nanoparticle lubrication in diamond turning of reaction-bonded SiC," *Int. J. Autom. Technol.*, vol. 5, no. 3, pp. 307–312, 2011, doi: 10.20965/ijat.2011.p0307.
- [25] E. G. S. Satnam Singh, Er. Jasvinder Singh, "Automatic Lubrication System," vol. 4, no. 4, pp. 894–899, 2017.
- [26] NN 3, "Studi pengaruh panas pada hasil pengelasan baja ST37 ditinjau dari kekuatan tarik bahan," 2015.

