

## DAFTAR PUSTAKA

- [1] Amalia, "Penggunaan Drone untuk Tingkatkan Produksi," *www.lapan.go.id*, vol. 3, no. 2, pp. 110–115, 2021, doi: 10.21831/dinamika.v3i2.21407.
- [2] A. Bandyopadhyay and B. Heer, "Additive manufacturing of multi-material structures," *Materials Science and Engineering R: Reports*, vol. 129, no. April, pp. 1–16, 2018, doi: 10.1016/j.mser.2018.04.001.
- [3] H. Pristianyah, "Pengaruh Parameter 3D Printing Terhadap Transparansi Produk yang Dihasilkan," *Seminar Nasional Inovasi Teknologi*, vol. 6, pp. 181–186, 2018.
- [4] N. Naboulsi, T. Hachimi, F. Majid, R. Rhanim, N. Zekriti, and H. Rhanim, "Modeling and control of 3D filament extruder," *Procedia Structural Integrity*, vol. 33, no. C, pp. 989–995, 2021, doi: 10.1016/j.prostr.2021.10.109.
- [5] D. Yadav, D. Chhabra, R. K. Gupta, A. Phogat, and A. Ahlawat, "Modeling and analysis of significant process parameters of FDM 3D printer using ANFIS," *Materials Today: Proceedings*, vol. 21, pp. 1592–1604, 2020, doi: 10.1016/j.matpr.2019.11.227.
- [6] S. Maurya, B. Malik, P. Sharma, A. Singh, and R. Chalisgaonkar, "Investigation of different parameters of cube printed using PLA by FDM 3D printer," *Materials Today: Proceedings*, vol. 64, pp. 1217–1222, 2022, doi: 10.1016/j.matpr.2022.03.700.
- [7] A. L. Silva, G. M. da S. Salvador, S. V. F. Castro, N. M. F. Carvalho, and R. A. A. Munoz, "A 3D Printer Guide for the Development and Application of Electrochemical Cells and Devices," *Frontiers in Chemistry*, vol. 9, no. July, 2021, doi: 10.3389/fchem.2021.684256.
- [8] R. ADHIYATMA, "Perancangan dan Pembuatan Prototipe Terminal Listrik Eksternal T dengan Modul Timer Otomatis Menggunakan 3D," 2022, [Online]. Available: <https://dspace.uui.ac.id/handle/123456789/37822>

- [9] L. Miazio, "IMPACT OF PRINT SPEED ON STRENGTH," vol. 23, no. 2, pp. 33–38, 2019, doi: 10.1515/agriceng-2019-0014.
- [10] R. Patel, C. Desai, S. Kushwah, and M. H. Mangrola, "A review article on FDM process parameters in 3D printing for composite materials," *Materials Today: Proceedings*, vol. 60, pp. 2162–2166, 2022, doi: 10.1016/j.matpr.2022.02.385.
- [11] O. S. Carneiro, A. F. Silva, and R. Gomes, "Fused deposition modeling with polypropylene," *Materials and Design*, vol. 83, pp. 768–776, 2015, doi: 10.1016/j.matdes.2015.06.053.
- [12] S. B. F. Winarto, "Pengaruh suhu pada bottom plate terhadap produk printer 3D," pp. 12–26, 2015.
- [13] B. M. Law, "ANALISIS SIFAT MEKANIK MATERIAL KOMPOSIT DARI SERAT SABUT KELAPA," *The Musical Times*, vol. 126, no. 1712, p. 583, 1985, doi: 10.2307/964910.
- [14] E. Pollet, *Enviromental Silicate Nano-Biocomposites*. 2006. doi: 10.2174/97816080528511060101.
- [15] Y. Subakti, T. Mesin, and P. Manufaktur Negeri Bangka Belitung, "PENGARUH PARAMETER PROSES TERHADAP KEKUATAN TARIK FILAMEN ST-PLA MENGGUNAKAN METODE TAGUCHI," 2021, [Online]. Available: [www.primes3d.com](http://www.primes3d.com)
- [16] V. Bhaskara Sardi, S. Jokosisworo, and H. Yudo, "JURNAL TEKNIK PERKAPALAN Pengaruh Normalizing dengan Variasi Waktu Penahanan Panas (Holding Time) Baja ST 46 terhadap Uji Kekerasan, Uji Tarik, dan Uji Mikrografi," *Jurnal Teknik Perkapalan*, vol. 6, no. 1, p. 142, 2018, [Online]. Available: <http://ejournal3.undip.ac.id/index.php/naval>
- [17] Z. Yu *et al.*, "Study on Effects of FDM 3D Printing Parameters on Mechanical Properties of Polylactic Acid," *IOP Conference Series: Materials Science and Engineering*, vol. 688, no. 3, 2019, doi: 10.1088/1757-899X/688/3/033026.

- [18] R. D. Bintara, D. Z. Lubis, and Y. R. Aji Pradana, “The effect of layer height on the surface roughness in 3D Printed Polylactic Acid (PLA) using FDM 3D printing,” *IOP Conference Series: Materials Science and Engineering*, vol. 1034, no. 1, p. 012096, 2021, doi: 10.1088/1757-899x/1034/1/012096.
- [19] J. R. Stojković *et al.*, “An Experimental Study on the Impact of Layer Height and Annealing Parameters on the Tensile Strength and Dimensional Accuracy of FDM 3D Printed Parts,” *Materials*, vol. 16, no. 13, p. 4574, 2023, doi: 10.3390/ma16134574.

