

DAFTAR PUSTAKA

- [1] R. A. Ibrahim and C. L. Pettit, “Uncertainties and dynamic problems of bolted joints and other fasteners,” *J. Sound Vib.*, vol. 279, no. 3–5, pp. 857–936, 2005, doi: 10.1016/j.jsv.2003.11.064.
- [2] T. Sakai, “NII-Electronic Library Service,” *Chem. Pharm. Bull.*, vol. 3, no. 1, 1978.
- [3] J. X. Yuan and X. M. Wu, “Identification of the Joint Structural Parameters of Machine Tool by DOS and FEM,” *J. Manuf. Sci. Eng. Trans. ASME*, vol. 107, no. 1, pp. 64–69, 1985, doi: 10.1115/1.3185967.
- [4] Yoshimi and M. Tsutsumi, “Determination of mathematical models for normal static stiffness of joints,” *Chem. Pharm. Bull.*, no. 43, p. 2091, 2002, [Online]. Available: <http://www.mendeley.com/research/geology-volcanic-history-eruptive-style-yakedake-volcano-group-central-japan/>.
- [5] G. H. Junker, “New criteria for self-loosening of fasteners under vibration,” *SAE Tech. Pap.*, pp. 314–335, 1969, doi: 10.4271/690055.
- [6] N. G. Pai and D. P. Hess, “Influence of fastener placement on vibration-induced loosening,” *J. Sound Vib.*, vol. 268, no. 3, pp. 617–626, 2003, doi: 10.1016/S0022-460X(03)00369-9.
- [7] B. Kenny and E. A. Patterson, “Stress analysis of some nut-bolt connections with modifications to the nut thread form,” *J. Strain Anal. Eng. Des.*, vol. 20, no. 1, pp. 35–40, 1985, doi: 10.1243/03093247V201035.
- [8] C. Dekoninck, “Deformation properties of metallic contact surfaces of joints under the influence of dynamic tangential loads,” *Int. J. Mach. Tool Des. Res.*, vol. 12, no. 3, pp. 193–199, 1972, doi: 10.1016/0020-7357(72)90020-0.

- [9] M. Burdekin, N. Back, and A. Cowley, “Analysis of the Local Deformations in Machine Joints.,” *J Mech Eng Sci*, vol. 21, no. 1, pp. 25–32, 1979, doi: 10.1243/JMES_JOUR_1979_021_006_02.
- [10] F. Huda, I. Kajiwara, N. Hosoya, and S. Kawamura, “Bolt loosening analysis and diagnosis by non-contact laser excitation vibration tests,” *Mech. Syst. Signal Process.*, vol. 40, no. 2, pp. 589–604, 2013, doi: 10.1016/j.ymssp.2013.05.023.
- [11] F. Wang and G. Song, “Bolt early looseness monitoring using modified vibro-acoustic modulation by time-reversal,” *Mech. Syst. Signal Process.*, vol. 130, pp. 349–360, 2019, doi: 10.1016/j.ymssp.2019.04.036.
- [12] T. C. Huynh, J. H. Park, H. J. Jung, and J. T. Kim, “Quasi-autonomous bolt-loosening detection method using vision-based deep learning and image processing,” *Autom. Constr.*, vol. 105, no. February, p. 102844, 2019, doi: 10.1016/j.autcon.2019.102844.
- [13] H. Mirmanto and N. Ikhwan, “Analisis Performa Circulating Water Pump Pada Industri Pembangkitan (Studi Kasus PLTU Bolok NTT),” *Semin. Nas. Sains dan Teknol. Terap. IV*, no. ISBN 978-602-98569-1-0, pp. 247–254, 2016.
- [14] G. E. Ramey and R. C. Jenkins, “Experimental Analysis of Thread Movement in Bolted Connections Due to Vibrations,” *Nasa*, pp. 1–164, 1995.
- [15] M. Rusli, C. Mardianto, and M. Bur, “Experimental analysis of bolt loosening dynamics characteristic in a beam by impact testing,” *ARPJ Eng. Appl. Sci.*, vol. 13, no. 1, pp. 175–180, 2018.
- [16] M. Bur, *Dasar-dasar Getaran Mekanik*. Padang: CV. Ferila, 2012.
- [17] J. H. Bickford, “A Review of: ‘An Introduction to the Design and Behavior of Bolted Joints,’” *Mater. Manuf. Process.*, vol. 14, no. 3, pp. 457–458, 1999, doi: 10.1080/10426919908907576.
- [18] Butterworth Heinemann, *Modal Analysis*. India, 2001.

- [19] J. H. Zhi-Fang Fu, *Modal Analysis*. 2001.
- [20] W. A. Milek, “Development of New Specification for Structural Joints Using Astm a325 or a490 Bolts.,” pp. 28–21, 1986.
- [21] M. Z. Xuetong Liu, Xue Mi, Jianhua Liu, Laohu Long, Zhenbing Cai, Jiliang Mo, Jinfang Peng, “Axial load distribution and self-loosening behavior of bolted joints subjected to torsional excitation, Engineering Failure Analysis,” *Axial load Distrib. self-loosening Behav. bolted joints Subj. to torsional Excit. Eng. Fail. Anal.*, vol. Volume 119, no. ISSN 1350-6307, p. 104985, 2021, doi: <https://doi.org/10.1016/j.engfailanal.2020.104985>.
- [22] R. Maksum. M. Rusli, M. Bur, “The Analysis of Loosening of Bolt Connection Due to Structural Vibration Through Changes in Dynamic Characteristics,” “*The Anal. Loosening Bolt Connect. Due to Struct. Vib. Through Chang. Dyn. Charact.*,” no. Vol 16 No 1 (2023): Jurnal Teknik Mesin, 2023, doi: <https://doi.org/10.30630/jtm.16.1.1091>.
- [23] W. Du, W. Li, S. Jiang, L. Sheng, and Y. Wang, “Nonlinear torsional vibration analysis of shearer semi-direct drive cutting transmission system subjected to multi-frequency load excitation,” *Nonlinear Dyn.*, vol. 111, no. 5, pp. 4071–4086, 2023, doi: 10.1007/s11071-022-08041-x.
- [24] N.M. Kinkaid, O.M. O'Reilly, P. Papadopoulos, Automotive disc brake squeal, *Journal of Sound and Vibration*, Volume 267, Issue 1, 2003, Pages 105-166, ISSN 0022-460X, [https://doi.org/10.1016/S0022-460X\(02\)01573-0](https://doi.org/10.1016/S0022-460X(02)01573-0).