

DAFTAR PUSTAKA

- [1] I. Idrissu, Z. Lv, and S. M. Rowland, "The dynamic character of partial discharge in epoxy resin at different stages of treeing," *Proc. 2016 IEEE Int. Conf. Dielectr. ICD 2016*, vol. 2, no. Mpd 600, pp. 728–731, 2016.
- [2] F. Rozi and U. Khayam, "Development of loop antennas for partial discharge detection," *Int. J. Electr. Eng. Informatics*, vol. 7, no. 1, pp. 29–41, 2015.
- [3] E. Akustik and K. Silikon, "Karakteristik Peluahan Sebagian (Partial Discharge) Pada Isolasi Karet Silikon (Silicone Rubber) Menggunakan Sensor."
- [4] E. Kuffel, W. S. Zaengl, and J. Kuffel, "High Voltage Engineering, Fundamentals," *High Volt. Eng.*, vol. 1, no. c, p. 552, 2001.
- [5] J. S. Panjaitan, H. H. Sinaga, and N. Purwasih, "Analisis Peluahan Sebagian di Udara Menggunakan Metode Elektromagnetik," *Electrician*, vol. 8, no. 3, 2014.
- [6] E. P. Waldi, A. Aulia, A. Hazmi, H. Abral, S. Arief, and M. H. Ahmad, "An optimized method of partial discharge data retrieval technique for phase resolved pattern," *TELKOMNIKA (Telecommunication Comput. Electron. Control.)*, vol. 14, no. 1, p. 21, 2016.
- [7] A. Elfaraskoury, M. Mokhtar, M. Mehanna, and O. Gouda, "Conventional and Un-Conventional Partial Discharge Detection Methods in High Voltage XLPE Cable Accessories," *Adv. Electr. Eng. Syst.*, vol. 1, no. 4, pp. 170–176, 2012.
- [8] D. A. Sulistyanto, Hermawan, and A. Syukur, "Analisis Arus Bocor Dan Tegangan Flashover Pada Polimer Resin Epoksi Silane Silika," *Transient*, vol. 1, no. 4, pp. 228–234, 2012.
- [9] J. Ardila-Rey *et al.*, "Behavior of an Inductive Loop Sensor in the Measurement of Partial Discharge Pulses with Variations in Its Separation from the Primary Conductor," *Sensors*, vol. 18, no. 7, p. 2324, 2018.

- [10] L. R. Syahputra, H. H. Sinaga, and Y. Martin, "Pendeteksian Beragam Sumber Peluahan Sebagian dengan Menggunakan Metode Elektromagnetik," *Electrician*, vol. 8, no. 3, 2014.



- [11] E. P. Waldi *et al.*, “Automatic threshold of standard deviation to reject noise in raw data of partial discharges,” *ARN J. Eng. Appl. Sci.*, vol. 12, no. 18, pp. 5319–5324, 2017.
- [12] M. E. Ibrahim and A. M. Abd-Elhady, “Power frequency AC voltage measurement based on double wound Rogowski coil,” *High Volt.*, vol. 2, no. 2, pp. 129–135, 2017.
- [13] M. Shafiq, M. Lehtonen, L. K?tt, G. A. Hussain, and M. Hashmi, “Effect of terminating resistance on high frequency behaviour of rogowski coil for transient measurements,” *Elektron. ir Elektrotehnika*, vol. 19, no. 7, pp. 22–28, 2013.

