

DAFTAR PUSTAKA

- [1] F. Chegiani *et al.*, “Fiber type effect on tribological behavior when cutting natural fiber reinforced plastics To cite this version : HAL Id : hal-01172039 Science Arts & Métiers (SAM),” 2015.
- [2] J. Y. Sheikh-Ahmad, “Machining of Polymer Composites”.
- [3] J. Suthar and K. Patel, “Tool wear and chip formation analysis of aluminium hybrid metal matrix composite,” *Mater. Today Proc.*, vol. 32, no. xxxx, pp. 422–430, 2019, doi: 10.1016/j.matpr.2020.02.126.
- [4] O. Özbek and H. Saruhan, “The effect of vibration and cutting zone temperature on surface roughness and tool wear in eco-friendly MQL turning of AISI D2,” *J. Mater. Res. Technol.*, vol. 9, no. 3, pp. 2762–2772, 2020, doi: 10.1016/j.jmrt.2020.01.010.
- [5] A. Langella, L. Nele, and A. Maio, “A torque and thrust prediction model for drilling of composite materials,” *Compos. Part A Appl. Sci. Manuf.*, vol. 36, no. 1, pp. 83–93, 2005, doi: 10.1016/j.compositesa.2004.06.024.
- [6] A. Uysal, M. Altan, and E. Altan, “Effects of cutting parameters on tool wear in drilling of polymer composite by Taguchi method,” *Int. J. Adv. Manuf. Technol.*, vol. 58, no. 9–12, pp. 915–921, 2012, doi: 10.1007/s00170-011-3464-6.
- [7] S. Jain and D. C. H. Yang, “Delamination-free drilling of composite laminates,” *J. Manuf. Sci. Eng. Trans. ASME*, vol. 116, no. 4, pp. 475–481, 1994, doi: 10.1115/1.2902131.
- [8] H. Hocheng and C. C. Tsao, “Effects of special drill bits on drilling-induced delamination of composite materials,” vol. 46, pp. 1403–1416, 2006, doi: 10.1016/j.ijmachtools.2005.10.004.
- [9] M. Ramesh, K. Palanikumar, and K. H. Reddy, “Experimental Investigation and Analysis of Machining Characteristics in Drilling Hybrid Glass-Sisal-Jute Fiber Reinforced Polymer Composites Experimental Investigation and Analysis of Machining Characteristics in Drilling Hybrid Glass-Sisal-Jute Fiber Rei,” *5th Int. 26th All India Manuf. Technol. Des. Res. Conf. (AIMTDR 2014)*, no. December, pp. 461(1–6), 2014.
- [10] P. K. Bajpai and I. Singh, “Drilling behavior of sisal fiber-reinforced polypropylene composite laminates,” *J. Reinf. Plast. Compos.*, vol. 32, no. 20, pp. 1569–1576, 2013, doi: 10.1177/0731684413492866.
- [11] C. C. Tsao and Y. C. Chiu, “Evaluation of drilling parameters on thrust force in drilling carbon fiber reinforced plastic (CFRP) composite laminates using compound core-special drills,” *Int. J. Mach. Tools Manuf.*, vol. 51, no. 9, pp. 740–744, 2011, doi: 10.1016/j.ijmachtools.2011.05.004.
- [12] A. N. Dahlen, H. Ascroft, and S. Barnes, “The Effect of Varying Cutting Speeds on Tool Wear during Conventional and Ultrasonic Assisted Drilling (UAD) of Carbon Fibre Composite (CFC) and Titanium Alloy Stacks,”

- Procedia CIRP*, vol. 46, pp. 420–423, 2016, doi: 10.1016/j.procir.2016.04.044.
- [13] R. John, R. Lin, K. Jayaraman, and D. Bhattacharyya, “Modified Taylor ’ s equation including the effects of fiber characteristics on tool wear when machining natural fiber composites,” vol. 469, no. December 2020, 2021.
- [14] Y. Bai, Z. Jia, R. Fu, J. Hao, and F. Wang, “Mechanical model for predicting thrust force with tool wear effects in drilling of unidirectional CFRP,” *Compos. Struct.*, vol. 262, no. May 2020, p. 113601, 2021, doi: 10.1016/j.compstruct.2021.113601.
- [15] J. M. Mathews, “The United States Department of State,” *Mich. Law Rev.*, vol. 17, no. 7, p. 553, 1919, doi: 10.2307/1276826.
- [16] K. B. Goutham, N. Tom, and L. Vijayaraghavan, “Materials Today : Proceedings Delamination and tool wear in drilling of carbon fabric reinforced epoxy composite laminate,” *Mater. Today Proc.*, no. xxxx, 2021, doi: 10.1016/j.matpr.2021.06.030.
- [17] J. Fernández-Pérez, J. L. Cantero, J. Díaz-Álvarez, and M. H. Miguélez, “Tool wear and induced damage in CFRP drilling with step and double point angle drill bits,” *Procedia Manuf.*, vol. 41, pp. 610–617, 2019, doi: 10.1016/j.promfg.2019.09.049.
- [18] J. Xu, T. Lin, J. P. Davim, M. Chen, and M. El Mansori, “Wear behavior of special tools in the drilling of CFRP composite laminates,” *Wear*, vol. 476, no. February, p. 203738, 2021, doi: 10.1016/j.wear.2021.203738.
- [19] M. Senthilkumar, A. Prabukarthi, and V. Krishnaraj, “Study on Tool Wear and Chip Formation during Drilling Carbon Fiber Reinforced Polymer (CFRP)/ Titanium Alloy (Ti6Al4V) Stacks,” *Procedia Eng.*, vol. 64, pp. 582–592, 2013, doi: 10.1016/j.proeng.2013.09.133.
- [20] D. S. Raj and L. Karunamoorthy, “A new and comprehensive characterisation of tool wear in CFRP drilling using micro-geometry and topography studies on the cutting edge,” *Journal of Manufacturing Processes*, vol. 32, pp. 839–856, 2018. doi: 10.1016/j.jmapro.2018.04.014.
- [21] A. Hrechuk and R. Wernke, “ScienceDirect ScienceDirect ScienceDirect Experimental investigations into tool wear of drilling Experimental investigations into wear of drilling,” *Procedia Manuf.*, vol. 25, pp. 294–301, 2018, doi: 10.1016/j.promfg.2018.06.086.
- [22] K. Debnath, *Drilling of composite laminates using a special tool point geometry*. Elsevier Ltd., 2019. doi: 10.1016/b978-0-08-102397-6.00005-2.
- [23] R. K. Bhushan, “Optimization of tool wear parameters in machining AA7075/SiC composite,” *Compos. Part C Open Access*, vol. 2, no. May, p. 100035, 2020, doi: 10.1016/j.jcomc.2020.100035.
- [24] D. A. Porwanto and L. Johar, “Karakterisasi komposit berpenguat serat bambu dan serat gelas sebagai alternatif bahan baku industri,” *J. Tek. Fis.*

ITS, pp. 1–16, 2008.

- [25] V. Fraction, O. N. The, M. Properties, O. F. Composite, and M. Polyester, “Analisis Variasi Panjang Serat Dan Fraksi Volume Terhadap Sifat Mekanik Material Komposit Polyester Yang (Variation Analysis of Fiber Length and Volume Fraction on the,” pp. 1–4.
- [26] N. O. T. Measurement, “HANDBOOK COMPOSITE MATERIALS HANDBOOK VOLUME 1 . POLYMER MATRIX COMPOSITES GUIDELINES FOR CHARACTERIZATION,” vol. 1, no. June, 2002.
- [27] I. M. Astika, “Analisa Delaminasi Pada Glass Fiber Reinforced Polymer Komposit Laminat Dengan Pembebanan Fatigue,” *Din. Tek. Mesin*, vol. 2, no. 1, pp. 7–14, 2012, doi: 10.29303/d.v2i1.106.
- [28] D. B. Setiawan, M. I. P. Hidayat, and W. Widyastuti, “Simulasi Delaminasi pada Komposit Glass Fiber-reinforced Polymer (GFRP) dan Carbon Fiber-reinforced Polymer Menggunakan Metode Cohesive Zone Model (CZM) dan Virtual Crack Closure Technique (VCCT),” *J. Tek. ITS*, vol. 9, no. 1, pp. 1–6, 2020, doi: 10.12962/j23373539.v9i1.50322.
- [29] A. D’Orazio, M. El Mehtedi, A. Forcellese, A. Nardinocchi, and M. Simoncini, “Tool wear and hole quality in drilling of CFRP/AA7075 stacks with DLC and nanocomposite TiAlN coated tools,” *J. Manuf. Process.*, vol. 30, pp. 582–592, 2017, doi: 10.1016/j.jmapro.2017.10.019.
- [30] S. Gaugel *et al.*, “A comparative study on tool wear and laminate damage in drilling of carbon-fiber reinforced polymers (CFRP),” *Composite Structures*, vol. 155, pp. 173–183, 2016. doi: 10.1016/j.compstruct.2016.08.004.
- [31] M. K. Nor Khairusshima, C. H. Che Hassan, A. G. Jaharah, A. K. M. Amin, and A. N. Md Idriss, “Effect of chilled air on tool wear and workpiece quality during milling of carbon fibre-reinforced plastic,” *Wear*, vol. 302, no. 1–2, pp. 1113–1123, 2013, doi: 10.1016/j.wear.2013.01.043.
- [32] B. Yenigun and E. Kilickap, “Influence of hole quality on fatigue life of drilled CFRP with the different ply orientation angle,” *J. Brazilian Soc. Mech. Sci. Eng.*, vol. 43, no. 1, pp. 1–14, 2021, doi: 10.1007/s40430-020-02719-2.
- [33] J. F. Pérez, J. L. Cantero, J. D. Álvarez, and M. H. Miguélez, “in composite aerospace components drilling,” *Compos. Struct.*, 2017, doi: 10.1016/j.compstruct.2017.06.043.
- [34] K. Giasin, G. Gorey, C. Byrne, J. Sinke, and E. Brousseau, “Effect of machining parameters and cutting tool coating on hole quality in dry drilling of fibre metal laminates,” *Compos. Struct.*, vol. 212, no. November 2018, pp. 159–174, 2019, doi: 10.1016/j.compstruct.2019.01.023.
- [35] I. S. Shyha *et al.*, “International Journal of Machine Tools & Manufacture Hole quality assessment following drilling of metallic-composite stacks,” *Int. J. Mach. Tools Manuf.*, vol. 51, no. 7–8, pp. 569–578, 2011, doi:

10.1016/j.ijmachtools.2011.04.007.

- [36] J. T. Mesin, F. Teknik, and U. S. Kuala, "PENGARUH JENIS SERAT TERHADAP KUALITAS HASIL PEMESINAN BAHAN KOMPOSIT," no. Snttm Xiv, pp. 7–8, 2015.
- [37] S. Rawat and H. Attia, "Wear mechanisms and tool life management of WC-Co drills during dry high speed drilling of woven carbon fibre composites," *Wear*, vol. 267, no. 5–8, pp. 1022–1030, 2009, doi: 10.1016/j.wear.2009.01.031.
- [38] J. Fernández-Pérez, J. L. Cantero, J. Díaz-Álvarez, and M. H. Miguélez, "Influence of cutting parameters on tool wear and hole quality in composite aerospace components drilling," *Compos. Struct.*, vol. 178, pp. 157–161, 2017, doi: 10.1016/j.compstruct.2017.06.043.
- [39] M. S. Kumar, A. Prabukarthi, and V. Krishnaraj, "Study on tool wear and chip formation during drilling carbon fiber reinforced polymer (CFRP)/titanium alloy (Ti6Al4V) stacks," *Procedia Eng.*, vol. 64, pp. 582–592, 2013, doi: 10.1016/j.proeng.2013.09.133.
- [40] P. V., "MRI Process Improvement," *Int. J. Res. Appl. Sci. Eng. Technol.*, vol. 8, no. 8, pp. 727–731, 2020, doi: 10.22214/ijraset.2020.30997.
- [41] C. Envisions, K. Hub, and I. C. Information, "Practical and Insightful Composites Information How To Keep Weave," 2022.
- [42] J. Fernández-Pérez, C. Domínguez-Monferrer, M. H. Miguélez, and J. L. Cantero, "Analysis of Tool Wear and Hole Delamination for Large-Diameter Drilling of CFRP Aircraft Fuselage Components: Identifying Performance Improvement Drivers and Optimization Opportunities," *J. Manuf. Mater. Process.*, vol. 7, no. 2, 2023, doi: 10.3390/jmmp7020076.
- [43] M. Ben Meftah, H. Khlifi, B. Gassara, M. Baili, G. Desein, and W. Bouzid, *Cycle time and hole quality in drilling canned cycle*, no. May. Springer International Publishing, 2019. doi: 10.1007/978-3-030-19781-0_11.
- [44] D. O'Sullivan and M. Cotterell, "Temperature measurement in single point turning," *J. Mater. Process. Technol.*, vol. 118, no. 1–3, pp. 301–308, 2001, doi: 10.1016/S0924-0136(01)00853-6.
- [45] S. T. Steel, "Metal drill bits," 1897.
- [46] A. Zhang, S. Zhang, C. Bian, and H. Kong, "Modified Chip-Evacuation Force Modeling and Chip-Clogging Prediction in Drilling of Cortical Bone," *IEEE Access*, vol. 7, pp. 180671–180683, 2019, doi: 10.1109/ACCESS.2019.2958428.
- [47] I. S. Shyha, D. K. Aspinwall, S. L. Soo, and S. Bradley, "Drill geometry and operating effects when cutting small diameter holes in CFRP," *Int. J. Mach. Tools Manuf.*, vol. 49, no. 12–13, pp. 1008–1014, 2009, doi: 10.1016/j.ijmachtools.2009.05.009.