

DAFTAR PUSTAKA

- [1] F. Chegdani, S. Mezghani, M. El Mansori, and A. Mkaddem, "Fiber type effect on tribological behavior when cutting natural fiber reinforced plastics," *Wear*, vol. 332–333, pp. 772–779, 2015, doi: 10.1016/j.wear.2014.12.039.
- [2] L. Mullen, "Applications Of," *Chicago Rev.*, vol. 46, no. 2, p. 67, 2000, doi: 10.2307/25304499.
- [3] J. Y. Sheikh-Ahmad, "Machining of Polymer Composites".
- [4] R. E. P. and K. . R. D.P.Bartholomew, *The Pineapple, Botany, Production and Uses*.
- [5] D. N. Saheb and J. P. Jog, "Natural Fiber Polymer Composites : A Review," vol. 18, no. 4, pp. 351–363, 1999.
- [6] B. Yenigun and E. Kilickap, "Influence of hole quality on fatigue life of drilled CFRP with the different ply orientation angle," *J. Brazilian Soc. Mech. Sci. Eng.*, vol. 43, no. 1, pp. 1–14, 2021, doi: 10.1007/s40430-020-02719-2.
- [7] V. Nizev, O. Polushkin, S. Kireev, and V. Stepanov, "Fatigue Strength of an Aircraft Wing Panel with a Repair Patch Based on the Filled Hole at Various Values of Interference Fit Based on the Filled Hole at Various Values of Interference Fit TransSiberia 2020 Conference," *Transp. Res. Procedia*, vol. 54, no. 2020, pp. 150–156, 2021, doi: 10.1016/j.trpro.2021.02.059.
- [8] C. Icme *et al.*, "Roughness composite materials : characterization of Roughness of composite materials : characterization of hole hole quality quality in in drilling Al / CFRP stacks . drilling of of A new methodology to analyze the Al / CFRP functional and physical archit," *Procedia CIRP*, vol. 88, pp. 473–478, 2019, doi: 10.1016/j.procir.2020.05.082.
- [9] A. Langella, L. Nele, and A. Maio, "A torque and thrust prediction model for drilling of composite materials," *Compos. Part A Appl. Sci. Manuf.*, vol. 36, no. 1, pp. 83–93, 2005, doi: 10.1016/j.compositesa.2004.06.024.
- [10] "Machining of Carbon Fibre Reinforced Plastics," *Procedia CIRP*, vol. 24, no. C, pp. 19–24, 2014. doi: 10.1016/j.procir.2014.07.135.
- [11] C. C. Tsao and H. Hocheng, "The effect of chisel length and associated pilot hole on delamination when drilling composite materials," *Int. J. Mach. Tools Manuf.*, vol. 43, no. 11, pp. 1087–1092, 2003, doi: 10.1016/S0890-6955(03)00127-5.
- [12] S. Jain and D. C. H. Yang, "Delamination-free drilling of composite laminates," *J. Manuf. Sci. Eng. Trans. ASME*, vol. 116, no. 4, pp. 475–481, 1994, doi: 10.1115/1.2902131.
- [13] H. Hocheng and C. C. Tsao, "Effects of special drill bits on drilling-induced delamination of composite materials," vol. 46, pp. 1403–1416, 2006, doi: 10.1016/j.ijmachtools.2005.10.004.
- [14] M. Ramesh, K. Palanikumar, and K. H. Reddy, "Experimental Investigation and Analysis of Machining Characteristics in Drilling Hybrid Glass-Sisal-Jute Fiber Reinforced Polymer Composites Experimental Investigation and Analysis of Machining Characteristics in Drilling Hybrid Glass-Sisal-Jute Fiber Rei," *5th Int.*

26th All India Manuf. Technol. Des. Res. Conf. (AIMTDR 2014), no. December, pp. 461(1–6), 2014.

- [15] P. K. Bajpai and I. Singh, “Drilling behavior of sisal fiber-reinforced polypropylene composite laminates,” *J. Reinf. Plast. Compos.*, vol. 32, no. 20, pp. 1569–1576, 2013, doi: 10.1177/0731684413492866.
- [16] C. C. Tsao and Y. C. Chiu, “Evaluation of drilling parameters on thrust force in drilling carbon fiber reinforced plastic (CFRP) composite laminates using compound core-special drills,” *Int. J. Mach. Tools Manuf.*, vol. 51, no. 9, pp. 740–744, 2011, doi: 10.1016/j.ijmachtools.2011.05.004.
- [17] S. T. Steel, “Metal drill bits,” 1897.
- [18] C. C. Tsao, “Investigation into the effects of drilling parameters on delamination by various step-core drills,” *J. Mater. Process. Technol.*, vol. 206, no. 1–3, pp. 405–411, 2008, doi: 10.1016/j.jmatprotec.2007.12.057.
- [19] M. P. Ho *et al.*, “Critical factors on manufacturing processes of natural fibre composites,” *Compos. Part B Eng.*, vol. 43, no. 8, pp. 3549–3562, 2012, doi: 10.1016/j.compositesb.2011.10.001.
- [20] S. Vyas, E. Goli, X. Zhang, and P. H. Geubelle, “Manufacturing of unidirectional glass-fiber-reinforced composites via frontal polymerization: A numerical study,” *Compos. Sci. Technol.*, vol. 184, no. August, p. 107832, 2019, doi: 10.1016/j.compscitech.2019.107832.
- [21] N. Shukla and G. L. Devnani, “A review on mechanical properties of hybrid natural fiber polymer composites,” *Mater. Today Proc.*, vol. 45, pp. 4702–4705, 2021, doi: 10.1016/j.matpr.2021.01.122.
- [22] D. A. Porwanto and L. Johar, “Karakterisasi komposit berpenguat serat bambu dan serat gelas sebagai alternatif bahan baku industri,” *J. Tek. Fis. ITS*, pp. 1–16, 2008.
- [23] V. Fraction, O. N. The, M. Properties, O. F. Composite, and M. Polyester, “Analisis Variasi Panjang Serat Dan Fraksi Volume Terhadap Sifat Mekanik Material Komposit Polyester Yang (Variation Analysis of Fiber Length and Volume Fraction on the,” pp. 1–4.
- [24] K. Oksman, M. Skrifvars, and J. F. Selin, “Natural fibres as reinforcement in polylactic acid (PLA) composites,” *Compos. Sci. Technol.*, vol. 63, no. 9, pp. 1317–1324, 2003, doi: 10.1016/S0266-3538(03)00103-9.
- [25] K. Debnath, *Drilling of composite laminates using a special tool point geometry*. Elsevier Ltd., 2019. doi: 10.1016/b978-0-08-102397-6.00005-2.
- [26] D. B. Setiawan, M. I. P. Hidayat, and W. Widyastuti, “Simulasi Delaminasi pada Komposit Glass Fiber-reinforced Polymer (GFRP) dan Carbon Fiber-reinforced Polymer Menggunakan Metode Cohesive Zone Model (CZM) dan Virtual Crack Closure Technique (VCCT),” *J. Tek. ITS*, vol. 9, no. 1, pp. 1–6, 2020, doi: 10.12962/j23373539.v9i1.50322.
- [27] M. S. Kumar, A. Prabukarthi, and V. Krishnaraj, “Study on tool wear and chip formation during drilling carbon fiber reinforced polymer (CFRP)/titanium alloy (Ti6Al4V) stacks,” *Procedia Engineering*, vol. 64, pp. 582–592, 2013. doi: 10.1016/j.proeng.2013.09.133.

- [28] J. Suthar and K. Patel, "Tool wear and chip formation analysis of aluminium hybrid metal matrix composite," *Mater. Today Proc.*, vol. 32, no. xxxx, pp. 422–430, 2019, doi: 10.1016/j.matpr.2020.02.126.
- [29] J. Fernández-Pérez, J. L. Cantero, J. Díaz-Álvarez, and M. H. Miguélez, "Tool wear and induced damage in CFRP drilling with step and double point angle drill bits," *Procedia Manuf.*, vol. 41, pp. 610–617, 2019, doi: 10.1016/j.promfg.2019.09.049.
- [30] Y. Bai, Z. Jia, R. Fu, J. Hao, and F. Wang, "Mechanical model for predicting thrust force with tool wear effects in drilling of unidirectional CFRP," *Compos. Struct.*, vol. 262, no. May 2020, p. 113601, 2021, doi: 10.1016/j.compstruct.2021.113601.
- [31] Z. Abidin, "Mekanisme Keausan Pahat Pada Proses Pemesinan: Sebuah Tinjauan Pustaka," *J. Momentum UNWAHAS*, vol. 6, no. 1, p. 114105, 2010.
- [32] K. B. Goutham, N. Tom, and L. Vijayaraghavan, "Materials Today : Proceedings Delamination and tool wear in drilling of carbon fabric reinforced epoxy composite laminate," *Mater. Today Proc.*, no. xxxx, 2021, doi: 10.1016/j.matpr.2021.06.030.
- [33] H. Sunardi, A. Zainuri, and A. D. Catur, "PENGARUH TAHAPAN PROSES PELUBANGAN DAN ARAH SERAT TERHADAP KEKUATAN TARIK MATERIAL KOMPOSIT POLYESTER -PANDAN WANGI Heri Sunardi, Achmad Zainuri, Agus Dwi Catur Jurusan Teknik Mesin, Universitas Mataram," vol. 3, no. 1, pp. 1–9, 2013.
- [34] S. Y. Park, W. J. Choi, C. H. Choi, and H. S. Choi, "Effect of drilling parameters on hole quality and delamination of hybrid GLARE laminate," *Compos. Struct.*, vol. 185, pp. 684–698, 2018, doi: 10.1016/j.compstruct.2017.11.073.
- [35] N. Venkateshwaran and A. ElayaPerumal, "Hole quality evaluation of natural fiber composite using image analysis technique," *J. Reinf. Plast. Compos.*, vol. 32, no. 16, pp. 1188–1197, 2012, doi: 10.1177/0731684413486847.
- [36] U. Heisel and T. Pfeifroth, "Influence of point angle on drill hole quality and machining forces when drilling CFRP," *Procedia CIRP*, vol. 1, no. 1, pp. 471–476, 2012, doi: 10.1016/j.procir.2012.04.084.
- [37] G. S. Samy and S. T. Kumaran, "Measurement and analysis of temperature, thrust force and surface roughness in drilling of AA (6351)-B4C composite," *Meas. J. Int. Meas. Confed.*, vol. 103, no. 6351, pp. 1–9, 2017, doi: 10.1016/j.measurement.2017.02.016.
- [38] A. N. Dahnel, H. Ascroft, and S. Barnes, "The Effect of Varying Cutting Speeds on Tool Wear during Conventional and Ultrasonic Assisted Drilling (UAD) of Carbon Fibre Composite (CFC) and Titanium Alloy Stacks," *Procedia CIRP*, vol. 46, pp. 420–423, 2016, doi: 10.1016/j.procir.2016.04.044.
- [39] J. Fernández-Pérez, J. L. Cantero, J. Díaz-Álvarez, and M. H. Miguélez, "Influence of cutting parameters on tool wear and hole quality in composite aerospace components drilling," *Composite Structures*, vol. 178, pp. 157–161, 2017. doi: 10.1016/j.compstruct.2017.06.043.
- [40] E. D. Eneyew and M. Ramulu, "Hole Surface Quality and Damage when Drilling Unidirectional CFRP Composites," pp. 1–9, 2016.

- [41] S. A. Ashrafi, S. Sharif, M. Y. Yahya, and A. Davoudinejad, "Assessment of hole quality and thrust force when drilling CFRP/Al stack using carbide tools," *Appl. Mech. Mater.*, vol. 234, pp. 28–33, 2012, doi: 10.4028/www.scientific.net/AMM.234.28.
- [42] M. Helmi Abdul Kudus, M. M. Ratnam, and H. M. Akil, "Factors affecting hole quality during drilling of natural fiber-reinforced composites: A comprehensive review," *J. Reinf. Plast. Compos.*, vol. 40, no. 9–10, pp. 391–405, 2021, doi: 10.1177/0731684420970650.
- [43] A. Hrechuk, V. Bushlya, and J. E. Stahl, "Hole-quality evaluation in drilling fiber-reinforced composites," *Compos. Struct.*, vol. 204, no. July, pp. 378–387, 2018, doi: 10.1016/j.compstruct.2018.07.105.
- [44] K. Giasin *et al.*, "The effects of through tool cryogenic machining on the hole quality in GLARE® fibre metal laminates," *J. Manuf. Process.*, vol. 64, no. October 2020, pp. 996–1012, 2021, doi: 10.1016/j.jmapro.2021.02.010.
- [45] H. Noura and P. Bourdet, "Evaluation of roundness error using a new method based on a small displacement screw," *Meas. Sci. Technol.*, vol. 25, no. 4, 2014, doi: 10.1088/0957-0233/25/4/044012.
- [46] gdandtbasics, "Cylindricity," *Gdandtbasics.Com/Cylindricity*, 2014.
- [47] B. Singaravel, M. Radhika, M. Mohammed Asif, and K. P. Reddy, "Analysis of hole quality errors in drilling of GFRP composite," *IOP Conf. Ser. Mater. Sci. Eng.*, vol. 1057, no. 1, p. 012069, 2021, doi: 10.1088/1757-899x/1057/1/012069.
- [48] M. Ben Meftah, H. Khelifi, B. Gassara, M. Baili, G. Desein, and W. Bouzid, *Cycle time and hole quality in drilling canned cycle*, no. May. Springer International Publishing, 2019. doi: 10.1007/978-3-030-19781-0_11.
- [49] A. Islam and V. K. Dwivedi, "Effect of drilling speed, bit size and cooling medium on the burr structure for mild steel," *Mater. Today Proc.*, vol. 28, no. xxxx, pp. 1407–1411, 2020, doi: 10.1016/j.matpr.2020.04.812.
- [50] J. Xu, M. Ji, M. Chen, and M. El Mansori, "Experimental investigation on drilling machinability and hole quality of CFRP/Ti6Al4V stacks under different cooling conditions," *Int. J. Adv. Manuf. Technol.*, vol. 109, no. 5–6, pp. 1527–1539, 2020, doi: 10.1007/s00170-020-05742-8.
- [51] M. Ben Meftah, H. Khelifi, B. Gassara, M. Baili, G. Desein, and W. Bouzid, *Cycle time and hole quality in drilling canned cycle*, no. October 2020. Springer International Publishing, 2019. doi: 10.1007/978-3-030-19781-0_11.
- [52] A. Uysal, M. Altan, and E. Altan, "Effects of cutting parameters on tool wear in drilling of polymer composite by Taguchi method," *Int. J. Adv. Manuf. Technol.*, vol. 58, no. 9–12, pp. 915–921, 2012, doi: 10.1007/s00170-011-3464-6.
- [53] Y. B. Guo and Y. K. Chou, "The determination of ploughing force and its influence on material properties in metal cutting," *J. Mater. Process. Technol.*, vol. 148, no. 3, pp. 368–375, 2004, doi: 10.1016/j.jmatprotec.2004.02.052.
- [54] A. Eltaggaz and I. Deiab, "Comparison of between direct and peck drilling for large aspect ratio in Ti-6Al-4V alloy," *Int. J. Adv. Manuf. Technol.*, vol. 102, no. 9–12, pp. 2797–2805, 2019, doi: 10.1007/s00170-019-03314-z.
- [55] GD&T Basics, "Cylindricity | GD&T Basics." 2014. [Online]. Available:

<https://www.gdandtbasics.com/cylindricity/>

- [56] “Cylindricity (GD&T) Explained _ Fractory.”
- [57] “What is Cylindricity & Difference Between Circularity and Cylindricity _ How to Measure Cylindricity _ Dajin Precision.”
- [58] G. Vinoth and G. Bharathiraja, “The effects of feed and spindle speed on the cylinder diameter tolerance of Al6061HYBRID Metal Matrix Composite Reinforced with 15 % Weight Fraction of B4C and Fly Ash,” vol. 10, pp. 753–761, 2023.
- [59] A. H. Ghasemi, A. M. Khorasani, and I. Gibson, “Investigation on the effect of a pre-center drill hole and tool material on thrust force, surface roughness, and cylindricity in the drilling of Al7075,” *Materials (Basel)*, vol. 11, no. 1, 2018, doi: 10.3390/ma11010140.
- [60] L. A. Mihail, “Robust engineering of deep drilling process by surface state optimization,” *Procedia CIRP*, vol. 8, no. December 2013, pp. 582–587, 2013, doi: 10.1016/j.procir.2013.06.154.
- [61] “Advantages and Disadvantages Machining Processes.”
- [62] L. Nele, A. Caggiano, and I. Improta, “Machining of composite materials,” *Fiber Reinf. Compos. Const. Compat. Perspect. Appl.*, pp. 83–111, 2021, doi: 10.1016/B978-0-12-821090-1.00021-1.
- [63] “GD&T Perpendicularity Definition _ eMachineShop.”

