

## DAFTAR PUSTAKA

- [1] L. M. P. Durão, D. J. S. Gonçalves, J. M. R. S. Tavares, V. H. C. de Albuquerque, A. Aguiar Vieira, and A. Torres Marques, "Drilling tool geometry evaluation for reinforced composite laminates," *Compos. Struct.*, vol. 92, no. 7, pp. 1545–1550, 2010, doi: 10.1016/j.compstruct.2009.10.035.
- [2] D. W. Van Krevelen, *Properties of Polymers: Their Correlation with Chemical Structure; their Numerical Estimation and Prediction from Additive Group Contributions: Fourth Edition*. 2009.
- [3] A.Langella,L.Nele,A.Maio, A torque and thrust prediction model for drilling of composite materials, *Compos PartA: Applied Science and Manufacturing* 36 (1)(2005)83–93
- [4] Alper Uysal, Mirigul Altan, Erhan Altan. 2012, Effects of cutting parameters on tool wear in drilling of polymer composite by Taguchi method. *Int J Adv Manuf Technol*, 58. pp: 915–921
- [5] W.K'onig, C.Wulf, P.Grass, H.Willerscheid, Machining of fiber reinforced plastics, *Annals of the CIRP*, 34(2)(1985), 537–548; C.C.Tsao, H.Hocheng, The effect of chisel length and associated pilot hole on delamination when drilling composite materials, *International Journal of Machine Tools and Manufacture*, 43(11)(2003), 1087–1092.
- [6] H. Hocheng, C.C. Tsao, Effects of special drill bits on drilling-induced delamination of composite materials, *International Journal of Machine Tools and Manufacture*, 46(12–13) (2006):1403–1416
- [8] Bajpai PK, Singh I (2013) Drilling behavior of sisal fiber-reinforced polypropylene composite laminates. *J Reinf Plast Compos* 32: 1569–1576. doi:10.1177/0731684413492866
- [9] C.C. Tsao n, Y.C.Chiu, Evaluation of drilling parameters on thrust force in drilling carbon fiber reinforced plastic (CFRP) composite laminates using compound core-special drills. *International Journal of Machine Tools & Manufacture*, 51(2011):740–744

- [10] Metal Machine Shop, Tips From Your CNC Machine Shop In Louviers, CO: How To Choose The Right Pecking Cycle, 2001, tersedia pada <https://www.focusedonmachining.com/blog/2018/08/tips-from-your-cnc-machine-shop-in-louviers-co-how-to-choose-the-right-pecking-cycle#:~:text=Pecking%20cycles%20help%20prevent%20chip,is%20a%20better%20completed%20component>. Diakses pada 20 November 2022
- [11] M. Dekker, *Composites Engineering Handbook*.
- [12] C. C. Tsao, "Experimental study of drilling composite materials with step-core drill," vol. 29, pp. 1740–1744, 2008, doi: 10.1016/j.matdes.2008.03.022.
- [13] H. Hocheng and C. C. Tsao, "Effects of special drill bits on drilling-induced delamination of composite materials," vol. 46, pp. 1403–1416, 2006, doi: 10.1016/j.ijmachtools.2005.10.004.
- [14] E. Capello, "Workpiece damping and its effect on delamination damage in drilling thin composite laminates," *J. Mater. Process. Technol.*, vol. 148, no. 2, pp. 186–195, 2004, doi: 10.1016/S0924-0136(03)00812-4.
- [15] N. Liu, X. Zou, J. Yuan, S. Wu, and Y. Chen, "Performance evaluation of castor oil-ethanol blended coolant under minimum quantity lubrication turning of difficult-to-machine materials," *J. Manuf. Process.*, vol. 58, no. July, pp. 1–10, 2020, doi: 10.1016/j.jmapro.2020.07.058.
- [16] H. Hocheng and C. C. Tsao, "The path towards delamination-free drilling of composite materials," *J. Mater. Process. Technol.*, vol. 167, no. 2–3, pp. 251–264, 2005, doi: 10.1016/j.jmatprotec.2005.06.039.
- [17] Z. Linbo, W. Lijiang, and W. Xin, "Study on vibration drilling of fiber reinforced plastics with hybrid variation parameters method," *Compos. Part A Appl. Sci. Manuf.*, vol. 34, no. 3, pp. 237–244, 2003, doi: 10.1016/S1359-835X(02)00207-5.
- [18] V. N. Gaitonde, S. R. Karnik, J. C. Rubio, A. E. Correia, A. M. Abrão, and

- J. P. Davim, "Analysis of parametric influence on delamination in high-speed drilling of carbon fiber reinforced plastic composites," *J. Mater. Process. Technol.*, vol. 203, no. 1–3, pp. 431–438, 2008, doi: 10.1016/j.jmatprotec.2007.10.050.
- [19] S. R. Karnik, V. N. Gaitonde, J. C. Rubio, A. E. Correia, A. M. Abrão, and J. P. Davim, "Delamination analysis in high speed drilling of carbon fiber reinforced plastics (CFRP) using artificial neural network model," *Mater. Des.*, vol. 29, no. 9, pp. 1768–1776, 2008, doi: 10.1016/j.matdes.2008.03.014.
- [20] D. Liu, H. Xu, C. Zhang, and H. Yan, "Drilling force in high speed drilling Carbon Fibre Reinforced Plastics (CFRP) using half core drill," *Adv. Mater. Res.*, vol. 102–104, pp. 729–732, 2010, doi: 10.4028/www.scientific.net/AMR.102-104.729.
- [21] J. Campos Rubio, A. M. Abrao, P. E. Faria, A. E. Correia, and J. P. Davim, "Effects of high speed in the drilling of glass fibre reinforced plastic: Evaluation of the delamination factor," *Int. J. Mach. Tools Manuf.*, vol. 48, no. 6, pp. 715–720, 2008, doi: 10.1016/j.ijmactools.2007.10.015.
- [22] M. Andrianary and P. Antoine, "No 主観的健康感を中心とした在宅高齢者における健康関連指標に関する共分散構造分析Title," vol. 2, p. 89, 2019.
- [23] U. Heisel and T. Pfeifroth, "Influence of point angle on drill hole quality and machining forces when drilling CFRP," *Procedia CIRP*, vol. 1, no. 1, pp. 471–476, 2012, doi: 10.1016/j.procir.2012.04.084.
- [24] R. Allemang, J. De Clerck, C. Niezrecki, and A. Wicks, "Preface," *Conf. Proc. Soc. Exp. Mech. Ser.*, vol. 45, no. 7, pp. 577–617, 2014.
- [25] J. F. Lancaster, "Brazing, soldering and adhesive bonding," *Metall. Weld.*, pp. 87–109, 1980, doi: 10.1007/978-94-010-9506-8\_6.
- [26] A. T. Marques, L. M. Durão, A. G. Magalhães, J. Francisco, J. Manuel, and

- R. S. Tavares, "Delamination analysis of carbon fibre reinforced laminates : Evaluation of a special step drill," *Compos. Sci. Technol.*, vol. 69, no. 14, pp. 2376–2382, 2009, doi: 10.1016/j.compscitech.2009.01.025.
- [27] S. Gaugel *et al.*, "A comparative study on tool wear and laminate damage in drilling of carbon-fiber reinforced polymers (CFRP)," *Compos. Struct.*, vol. 155, pp. 173–183, 2016, doi: 10.1016/j.compstruct.2016.08.004.
- [28] R. Angelone, A. Caggiano, I. Improta, L. Nele, and R. Teti, "Roughness of composite materials: Characterization of hole quality in drilling of Al/CFRP stacks," *Procedia CIRP*, vol. 88, pp. 473–478, 2020, doi: 10.1016/j.procir.2020.05.082.
- [29] R. Angelone, A. Caggiano, I. Improta, L. Nele, and R. Teti, "Characterization of hole quality and temperature in drilling of Al/CFRP stacks under different process condition," *Procedia CIRP*, vol. 79, pp. 319–324, 2019, doi: 10.1016/j.procir.2019.02.074.
- [30] N. O. T. Measurement, "HANDBOOK COMPOSITE MATERIALS HANDBOOK VOLUME 1 . POLYMER MATRIX COMPOSITES GUIDELINES FOR CHARACTERIZATION," vol. 1, no. June, 2002.
- [31] I. M. Astika, "Analisa Delaminasi Pada Glass Fiber Reinforced Polymer Komposit Laminat Dengan Pembebanan Fatigue," *Din. Tek. Mesin*, vol. 2, no. 1, pp. 7–14, 2012, doi: 10.29303/d.v2i1.106.
- [32] W. Thermoplastic, "Wood Thermoplastic Composites," 2005.
- [33] B. Yenigun and E. Kilickap, "Influence of hole quality on fatigue life of drilled CFRP with the different ply orientation angle," *J. Brazilian Soc. Mech. Sci. Eng.*, vol. 43, no. 1, pp. 1–14, 2021, doi: 10.1007/s40430-020-02719-2.
- [34] J. F. Pérez, J. L. Cantero, J. D. Álvarez, and M. H. Miguélez, "in composite aerospace components drilling," *Compos. Struct.*, 2017, doi: 10.1016/j.compstruct.2017.06.043.

- [35] K. Giasin, G. Gorey, C. Byrne, J. Sinke, and E. Brousseau, "Effect of machining parameters and cutting tool coating on hole quality in dry drilling of fibre metal laminates," *Compos. Struct.*, vol. 212, no. November 2018, pp. 159–174, 2019, doi: 10.1016/j.compstruct.2019.01.023.
- [36] I. S. Shyha *et al.*, "International Journal of Machine Tools & Manufacture Hole quality assessment following drilling of metallic-composite stacks," *Int. J. Mach. Tools Manuf.*, vol. 51, no. 7–8, pp. 569–578, 2011, doi: 10.1016/j.ijmachtools.2011.04.007.
- [37] J. T. Mesin, F. Teknik, and U. S. Kuala, "PENGARUH JENIS SERAT TERHADAP KUALITAS HASIL PEMESINAN BAHAN KOMPOSIT," no. Snttm Xiv, pp. 7–8, 2015.
- [38] A. D’Orazio, M. El Mehtedi, A. Forcellese, A. Nardinocchi, and M. Simoncini, "Tool wear and hole quality in drilling of CFRP/AA7075 stacks with DLC and nanocomposite TiAlN coated tools," *J. Manuf. Process.*, vol. 30, pp. 582–592, 2017, doi: 10.1016/j.jmapro.2017.10.019.
- [39] M. K. Nor Khairusshima, C. H. Che Hassan, A. G. Jaharah, A. K. M. Amin, and A. N. Md Idriss, "Effect of chilled air on tool wear and workpiece quality during milling of carbon fibre-reinforced plastic," *Wear*, vol. 302, no. 1–2, pp. 1113–1123, 2013, doi: 10.1016/j.wear.2013.01.043.
- [40] S. Kannan, H. A. Kishawy, I. M. Deiab, and M. K. Surappa, "Analysis of Tool Wear During Machining."
- [41] J. Fernández-Pérez, J. L. Cantero, J. Díaz-Álvarez, and M. H. Miguélez, "Tool wear and induced damage in CFRP drilling with step and double point angle drill bits," *Procedia Manuf.*, vol. 41, pp. 610–617, 2019, doi: 10.1016/j.promfg.2019.09.049.
- [42] I. Print, I. Online, B. Dwi, and I. Hari, "METAL : Jurnal Sistem Mekanik dan Termal Pengaruh Parameter Pemotongan dan Variasi Susunan Serat Terhadap Terbentuknya Delaminasi pada Proses Menggurdi Material Komposit Serat Nanas," vol. 01, pp. 1–8, 2018.

- [43] N. Abilash and M. Sivapragash, "Optimizing the delamination failure in bamboo fiber reinforced polyester composite," *J. King Saud Univ. - Eng. Sci.*, vol. 28, no. 1, pp. 92–102, 2016, doi: 10.1016/j.jksues.2013.09.004.
- [44] S. Y. Park, W. J. Choi, C. H. Choi, and H. S. Choi, "Effect of drilling parameters on hole quality and delamination of hybrid GLARE laminate," *Compos. Struct.*, vol. 185, pp. 684–698, 2018, doi: 10.1016/j.compstruct.2017.11.073.
- [45] C. C. Tsao, H. Hocheng, P. Mechanical, and N. Tsing, "Evaluation of thrust force and surface roughness in drilling composite material using Taguchi analysis and neural network," vol. 3, pp. 342–348, 2007, doi: 10.1016/j.jmatprotec.2006.04.126.
- [46] M. M. Ilham and A. Mufarrih, "Analisa Gaya Tekan dan Delaminasi pada Penggurdian KFRP Komposit," vol. IV, no. 2, pp. 33–38, 2018.

