

## DAFTAR PUSTAKA

- [1] H. M. C. Azeredo, M. F. Rosa, L. Henrique, and C. Mattoso, "Nanocellulose in bio-based food packaging applications," *Ind. Crop. Prod.*, vol. 97, pp. 664–671, 2017.
- [2] Dufresne, "Nanocellulose : a new ageless bionanomaterial," *Mater. Today*, vol. 16, no. 6, pp. 220–227, 2013.
- [3] M. Asrofi, "Isolation of Nanocellulose from Water Hyacinth Fiber ( WHF ) Produced via Digester-Sonication and Its Characterization," vol. 19, no. 8, pp. 1618–1625, 2018.
- [4] M. Melbi, "Production of Nanocellulose from Pineapple Leaf," pp. 1–12, 2018.
- [5] Fahma Farah et al, "Isolation , preparation , and characterization of nanofibers from oil palm empty-fruit-bunch ( OPEFB )," pp. 977–985, 2010.
- [6] Syafri Edi, "Cellulose nanofibers isolation and characterization from ramie using a chemical-ultrasonic treatment," *J. Nat. Fibers*, vol. 00, no. 00, pp. 1–11, 2018.
- [7] W. W. et J Li, Wei Xiaoyi, "Homogeneous isolation of nanocellulose from sugarcane bagasse by high pressure homogenization," *Carbohydr. Polym.*, vol. 90, no. 4, pp. 1609–1613, 2012.
- [8] C. S. Julie Chandra, N. George, and S. K. Narayanankutty, "Isolation and characterization of cellulose nanofibrils from arecanut husk fibre," *Carbohydr. Polym.*, vol. 142, pp. 158–166, 2016.
- [9] Saito T, "Homogeneous Suspensions of Individualized Microfibrils from TEMPO-Catalyzed Oxidation of Native Cellulose," vol. 7, no. 6, pp. 3–7, 2006.
- [10] H. Abrial, V. Lawrensus, D. Handayani, and E. Sugiarti, "Preparation of nano-sized particles from bacterial cellulose using ultrasonication and their characterization," *Carbohydr. Polym.*, vol. 191, pp. 161–167, 2018.
- [11] L. S. Li Wei, Yue Jinquan, "Preparation of nanocrystalline cellulose via ultrasound and its reinforcement capability for poly(vinyl alcohol) composites," *Ultrason. Sonochem.*, vol. 19, no. 3, pp. 479–485, 2012.
- [12] Zhao J, "Extraction of cellulose nanofibrils from dry softwood pulp using high shear homogenization," *Carbohydr. Polym.*, vol. 97, no. 2, pp. 695–702, 2013.
- [13] Kaushik et.al, "Isolation and characterization of cellulose nanofibrils from wheat straw using steam explosion coupled with high shear homogenization," *Carbohydr. Res.*, vol.

- 346, no. 1, pp. 76–85, 2011.
- [14] C. W. Irvin, C. C. Satam, J. C. Meredith, and M. L. Shofner, “Mechanical Reinforcement and Thermal Properties of PVA Tricomponent Nanocomposites with Chitin Nanofibers and Cellulose Nanocrystals,” *Compos. Part A*, 2018.
- [15] J. Zhang *et al.*, “Enhancing the thermal and mechanical properties of polyvinyl alcohol ( PVA ) with boron nitride nanosheets and cellulose nanocrystals,” *Polymer (Guildf)*, vol. 148, pp. 101–108, 2018.
- [16] Z. Jahan, M. Bilal, K. Niazi, and Ø. W. Gregersen, “Mechanical , thermal and swelling properties of Cellulose Nanocrystals / PVA nanocomposites membranes,” *J. Ind. Eng. Chem.*, 2017.
- [17] H. Abrial, A. Hartono, F. Hafizulhaq, D. Handayani, E. Sugiarti, and O. Pradipta, “Characterization of PVA/cassava starch biocomposites fabricated with and without sonication using bacterial cellulose fiber loadings,” *Carbohydr. Polym.*, 2018.
- [18] V. L. Peña-Reyes, M. Q. Marin-Bustamante, A. Manzo-Robledo, J. J. Chanona-Pérez, R. G. Cásarez-Santiago, and E. Suarez-Najera, “Effect of crosslinking of alginate / pva and chitosan / pva, reinforced with cellulose nanoparticles obtained from agave *Atrivirens karw*,” *Procedia Eng.*, vol. 200, pp. 434–439, 2017.
- [19] D. M. Panaitescu, A. N. Frone, M. Ghiurea, and I. Chiulan, “Influence of storage conditions on starch/PVA films containing cellulose nanofibers,” *Ind. Crops Prod.*, vol. 70, pp. 170–177, 2015.
- [20] Z. Wang, X. Qiao, and K. Sun, “Rice straw cellulose nano fi brils reinforced poly ( vinyl alcohol ) composite fi lms,” vol. 197, no. April, pp. 442–450, 2018.
- [21] S. Xiao, R. Gao, L. K. Gao, and J. Li, “Poly(vinyl alcohol) films reinforced with nanofibrillated cellulose (NFC) isolated from corn husk by high intensity ultrasonication,” *Carbohydr. Polym.*, vol. 136, pp. 1027–1034, 2015.
- [22] D. G. Callister, W. D., & Rethwisch, *Callister, W. D., & Rethwisch, D. G. (2007). Materials science and engineering: an introduction (Vol. 7, pp. 665-715). New York: John wiley & sons.*, 9th ed. New York, 2014.
- [23] W. F. Smith, *Principles of materials science and engineering*. 1986.
- [24] A. Riyanto, “Pengaruh Waktu Pengempaan Pembuatan Papan Partikel Dari Serat Tandan Kosong Kelapa Sawit Dengan Perikat Urea Formadehyde Terhadap Kekuatan Tarik

Papan Partikel,” Padang, 2013.

- [25] F. . GiBCon, *Principles of Composite Material Mechanis, International Edition*. New York: McGraw-Hill Inc, 1994.
- [26] D. Holbery, J., & Houston, “Natural-fiber-reinforced polymer composites in automotive applications.,” no. Jom, pp. 58(11), 80–86., 2006.
- [27] I. S. Nakagaito A.N, “Bacterial cellulose : the ultimate nano-scalar cellulose morphology for the production of high-strength composites,” vol. 97, pp. 93–97, 2005.
- [28] N. Soykeabkaew, C. Sian, S. Gea, T. Nishino, and T. Peijs, “All-cellulose nanocomposites by surface selective dissolution of bacterial cellulose,” *Cellulose*, vol. 16, no. 3, pp. 435–444, 2009.
- [29] C. M. Hassan and N. A. Peppas, “Structure and morphology of freeze/thawed PVA hydrogels,” *Macromolecules*, vol. 33, no. 7, pp. 2472–2479, 2000.
- [30] R. Stefano, “Karakterisasi Plastik Biodegradabel dari Campuran Kitosan dan Poli Vinil Alkohol Menggunakan Metode Tanpa Pelarut,” Lampung, 2012.
- [31] G. Siqueira, S. Tapin-Lingua, J. Bras, D. da Silva Perez, and A. Dufresne, “Mechanical properties of natural rubber nanocomposites reinforced with cellulosic nanoparticles obtained from combined mechanical shearing, and enzymatic and acid hydrolysis of sisal fibers,” *Cellulose*, vol. 18, no. 1, pp. 57–65, 2011.
- [32] A. L. S. Pereira *et al.*, “Improvement of polyvinyl alcohol properties by adding nanocrystalline cellulose isolated from banana pseudostems,” *Carbohydr. Polym.*, vol. 112, pp. 165–172, 2014.
- [33] Y. M. Zhou, S. Y. Fu, L. M. Zheng, and H. Y. Zhan, “Effect of nanocellulose isolation techniques on the formation of reinforced poly(vinyl alcohol) nanocomposite films,” *Express Polym. Lett.*, vol. 6, no. 10, pp. 794–804, 2012.
- [34] Q. Cheng, S. Wang, and T. G. Rials, “Poly(vinyl alcohol) nanocomposites reinforced with cellulose fibrils isolated by high intensity ultrasonication,” *Compos. Part A Appl. Sci. Manuf.*, vol. 40, no. 2, pp. 218–224, 2009.
- [35] Z. Zhang *et al.*, “Mechanical properties, water swelling behavior, and morphology of swellable rubber compatibilized by PVA-g-PBA,” *Polym. Eng. Sci.*, vol. 44, no. 1, pp. 72–78, 2004.
- [36] K. T. Shalumon, K. H. Anulekha, C. M. Girish, R. Prasanth, S. V. Nair, and R.

- Jayakumar, "Single step electrospinning of chitosan/poly(caprolactone) nanofibers using formic acid/acetone solvent mixture," *Carbohydr. Polym.*, vol. 80, no. 2, pp. 414–420, 2010.
- [37] Markus Yovian W. L, "Perancangan homogenizer untuk skala industri rumah tangga," Widya Mandala Catholic University Surabaya., 2010.
- [38] W. Chen, H. Yu, Y. Liu, P. Chen, M. Zhang, and Y. Hai, "Individualization of cellulose nanofibers from wood using high-intensity ultrasonication combined with chemical pretreatments," *Carbohydr. Polym.*, vol. 83, no. 4, pp. 1804–1811, 2011.
- [39] ASTM, *Standard test method for tensile properties of plastic. D638- 02a*. USA, 2002.
- [40] I. D. Mall, V. C. Srivastava, N. K. Agarwal, and I. M. Mishra, "Removal of congo red from aqueous solution by bagasse fly ash and activated carbon: Kinetic study and equilibrium isotherm analyses," *Chemosphere*, vol. 61, no. 4, pp. 492–501, 2005.
- [41] H. S. Mansur, C. M. Sadahira, A. N. Souza, and A. A. P. Mansur, "FTIR spectroscopy characterization of poly (vinyl alcohol) hydrogel with different hydrolysis degree and chemically crosslinked with glutaraldehyde," *Mater. Sci. Eng. C*, vol. 28, no. 4, pp. 539–548, 2008.
- [42] S. Wong, S. Kasapis, and Y. Mabelyn, "Bacterial and plant cellulose modification using ultrasound irradiation," *Carbohydr. Polym.*, vol. 77, no. 2, pp. 280–287, 2009.
- [43] S. Fizikokimia and N. De Coco, "Physicochemical Properties and Characterization of Nata de Coco from Local Food Industries as a Source of Cellulose," vol. 41, no. 2, pp. 205–211, 2012.
- [44] F. Hafizulhaq, H. Abral, A. Kasim, S. Arief, and J. Affi, "Moisture Absorption and Opacity of Starch-Based Biocomposites Reinforced with Cellulose Fiber from Bengkoang," *Fibers*, vol. 6, no. 3, p. 62, 2018.
- [45] H. Abral, A. S. Anugrah, F. Hafizulhaq, E. Sugiarti, and A. N. Muslimin, "AC PT Faculty of Pharmacy," no. 2017, p. #pagerange#, 2018.
- [46] R. Sakai and Y. Teramoto, "Producing a magnetically anisotropic soft material : synthesis of iron oxide nanoparticles in a carrageenan / PVA matrix and stretching of the hybrid gelatinous bulk," pp. 251–260, 2018.
- [47] A. Peri and V. Mi, "Biological activity of electrochemically synthesized silver doped polyvinyl alcohol / graphene composite hydrogel discs for biomedical applications," vol.

- 104, pp. 26–34, 2016.
- [48] H. Abral, G. J. Putra, M. Asrofi, J. Park, and H. Kim, “Effect of Vibration Duration of High Ultrasound Applied to Bio- composite While Gelatinized on its Properties,” *Ultrason. - Sonochemistry*, 2017.
- [49] A. J. Svagan, M. A. S. A. Samir, and L. A. Berglund, “Biomimetic Polysaccharide Nanocomposites of High Cellulose Content and High Toughness,” pp. 2556–2563, 2007.
- [50] S. Wong, S. Kasapis, and D. Huang, “Food Hydrocolloids Molecular weight and crystallinity alteration of cellulose via prolonged ultrasound fragmentation,” *Food Hydrocoll.*, vol. 26, no. 2, pp. 365–369, 2012.
- [51] J. Zhu, L. Li, L. Chen, and X. Li, “Food Hydrocolloids Study on supramolecular structural changes of ultrasonic treated potato starch granules,” *Food Hydrocoll.*, vol. 29, no. 1, pp. 116–122, 2012.
- [52] E. Syafri, A. Kasim, H. Abral, and A. Asben, “Effect of Precipitated Calcium Carbonate on Physical , Mechanical and Thermal Effect of Precipitated Calcium Carbonate on Physical , Mechanical and Thermal Properties of Cassava Starch Bioplastic Composites,” no. October, 2017.
- [53] A. Garcia- Hernandez, E. J. Vernon- Carter, and J. Alvarez- Ramirez, “Impact of ghosts on the mechanical, optical, and barrier properties of corn starch films,” *Starch- Stärke*, vol. 69, no. 1–2, p. 1600308, 2017.
- [54] D. Liu, X. Sun, and H. Tian, “Effects of cellulose nanofibrils on the structure and properties on PVA nanocomposites,” pp. 2981–2989, 2013.
- [55] E. Syafri, A. Kasim, H. Abral, G. Tj, M. R. Sanjay, and N. H. Sari, “PT,” *Int. J. Biol. Macromol.*, p. #pagerange#, 2018.
- [56] M. Asrofi, H. Abral, Y. K. Putra, S. M. Sapuan, and H. J. Kim, “Effect of duration of sonication during gelatinization on properties of tapioca starch water hyacinth fiber biocomposite,” *Int. J. Biol. Macromol.*, vol. 108, pp. 167–176, 2018.
- [57] J. George, K. V Ramana, and A. S. Bawa, “International Journal of Biological Macromolecules Bacterial cellulose nanocrystals exhibiting high thermal stability and their polymer nanocomposites,” *Int. J. Biol. Macromol.*, vol. 48, no. 1, pp. 50–57, 2011.
- [58] K. L. Manis, S. Barat, K. L. Manis, and S. Barat, “CHARACTERIZATION OF THE SONICATED YAM BEAN STARCH BIONANOCOMPOSITES REINFORCED BY

NANOCELLULOSE WATER HYACINTH FIBER ( WHF ): THE EFFECT OF VARIOUS FIBER LOADING,” vol. 13, no. 9, pp. 2700–2715, 2018.

- [59] A. Jokar, M. H. Azizi, and Z. H. Esfehiani, “Original Article Effects of ultrasound time on the properties of polyvinyl alcohol-based nanocomposite films,” vol. 2, no. 4, pp. 29–38, 2015.
- [60] X. Li, C. Qiu, N. Ji, C. Sun, L. Xiong, and Q. Sun, “Mechanical , barrier and morphological properties of starch nanocrystals-reinforced pea starch films,” vol. 121, pp. 155–162, 2015.



