

DAFTAR PUSTAKA

- [1] J. C. Williams and E. A. Starke, "Progress in structural materials for aerospace systems &," vol. 51, pp. 5775–5799, 2003, doi: 10.1016/j.actamat.2003.08.023.
- [2] W. D. Callister Jr and D. G. Rethwisch, *Characteristics, Application, and Processing of Polymers*. 2018.
- [3] I. H. Carli, S. A & Widyanto, "Analisis kekuatan tarik dan lentur komposit serat gelas jenis woven dengan matriks epoxy dan polyester berlapis simetri dengan metoda manufaktur hand lay-up," *Tek. Mesin, Politek. Negeri Semarang dan Tek. Mesin, Univ. Diponegoro Semarang*, 2012.
- [4] "05_08-stress_analysis_of_fiber_reinforced_composite_materials.pdf."
- [5] B. Wang and H. Gao, "Fibre Reinforced Polymer Composites," *Eng. Mater.*, pp. 15–43, 2021, doi: 10.1007/978-3-030-71438-3_2.
- [6] I. O. P. C. Series and M. Science, "Hole Introduction Effect on The E-Glass WR 185 Fibre Reinforcement Polyester Hole Introduction Effect on The E-Glass WR 185 Fibre Reinforcement Polyester," 2021, doi: 10.1088/1757-899X/1062/1/012027.
- [7] M. S. Goyat, S. Rana, S. Halder, and P. K. Ghosh, "Facile fabrication of epoxy-TiO₂ nanocomposites: A critical analysis of TiO₂ impact on mechanical properties and toughening mechanisms," *Ultrason. Sonochem.*, vol. 40, pp. 861–873, 2018, doi: 10.1016/j.ultsonch.2017.07.040.
- [8] D. Pinto, L. Bernardo, A. Amaro, and S. Lopes, "Mechanical properties of epoxy nanocomposites using titanium dioxide as reinforcement - A review," *Constr. Build. Mater.*, vol. 95, pp. 506–524, 2015, doi: 10.1016/j.conbuildmat.2015.07.124.
- [9] Ilhamdi, A. Nugroho, D. Hidayat, and R. A. Nur, "Physical and Mechanicals Characteristic of the Nano Particulate TiO₂-Epoxy Composite," in *IOP Conference Series: Materials Science and Engineering*, IOP Publishing Ltd, Feb. 2021. doi: 10.1088/1757-899X/1062/1/012028.
- [10] A. Chatterjee and M. S. Islam, "Fabrication and characterization of TiO₂-epoxy nanocomposite," *Mater. Sci. Eng. A*, vol. 487, no. 1–2, pp. 574–585, 2008, doi: 10.1016/j.msea.2007.11.052.
- [11] D. Chandramohan, L. Ravikumar, C. Sivakandhan, G. Murali, and A. Senthilathiban, "Review on Tribological Performance of Natural Fibre-Reinforced Polymer Composites," *J. Bio-Tribo-Corrosion*, vol. 4, no. 4, p. 0, 2018, doi: 10.1007/s40735-018-0172-x.

- [12] F. S. wiliam, *Principle of Materials Science And Engineering*, 2nd ed. Singapore: Mc Graw-Hill, 1996.
- [13] R. Kartini, H. Darmasetiawan, A. K. Karo, and Sudirman, "Pembuatan dan Karakterisasi Komposit Polimer Berpenguat Serat Alam," *J. Sains Mater. Indones.*, vol. 3, no. 3, pp. 30–38, 2002.
- [14] B. M. Law, "Rawlings," *Music. Times*, vol. 126, no. 1712, p. 583, 1985, doi: 10.2307/964910.
- [15] M. S., *Composite Manufacturing : Materials, Product, and Process Engineering*. Florida, 2001.
- [16] H. Fahmi and D. N. Arifin, "Pengaruh Variasi Komposisi Komposit Resin Epoxy/Serat Glass Dan Serat Daun Nanas Terhadap Ketangguhan," *J. Tek. Mesin*, vol. 4, no. 2, pp. 84–89, 2014.
- [17] K. Prakash Marimuthu, S. Mohan Kumar, V. Ravi Kumar, and H. K. Govindaraju, "Characterization of mechanical properties of epoxy reinforced with glass fiber and coconut fiber," *Mater. Today Proc.*, vol. 16, pp. 661–667, 2019, doi: 10.1016/j.matpr.2019.05.143.
- [18] *PROPAN EPOXY CAST EC-973-2K TEKNIKAL DATA*. PROPAN RAYA CORPORATION.
- [19] X. Chen and S. S. Mao, "Titanium dioxide nanomaterials: Synthesis, properties, modifications and applications," *Chem. Rev.*, vol. 107, no. 7, pp. 2891–2959, 2007, doi: 10.1021/cr0500535.
- [20] Y. Xiaodong C. Xiaobo, "Titanium Dioxide Nanomaterials," *Encycl. Inorg. Bioinorg. Chem.*, vol. 1, no. 2015.
- [21] B. Setiadi, "KAJIAN SIFAT FISIS DAN MEKANIS MATERIAL KOMPOSIT DENGAN Matrik AlSiMg DIPERKUAT DENGAN SERBUK SiC," *J. Tek. Mesin S-1*, vol. 2, no. 4, pp. 480–487, 2014.
- [22] M. Ridha and D. Darminto, "Analisis Densitas, Porositas, dan Struktur Mikro Batu Apung Lombok dengan Variasi Lokasi dan Kedalaman," *J. Fis. dan Apl.*, vol. 12, no. 3, pp. 124–130, 2016, doi: 10.12962/j24604682.v12i3.1403.
- [23] Lijun Fang et al, "Nano - micro Structure of functionalized Boron Nitride and Aluminum oxide for Epoxy Composites with Enhanced and Thermal Conductivity and Breakdown Strength," *Electrical Insul. Therm. Aging*, 2014.
- [24] A. Mirmohseni and S. Zavareh, "Preparation and characterization of an epoxy nanocomposite toughened by a combination of thermoplastic, layered and particulate nano-fillers," *Mater. Des.*, vol. 31, no. 6, pp. 2699–2706, 2010, doi: 10.1016/j.matdes.2010.01.035.

- [25] Y. Zhou, E. White, M. Hosur, and S. Jeelani, "Effect of particle size and weight fraction on the flexural strength and failure mode of TiO₂ particles reinforced epoxy," *Mater. Lett.*, vol. 64, no. 7, pp. 806–809, 2010, doi: 10.1016/j.matlet.2010.01.016.
- [26] H. A. Al-Turaif, "Effect of nano TiO₂ particle size on mechanical properties of cured epoxy resin," *Prog. Org. Coatings*, vol. 69, no. 3, pp. 241–246, 2010, doi: 10.1016/j.porgcoat.2010.05.011.
- [27] D. Bazrgari, F. Moztarzadeh, A. A. Sabbagh-Alvani, M. Rasoulianboroujeni, M. Tahri, and L. Tayebi, "Mechanical properties and tribological performance of epoxy/Al₂O₃ nanocomposite," *Ceram. Int.*, vol. 44, no. 1, pp. 1220–1224, 2018, doi: 10.1016/j.ceramint.2017.10.068.
- [28] S. S. Vinay and C. V. Venkatesh, "Effect of nano-Al₂O₃ particles on mechanical and wear behaviour of glass fibre epoxy composites," *Mater. Today Proc.*, vol. 46, no. xxxx, pp. 9004–9007, 2021, doi: 10.1016/j.matpr.2021.05.378.
- [29] D. ASTM, "Annual Book of ASTM Standards: Standard Test Method for Tensile Properties Of Plastics," Philadelphia, USA: American Society for Testing and Materials.
- [30] D. ASTM, "Standart Test Method For Compress Properties Of Polymer Matrix Composite Material By the V-Notched," Philadelphia, USA: American Society for Testing and Materials (ASTM).
- [31] D. ASTM, "Standard Test Methods For Flexural Properties of Unreinforced and Reinforced Plastics and Electrical Insulating Materials," Philadelphia, USA: American Society For Testing and Materials (ASTM).

