

DAFTAR PUSTAKA

- [1] A. Kurniawan, “Kekuatan Tarik Film Bakteri Nata De Coco Hasil Perlakuan Ultrasonik dan Penambahan Gambir,” p. 43, 2021.
- [2] H. T. Raudah, “Pengaruh Waktu Steam Terhadap Sifat Mekanik Film Biopolimer Dari Pellicle Nata De Coco,” Padang, 2022. [Online]. Available: <http://scholar.unand.ac.id/id/eprint/100703>
- [3] M. Suryati¹, Meriatna², “Optimasi Proses Pembuatan Bioplastik dari Pati Limbah Kulit Singkong,” *Teknologi Kimia Unimal*, pp. 78–91, 2016, [Online]. Available: jtk@unimal.ac.id
- [4] F. A. Bernadeta Ayu Widyaningrum¹, Wida Banar Kusumaningrum¹, R. Syamani¹, Dwi Ajias Pramasari¹, Sukma Surya Kusuma¹, Fazhar Akbar¹, and A. A. C. Ermawati², “Karakteristik Sifat Mekanik Bioplastik Pati Singkong/PVA dengan Penambahan Pulp Tandan Kosong Kelapa Sawit dan Asam Sitrat Teraktivasi,” *J. Kim. dan Kemasan*, pp. 46–45, 2020, doi: doi.org/10.24817/jkk.v42i2.6130.
- [5] D. R. c Hairul Abral a,^{*} Muhammad Ikhsan a, E. S. d Dian Handayani b, Neny Sandrawati b, and A. N. M. D, “Anti-UV, antibacterial, strong, and high thermal resistant polyvinyl alcohol/Uncaria gambir extract biocomposite film,” *J. Mater. Res. Technol.*, pp. 2 1 9 3-2 2 0 2, 2020, doi: <https://doi.org/10.1016/j.jmrt.2022.01.120>.
- [6] Ilham Chayri Iby, “Pengaruh penambahan Gambir dan Asam Borat Terhadap Kekuatan Tarik Film Bermatriks Polyvinyl Alcohol,” Andalas University, 2022.
- [7] P. H. Lissberger, “Materials science,” *Phys. Technol.*, vol. 7, no. 1, pp. 35–36, Jan. 1976, doi: 10.1088/0305-4624/7/1/408.
- [8] W. S. Faricha Tunjungsari, Jumaeri, “Karakteristik Adhesive Polymer Polivinil Asetat Termodifikasi Butil Akrilat untuk Aplikasi Transfer Metaliz,” *Article*, vol. 2, 2019, doi: 10.15294/IJCS.V6I2.13400.
- [9] L. W. McKeen, “Introduction to Plastics and Polymers,” in *The Effect of UV*

Light and Weather on Plastics and Elastomers, Elsevier, 2019, pp. 1–20. doi: 10.1016/B978-0-12-816457-0.00001-0.

- [10] C. Johansson, “Bio-nanocomposites for food packaging applications,” in *Nanocomposites with Biodegradable Polymers*, Oxford University Press, 2011, pp. 348–367. doi: 10.1093/acprof:oso/9780199581924.003.0014.
- [11] M. K. Chairani, “Efek durasi pemanasan terhadap sifat mekanik cellulose paper nata de coco,” 2019.
- [12] S. B. Zainab Waheed Abdullah¹, Yu Dong¹, Ian Jeffery Davies¹, “PVA, PVA blends and their nanocomposites for biodegradable packaging application”, doi: doi.org/10.1080/03602559.2016.1275684.
- [13] K. Z. Rafiqah S. Ayu, Abdan Khalina, Ahmad Saffan Harmaen and R. A. I. and C. H. L. Tawakkal Isma, Qiuyun Liu, “Characterization Study of Empty Fruit Bunch (EFB) Fibers Reinforcement in Poly(Butylene) Succinate (PBS)/Starch/Glycerol Composite Sheet,” 2020.
- [14] M. J. K. M. Hazwan Hussin, “The corrosion inhibition and adsorption behavior of Uncaria gambir extract on mild steel in 1 M HCl,” *Mater. Chem. Phys.*, vol. 125, no. 3, pp. 461–468, 2011, doi: <https://doi.org/10.1016/j.matchemphys.2010.10.032>.
- [15] W. D. Callister Jr and D. G. Rethwisch, *Characteristics, Application, and Processing of Polymers*. 2018.
- [16] S. T. Dwiwati, MT, “Pengaruh Fraksi Volume Serat Terhadap Sifat Mekanik Komposit Serat Tebu/Poliester,” *J. Konversi Energi dan Manufaktur*, vol. 1, no. 3, pp. 164–168, Oct. 2014, doi: 10.21009/JKEM.1.3.8.
- [17] A. danGuntarti S. Wiwik Pudjiastuti,ArieListyarini, “Sifat Mekanik dan Sifat Barrier Campuran Polyvinyl Alkohol dan Kitosan,” *J. Sains Mater. Indones.*, 2016, doi: 10.17146/jsmi.2016.17.3.4187.