

DAFTAR PUSTAKA

- [1] M. Ben Achour, M. Rguiti, C. Samuel, S. Barrau, M. F. Lacrampe, and C. Courtois, “Energy harvesting by uniaxially stretched Poly(lactic acid) film at low strain frequency for powering wearable sensors: Experimental results and theoretical extrapolation.,” *Smart Mater. Struct.*, vol. 32, May 2023, doi: 10.1088/1361-665X/acd972.
- [2] S. Dong *et al.*, “Unveiling the Mechanism of the in Situ Formation of 3D Fiber Macroassemblies with Controlled Properties,” 2023, doi: 10.1021/acsnano.3c00289.
- [3] G. B. Medeiros, F. D. A. Lima, D. S. De Almeida, V. G. Guerra, and M. L. Aguiar, “Modification and Functionalization of Fibers Formed by Electrospinning : A Review,” 2022.
- [4] S. F. Shaikh and Z. A. Shaikh, “Chapter 8 - Electrospinning of metal oxide nanostructures,” in *Metal Oxides*, R. Mane, V. Jadhav, and A. B. T.-S. M. for M. O. N. Al-Enizi, Eds. Elsevier, 2023, pp. 125–152. doi: <https://doi.org/10.1016/B978-0-12-824353-4.00009-9>.
- [5] H. Huang *et al.*, “Electrospun Nanofibers: Current Progress and Applications in Food Systems,” *J. Agric. Food Chem.*, vol. 70, no. 5, pp. 1391–1409, Feb. 2022, doi: 10.1021/acs.jafc.1c05352.
- [6] G. Rajeshkumar *et al.*, “Environment friendly , renewable and sustainable poly lactic acid (PLA) based natural fiber reinforced composites – A comprehensive review,” *J. Clean. Prod.*, vol. 310, no. January, p. 127483, 2021, doi: 10.1016/j.jclepro.2021.127483.
- [7] M. Lackner, “Sustainable Bioplastics 2016 - PBAT-A versatile material for biodegradable and compostable packagings - Maximilian Lackner-UniversityofAppliedSciencesFHTechnikumWien,” vol. 4, no. 1, pp. 10–11, 2020, doi: 10.1126/science.1261689.
- [8] M. Eichers, D. Bajwa, J. Shojaeiarnani, and S. Bajwa, “Biobased plasticizer and cellulose nanocrystals improve mechanical properties of polylactic acid composites,” *Ind. Crops Prod.*, vol. 183, p. 114981, 2022, doi: <https://doi.org/10.1016/j.indcrop.2022.114981>.
- [9] M. G. Tadesse, A. Prince Periyasamy, and J. F. Lübben, “Nanomaterials Based Polymer Composites: Mechanical Properties BT - Mechanics of Nanomaterials and Polymer Nanocomposites,” H. Abdellaoui, S. M. R., and S. Siengchin, Eds. Singapore: Springer Nature Singapore, 2023, pp. 129–145. doi: 10.1007/978-981-99-2352-6_7.
- [10] R. F. Listyanda, Kusmono, M. W. Wildan, and M. N. Ilman, “Extraction and characterization of nanocrystalline cellulose (NCC) from ramie fiber by sulphuric acid hydrolysis,” *AIP Conf. Proc.*, vol. 2217, no. 1, p. 30069, Apr. 2020, doi: 10.1063/5.0001068.

- [11] N. D. N. Affandi, M. R. Ahmad, A. Baharudin, and N. A. A. Shukry, “Effect of crosslinking on the solubility and morphological structures of the PVA nanofibres,” in *2012 IEEE Colloquium on Humanities, Science and Engineering (CHUSER)*, 2012, pp. 458–462. doi: 10.1109/CHUSER.2012.6504358.
- [12] X. Wang and M. Nie, “Properties of PANI-PVA Composite Film,” vol. 286, pp. 253–256, 2011, doi: 10.4028/www.scientific.net/AMR.284-286.253.
- [13] G. S. Mukherjee, A. Jain, and M. Banerjee, “Engineering Matrix Materials for Composites: Their Variety, Scope and Applications,” *Fine Chem. Eng.*, vol. 4, no. 1, pp. 13–45, 2023, doi: 10.37256/fce.4120232128.
- [14] T. Trzepieciński, T. Batu, F. Kibrete, and H. G. Lemu, “Application of Composite Materials for Energy Generation Devices,” *J. Compos. Sci.*, vol. 7, no. 2, 2023, doi: 10.3390/jcs7020055.
- [15] M. Al-Nabulsi *et al.*, “Co-blend application mode of bulk fill composite resin,” *Materials (Basel)*., vol. 12, no. 16, pp. 1–15, 2019, doi: 10.3390/ma12162504.
- [16] S. Shoor, “A Review of Composite Materials and its application,” vol. 6, no. 4, pp. 1192–1197, 2019.
- [17] M. A. Ben Achour, M. Rguiti, C. Samuel, S. Barrau, M.-F. Lacrampe, and C. Courtois, “Energy harvesting by uniaxially-stretched poly(lactide) films at low tensile strain frequencies for powering wearable sensors: experimental results and theoretical extrapolation,” *Smart Mater. Struct.*, vol. 32, no. 7, p. 75009, 2023, doi: 10.1088/1361-665X/acd972.
- [18] T. Fan and R. Daniels, “Preparation and Characterization of Electrospun Polylactic Acid (PLA) Fiber Loaded with Birch Bark Triterpene Extract for Wound Dressing,” *AAPS PharmSciTech*, vol. 22, no. 6, pp. 1–9, 2021, doi: 10.1208/s12249-021-02081-z.
- [19] M. Cao *et al.*, “Investigation of Carbon Fiber on the Tensile Property of FDM-Produced PLA Specimen,” *Polymers (Basel)*., vol. 14, no. 23, 2022, doi: 10.3390/polym14235230.
- [20] Ufuoma Abigail Oyohwose and Victoria Ikpemhinoghe Omoko, “Synthesis, characterization and application of nanocrystalline cellulose: A review,” *Int. J. Sci. Res. Arch.*, vol. 8, no. 2, pp. 234–243, 2023, doi: 10.30574/ijrsa.2023.8.2.0217.
- [21] A. Kaboorani and B. Riedl, *Mechanical performance of polyvinyl acetate (PVA)-based biocomposites*, Fourteenth. Elsevier Ltd., 2015. doi: 10.1016/B978-1-78242-373-7.00009-3.
- [22] L. É. Uhljar and R. Ambrus, “Electrospinning of Potential Medical Devices (Wound Dressings, Tissue Engineering Scaffolds, Face Masks) and Their

- Regulatory Approach,” *Pharmaceutics*, vol. 15, no. 2, 2023, doi: 10.3390/pharmaceutics15020417.
- [23] J. Xing, M. Zhang, X. Liu, C. Wang, N. Xu, and D. Xing, “Multi-material electrospinning: from methods to biomedical applications,” *Mater. Today Bio*, vol. 21, no. February, p. 100710, 2023, doi: 10.1016/j.mtbiol.2023.100710.
- [24] A. Keirouz *et al.*, “The History of Electrospinning: Past, Present, and Future Developments,” *Adv. Mater. Technol.*, vol. 8, no. 11, pp. 1–34, 2023, doi: 10.1002/admt.202201723.
- [25] X. Shi *et al.*, “Electrospinning of Nanofibers and Their Applications for Energy Devices,” vol. 2015, 2015.
- [26] N. Z. A. Al-Hazeem, “Nanofibers and Electrospinning Method,” in *Novel Nanomaterials*, G. Z. Kyzas and A. C. Mitropoulos, Eds. Rijeka: IntechOpen, 2018. doi: 10.5772/intechopen.72060.
- [27] J. V Patil, S. S. Mali, A. S. Kamble, C. K. Hong, J. H. Kim, and P. S. Patil, “Electrospinning: A versatile technique for making of 1D growth of nanostructured nanofibers and its applications: An experimental approach,” *Appl. Surf. Sci.*, vol. 423, pp. 641–674, 2017, doi: <https://doi.org/10.1016/j.apsusc.2017.06.116>.
- [28] W. Zuo, M. Zhu, W. Yang, H. Yu, Y. Chen, and Y. Zhang, “Experimental study on relationship between jet instability and formation of beaded fibers during electrospinning,” *Polym. Eng. & Sci.*, vol. 45, no. 5, pp. 704–709, 2005, doi: <https://doi.org/10.1002/pen.20304>.
- [29] M. Takasaki, H. Kurita, T. Kubota, K. Takashima, M. Hayashi, and A. Mizuno, “Electrostatic precipitation of diesel PM at reduced gas temperature,” in *2015 IEEE Industry Applications Society Annual Meeting*, 2015, pp. 1–4. doi: 10.1109/IAS.2015.7356755.
- [30] A. Haider, S. Haider, and I.-K. Kang, “A comprehensive review summarizing the effect of electrospinning parameters and potential applications of nanofibers in biomedical and biotechnology,” *Arab. J. Chem.*, vol. 11, no. 8, pp. 1165–1188, 2018, doi: <https://doi.org/10.1016/j.arabjc.2015.11.015>.
- [31] F. Ridwan and A. A. Ananta, “Preparation Smallest PVA/Binahong Leaf Nanofiber for Wound Dressing Applications by Varying Electrospinning Variable using Taguchi Method,” *IOP Conf. Ser. Mater. Sci. Eng.*, vol. 1041, no. 1, p. 012063, 2021, doi: 10.1088/1757-899x/1041/1/012063.
- [32] N. Sciences, F. Findik, and S. A. Sciences, “Nanomaterials and their applications,” vol. 9, no. 3, pp. 62–75, 2021.
- [33] S. Qi, A. Xu, J. Liu, and Z. Xia, “Qualified nano-composite yarn for hydrophobic fabric via online nano- and micron-fiber composite spinning,”

Text. Res. J., vol. 93, no. 3–4, pp. 739–749, Sep. 2022, doi: 10.1177/00405175221124357.

- [34] L. L. Shaw and H. Luo, “Deformation behavior and mechanisms of a nanocrystalline multi-phase aluminum alloy,” *J. Mater. Sci.*, vol. 42, no. 5, pp. 1415–1426, 2007, doi: 10.1007/s10853-006-1118-0.
- [35] B. Kusharjanta, R. Soenoko, A. Purnowidodo, and Y. S. Irawan, “Analysis of Tensile Strength, Crystallinity, Crystallite Size, and Thermal Stability of Polypropylene Joined By Friction Stir Welding,” *J. Appl. Eng. Sci.*, vol. 20, no. 1, pp. 85–90, 2022, doi: 10.5937/jaes0-30899.
- [36] X. Zhang *et al.*, “Reinforcing effect of nanocrystalline cellulose and office waste paper fibers on mechanical and thermal properties of poly (lactic acid) composites,” *J. Appl. Polym. Sci.*, vol. 138, no. 21, 2021, doi: 10.1002/app.50462.
- [37] A. Kaboorani, B. Riedl, P. Blanchet, M. Fellin, O. Hosseinaei, and S. Wang, “Nanocrystalline cellulose (NCC): A renewable nano-material for polyvinyl acetate (PVA) adhesive,” *Eur. Polym. J.*, vol. 48, no. 11, pp. 1829–1837, 2012, doi: 10.1016/j.eurpolymj.2012.08.008.
- [38] Q.-L. Lu, J. Wu, Y. Li, L. Li, and B. Huang, “One-pot green extraction of high charge density cellulose nanocrystals with high yield for bionanocomposites,” *J. Mater. Sci.*, vol. 56, no. 21, pp. 12212–12223, 2021, doi: 10.1007/s10853-021-06085-9.
- [39] L. Maria, V. Peter, S. Gunther, and R. Erdmann, “Effect of size and shape on the elastic modulus of metal nanowires,” *MRS Adv.*, vol. 6, no. 27, pp. 665–673, 2021, doi: 10.1557/s43580-021-00103-3.
- [40] T. Huq *et al.*, “Nanocrystalline cellulose (NCC) reinforced alginate based biodegradable nanocomposite film,” *Carbohydr. Polym.*, vol. 90, no. 4, pp. 1757–1763, 2012, doi: 10.1016/j.carbpol.2012.07.065.