

## DAFTAR PUSTAKA

- [1] R. Mori, “Recent Developments for Aluminum–Air Batteries,” *Electrochem. Energy Rev.*, vol. 3, no. 2, pp. 344–369, 2020, doi: 10.1007/s41918-020-00065-4.
- [2] P. Goel, D. Dobhal, and R. C. Sharma, “Aluminum–air batteries: A viability review,” *J. Energy Storage*, vol. 28, no. February, 2020, doi: 10.1016/j.est.2020.101287.
- [3] S. M. B. Respati, “5992-14032-2-Pb,” *Baterai Alum. Udar. Dengan Bahan Dasar Zeolit Alam Yang Dipanaskan Sebagai Elektroda*, vol. 18, no. 1, pp. 74–79, 2022.
- [4] P. Katsoufis *et al.*, “Study of a thin film aluminum-air battery,” *Energies*, vol. 13, no. 6, pp. 1–9, 2020, doi: 10.3390/en13061447.
- [5] H. S. Majdi *et al.*, “Nano and Battery Anode: A Review,” *Nanoscale Res. Lett.*, vol. 16, no. 1, 2021, doi: 10.1186/s11671-021-03631-x.
- [6] S. Barthwal, Y. S. Kim, and S. H. Lim, “Mechanically robust superamphiphobic aluminum surface with nanopore-embedded microtexture,” *Langmuir*, vol. 29, no. 38, pp. 11966–11974, 2013, doi: 10.1021/la402600h.
- [7] L. Yi, L. Zhiyuan, H. Xing, L. Yisen, and C. Yi, “Formation and microstructures of unique nanoporous AAO films fabricated by high voltage anodization,” *J. Mater. Chem.*, vol. 21, no. 26, pp. 9661–9666, 2011, doi: 10.1039/c1jm10781j.
- [8] B. D. Clark *et al.*, “Aluminum Nanorods,” *Nano Lett.*, vol. 18, no. 2, pp. 1234–1240, 2018, doi: 10.1021/acs.nanolett.7b04820.

- [9] M. Winter and R. J. Brodd, “What are batteries, fuel cells, and supercapacitors?,” *Chem. Rev.*, vol. 104, no. 10, pp. 4245–4269, 2004, doi: 10.1021/cr020730k.
- [10] T. Cutler, “Design guide for rechargeable zinc-air battery technology,” *Southcon Conf. Rec.*, pp. 616–621, 1996, doi: 10.1109/southc.1996.535134.
- [11] F. Ridwan, N. Febriyan, M. A. Husin, and F. Aulia, “A Study on the Effect of Cellulose Nanocrystalline Paper on PVA-KOH Electrolyte Membranes for Increasing Ionic Conductivity,” *Int. J. Energy Prod. Manag.*, vol. 9, no. 2, pp. 113–120, 2024, doi: 10.18280/ijepm.090206.
- [12] S. Tombolesi, N. Zanieri, L. Bargnesi, M. Mernini, G. Lacarbonara, and C. Arbizzani, “A Sustainable Gel Polymer Electrolyte for Solid-State Electrochemical Devices,” *Polymers (Basel)*, vol. 15, no. 14, 2023, doi: 10.3390/polym15143087.
- [13] F. Ridwan, D. Agusta, M. A. Husin, and D. Dahlan, “Evaluation of the addition of cement ash to the PVA/TEOS/HCl gel electrolyte on the performance of aluminium air batteries,” *Mater. Sci. Energy Technol.*, vol. 8, pp. 24–31, 2025, doi: <https://doi.org/10.1016/j.mset.2024.07.003>.
- [14] S. Xue and Z. Wang, “Electrochemically synthesized copper nanotubes and nanorod arrays in polycarbonate membranes,” *Surf. Rev. Lett.*, vol. 13, no. 6, pp. 759–762, 2006, doi: 10.1142/S0218625X06008815.
- [15] O. Çakir, “Chemical etching of aluminium,” *J. Mater. Process. Technol.*, vol. 199, no. 1, pp. 337–340, 2008, doi: 10.1016/j.jmatprotec.2007.08.012.
- [16] N. Lim, Y. S. Choi, A. Efremov, and K. H. Kwon, “Dry etching performance and gas-phase parameters of c<sub>6</sub>f<sub>12</sub>o + ar plasma in comparison with cf<sub>4</sub> + ar,” *Materials (Basel)*, vol. 14, no. 7, 2021, doi: 10.3390/ma14071595.

- [17] R. Wrobel, D. Salt, N. Simpson, and P. H. Mellor, “Comparative study of copper and aluminium conductors - future cost effective PM machines,” *7th IET Int. Conf. Power Electron. Mach. Drives, PEMD 2014*, pp. 1–6, 2014.

