

DAFTAR PUSTAKA

- [1] X. Zhao, J. Liu, J. Li, X. Liang, W. Zhou, and S. Peng, "Strategies and techniques for improving heat resistance and mechanical performances of poly(lactic acid) (PLA) biodegradable materials," *Int J Biol Macromol*, vol. 218, pp. 115–134, Oct. 2022, doi: 10.1016/J.IJBIOMAC.2022.07.091.
- [2] O. Dagdag *et al.*, "Viscosity of epoxy resins based on aromatic diamines, glucose, bisphenolic and bio-based derivatives: a comprehensive review," *Journal of Polymer Research*, vol. 29, no. 5, May 2022, doi: 10.1007/s10965-022-03040-3.
- [3] D. Grosso, "How to exploit the full potential of the dip-coating process to better control film formation," *J Mater Chem*, vol. 21, no. 43, pp. 17033–17038, Nov. 2011, doi: 10.1039/c1jm12837j.
- [4] Mawardi Cholid, *Pengantar 3D Printing*. Politeknik Negeri Media Kreatif, 2020.
- [5] N. Divakaran, J. P. Das, A. K. P V, S. Mohanty, A. Ramadoss, and S. K. Nayak, "Comprehensive review on various additive manufacturing techniques and its implementation in electronic devices," *J Manuf Syst*, vol. 62, pp. 477–502, Jan. 2022, doi: 10.1016/J.JMSY.2022.01.002.
- [6] F. M. Mwema and E. T. Akinlabi, "Basics of Fused Deposition Modelling (FDM)," in *SpringerBriefs in Applied Sciences and Technology*, Springer, 2020, pp. 1–15. doi: 10.1007/978-3-030-48259-6_1.
- [7] H. Sanjaya, S. Arief, and A. Alif, "Pembuatan Lapisan Tipis Tio₂ Pada Plat Kaca Dengan Metoda Dip-Coating Dan Uji Aktivitas Fotokatalisnya Pada Air Gambut," Padang, 2013.
- [8] Aegerter Michel A. and Martin Mennig, *Sol-Gel Technologies for Glass Producers and Users*, 1st Edition. New York: Springer US, 2004. doi: 10.1007/978-0-387-88953-5.
- [9] D. Frederichi, M. Heloisa Neves Olsen Scaliante, and R. Bergamasco, "Structured photocatalytic systems: photocatalytic coatings on low-cost

structures for treatment of water contaminated with micropollutants-a short review”, doi: 10.1007/s11356-020-10022-9/Published.

- [10] A. Abdullah, A. Ali, and R. Demirboga, “A Review for Characterization of Silica Fume and Its Effects on Concrete Properties,” 2011. [Online]. Available: <https://www.researchgate.net/publication/265803466>
- [11] “HDK® N20 Pyrogenic Silica Product Description,” May 06, 2009, *Wacker Chemie AG, Munchen*.
- [12] R. R. Retamal Marín, F. Babick, G. G. Lindner, M. Wiemann, and M. Stintz, “Effects of sample preparation on particle size distributions of different types of silica in suspensions,” *Nanomaterials*, vol. 8, no. 7, Jul. 2018, doi: 10.3390/nano8070454.
- [13] George. Wypych, *Handbook of Fillers (Fourth Edition)*. ChemTec Publishing, 2016.
- [14] M. Lutfi Hidayat, “Studi Penambahan Aluminium Hidroksida Terhadap Sifat Mekanik Dan Morfologi Komposit Tahan Api Glass Fiber Reinforced Polymer Untuk Material Interior Kereta Api,” Institut Teknologi Sepuluh November, Surabaya, 2019.
- [15] Rabbiatul Nor, Norzali Adawiyah, Badri Khairiah Haji, and Nuawi Mohd Zaki, “Effect of Aluminum Hydroxide Loading on the Compression Stress and Modulus, Thermal Conductivity and Acoustic Properties of Palm-Based Polyurethane Hybrid Composite,” *Sains Malays*, vol. 40, no. 4, pp. 1–6, Jul. 2010.
- [16] M. S. R. Sarker, M. Z. Alam, M. R. Qadir, M. A. Gafur, and M. Moniruzzaman, “Extraction and characterization of alumina nanopowders from aluminum dross by acid dissolution process,” *International Journal of Minerals, Metallurgy and Materials*, vol. 22, no. 4, pp. 429–436, Apr. 2015, doi: 10.1007/s12613-015-1090-2.
- [17] Ellis Bryan, *Chemistry and Technology of Epoxy Resins*. Springer Netherlands, 1993. doi: 10.1007/978-94-011-2932-9.
- [18] E. Sulaiman, Y. M. Yeo, and Y. T. Chong, “The flexural strengths of five commercially available tooth-coloured restorative materials,” *Ann Dent*, vol. 14, no. 1, pp. 39–45, Dec. 2007, doi: 10.22452/adum.vol14no1.7.

- [19] K. M. Kim, H. Kim, and H. J. Kim, “Enhancing thermo-mechanical properties of epoxy composites using fumed silica with different surface treatment,” *Polymers (Basel)*, vol. 13, no. 16, Aug. 2021, doi: 10.3390/polym13162691.
- [20] K. Shaker *et al.*, “Mechanical Performance of Glass/Epoxy Composites Loaded with Silane-Treated Aluminum Hydroxide Fillers,” *Polymers (Basel)*, vol. 15, no. 17, Sep. 2023, doi: 10.3390/polym15173514.
- [21] K. G. Jaya Christiyan, U. Chandrasekhar, and K. Venkateswarlu, “Flexural Properties of PLA Components Under Various Test Condition Manufactured by 3D Printer,” *Journal of The Institution of Engineers (India): Series C*, vol. 99, no. 3, pp. 363–367, Jun. 2018, doi: 10.1007/s40032-016-0344-8.

