

DAFTAR PUSTAKA

- [1] H. Rahman *et al.*, “Water-Based Lubricants : Development , Properties , and Performances,” pp. 1–28, 2021.
- [2] H. Xie *et al.*, “Tribological performances of SiO₂ /graphene combinations as water-based lubricant additives for magnesium alloy rolling,” *Appl. Surf. Sci.*, vol. 475, no. October 2018, pp. 847–856, 2019, doi: 10.1016/j.apsusc.2019.01.062.
- [3] P. Kim, L. Shi, A. Majumdar, and P. L. McEuen, “Thermal transport measurements of individual multiwalled nanotubes,” *Phys. Rev. Lett.*, vol. 87, no. 21, pp. 215502-1-215502–4, 2001, doi: 10.1103/PhysRevLett.87.215502.
- [4] I. Khoswan, H. Nassar, M. Assali, A. AbuSafa, S. Sawalha, and H. S. Hilal, “Why Carbon Nanotubes Improve Aqueous Nanofluid Thermal Conductivity: A Qualitative Model Critical Review,” *Processes*, vol. 12, no. 4, pp. 1–26, 2024, doi: 10.3390/pr12040834.
- [5] A. Kotia, K. Chowdary, I. Srivastava, S. K. Ghosh, and M. K. A. Ali, “Carbon nanomaterials as friction modifiers in automotive engines: Recent progress and perspectives,” *J. Mol. Liq.*, vol. 310, p. 113200, 2020, doi: 10.1016/j.molliq.2020.113200.
- [6] R. Siskayanti and M. E. Kosim, “Analisis Pengaruh Bahan Dasar Terhadap Indeks Viskositas Pelumas Berbagai Kekentalan,” *J. Rekayasa Proses*, vol. 11, no. 2, p. 94, 2018, doi: 10.22146/jrekpros.31147.
- [7] P. Yang, X. Zhao, Y. Liu, and X. Lai, “Preparation and tribological properties of dual-coated CuO nanoparticles as water based lubricant additives,” *J. Nanosci. Nanotechnol.*, vol. 16, no. 9, pp. 9683–9689, 2016, doi: 10.1166/jnn.2016.12394.

- [8] H. T. Nguyen and K. H. Chung, "Assessment of tribological properties of Ti_3C_2 as a water-based lubricant additive," *Materials (Basel)*, vol. 13, no. 23, pp. 1–14, 2020, doi: 10.3390/ma13235545.
- [9] D. A. Putri, P. Studi, T. Sipil, J. T. Sipil, F. Teknik, and U. Malikussaleh, "PENGARUH PENGGUNAAN CARBON NANOTUBE," 2024.
- [10] E. Goldmann, M. Górski, and B. Klemczak, "Recent advancements in carbon nano-infused cementitious composites," *Materials (Basel)*, vol. 14, no. 18, 2021, doi: 10.3390/ma14185176.
- [11] B. R. Ahmed, A. J. Hussein, D. Saleh, and R. S. M. Rashid, "Influence of Carbon Nanotubes (CNTs) in the Cement Composites," *IOP Conf. Ser. Earth Environ. Sci.*, vol. 357, no. 1, 2019, doi: 10.1088/1755-1315/357/1/012024.
- [12] V. A and S. M., "Usage of Carbon nanotubes and nano fibers in cement and concrete: A review," *Int. J. Eng. Technol.*, vol. 9, no. 2, pp. 564–569, 2017, doi: 10.21817/ijet/2017/v9i2/170902045.
- [13] P. R. Thakre, Y. Bisrat, and D. C. Lagoudas, "Electrical and mechanical properties of carbon nanotube-epoxy nanocomposites," *J. Appl. Polym. Sci.*, vol. 116, no. 1, pp. 191–202, 2010, doi: 10.1002/app.31122.
- [14] L. Azmi, "Pengaruh Penambahan Surfaktan Terhadap Kestabilan Emulsi Solar-Air Sebagai Bahan Bakar Alternatif pada Mesin Diesel," *Skripsi*, pp. 1–73, 2016.
- [15] I. Malang, "KARAKTERISTIK SISTEM NIOSOM DENGAN VARIASI KONSENTRASI SPAN 60 SEBAGAI SURFAKTAN MENGGUNAKAN KUERSETIN Oleh : NOVENDA ANDEN BIMALA FAKULTAS KEDOKTERAN DAN ILMU-ILMU KESEHATAN," 2017.
- [16] D. Rahmadiawan *et al.*, "Experimental investigation on stability, tribological, viscosity, and thermal conductivity of MXene/Carboxymethyl cellulose (CMC) water-based nanofluid lubricant," *J. Tribol.*, vol. 39, no.

September, pp. 36–50, 2023.

- [17] M. Ariansyah, Riyan dan Heriyani, *TEKNOLOGI PELUMASAN*. Kota Solok, Sumatera Barat: PT MAFY MEDIA LITERASI INDONESIA, 2023.
- [18] M. Ariyansah, Riyan dan Heriyani, *Teknologi Pelumasan*. Solok, Sumatera Barat: PT Mafy Media Literasi Indonesia, 2023.
- [19] R. Andwika Simatupang, Ramli, and Mahrizal, “Optimasi Kecepatan Putar Pengadukan Dan Waktu Pengadukan Terhadap Kualitas Fisika Biodiesel Dari Minyak Kelapa,” *Pillar Phys.*, vol. 7, no. April, pp. 89–96, 2016.
- [20] A. Wijayani, K. Ummah, and S. Tjahjani, “CHARACTERIZATION OF CARBOXY METHYL CELLULOSE (CMC) FROM *Eichornia crassipes* (Mart) Solms,” *Indones. J. Chem.*, vol. 5, no. 3, pp. 228–231, 2010, doi: 10.22146/ijc.21795.
- [21] N. Kamal, “Pengaruh Bahan Aditif Cmc (Carboxyl Methyl Cellulose) Terhadap Beberapa Parameter Pada Larutan Sukrosa,” *J. Teknol.*, vol. I, no. 17, pp. 78–85, 2010.
- [22] A. Allaoui and N. Bounia, “Rheological and Electrical Transitions in Carbon Nanotube/Epoxy Suspensions,” *Curr. Nanosci.*, vol. 6, no. 2, pp. 158–162, 2010, doi: 10.2174/157341310790945669.
- [23] D. Ratnasari and R. N. Puspitasari, “OPTIMASI FORMULA SEDIAAN KRIM ANTI-AGING DARI EKSTRAK TERONG UNGU (*Solanum melongena* L.) DAN TOMAT (*Solanum lycopersicum* L.),” *J. Ris. Kesehat.*, vol. 7, no. 2, p. 66, 2018, doi: 10.31983/jrk.v7i2.3703.
- [24] Rosdanelli Hasibuan, Fransiska Adventi, and Rahmad Parsaulian Rtg, “PENGARUH SUHU REAKSI, KECEPATAN PENGADUKAN DAN WAKTU REAKSI PADA PEMBUATAN SABUN PADAT DARI MINYAK KELAPA (*Cocos nucifera* L.),” *J. Tek. Kim. USU*, vol. 8, no. 1, pp. 11–17, 2019, doi: 10.32734/jtk.v8i1.1601.

- [25] M. Gulzar *et al.*, “Tribological performance of nanoparticles as lubricating oil additives,” *J. Nanoparticle Res.*, vol. 18, no. 8, 2016, doi: 10.1007/s11051-016-3537-4.
- [26] E. Toolbox, “Water - Dynamic and Kinematic Viscosity at Various Temperatures and Pressures.” https://www.engineeringtoolbox.com/water-dynamic-kinematic-viscosity-d_596.html (accessed Mar. 05, 2025).
- [27] M. Hemmat Esfe and S. Esfandeh, “A new generation of hybrid-nanofluid: thermal properties enriched lubricant fluids with controlled viscosity amount,” *SN Appl. Sci.*, vol. 2, no. 7, pp. 1–16, 2020, doi: 10.1007/s42452-020-2875-0.
- [28] Y. J. J. Jason, H. G. How, Y. H. Teoh, and H. G. Chuah, “A study on the tribological performance of nanolubricants,” *Processes*, vol. 8, no. 11, pp. 1–33, 2020, doi: 10.3390/pr8111372.

