

DAFTAR PUSTAKA

- [1] J. Liu et al, "*Study on lubricating characteristic and tool wear with water vapor as coolant and lubricant in green cutting*. 2007. [Online]. Available: <https://doi.org/10.1016/j.wear.2006.06.014>
- [2] D. P. M. Namb, "*Influence of coolant in machinability of titanium alloy*." 2011.
- [3] J. C. M.C. Shaw, "*Metal cutting principles Vol. 2*." Newyork, 2005.
- [4] R. R. Moura, M. B. da Silva, Á. R. Machado, and W. F. Sales, "The effect of application of cutting fluid with solid lubricant in suspension during cutting of Ti-6Al-4V alloy," *Wear*, vol. 332–333, pp. 762–771, 2015, doi: 10.1016/j.wear.2015.02.051.
- [5] H. Z. A. Zailani, R. Hamidon, M. S. Hussin and and S. S. Hadi, "*The influence of solid lubricant in machining*." 2011.
- [6] Z. Lu *et al.*, "MoS₂ Nanomaterials as Lubricant Additives: A Review," *Lubricants*, vol. 11, no. 12, 2023, doi: 10.3390/lubricants11120527.
- [7] C. Zhu, Z. He, L. Xiong, J. Li, Y. Wu, and L. Li, "Study on the Influence of the MoS₂ Addition Method on the Tribological and Corrosion Properties of Greases," *Lubricants*, vol. 11, no. 12, 2023, doi: 10.3390/lubricants11120517.
- [8] K. K. Singh, R. Prabhu B, S. Choudhary, C. Pramanik, and N. S. John, "Effect of Graphene and MoS₂ Flakes in Industrial Oils to Enhance Lubrication," *ACS Omega*, vol. 4, no. 11, pp. 14569–14578, 2019, doi: 10.1021/acsomega.9b01799.
- [9] C. Johan, "Karakteristik Keausan Pahat HSS Pada Pemesinan Baja St 60," *J. Tek. Mesin*, pp. 1–5, 2018.

- [10] J. H. Sudarto, "Mekanisme Keausan Pahat Pada Pemesinan," *J. Momentum Jur. Tek. Mesin Politek. Negeri Semarang*, vol. 6, no. 1, pp. 9–16, 2010.
- [11] V. P. Astakhov and J. P. Davim, "m, 'Tools (Geometry and Material) and ToolWear'.".
- [12] P. M. B. and W. W. O, "'Wear control handbook,'" *ASME*, 1980.
- [13] Darmanto, "Mengenal Pelumas Pada Mesin," *Momentum*, vol. 7, no. 1, pp. 5–10, 2011.
- [14] F. Burhanuddin Muhammad, "Analisis Perbandingan Tipe Pelumas Berdasarkan Wujud pada Studi Kasus Pelumasan pada Gearbox Sepeda Motor," *J. Rekayasa Mesin*, vol. 6, no. 2, pp. 111–118, 2015, doi: 10.21776/ub.jrm.2015.006.02.4.
- [15] Y. Zhang, C. Li, D. Jia, D. Zhang, and X. Zhang, "Experimental evaluation of MoS₂ nanoparticles in jet MQL grinding with different types of vegetable oil as base oil," *J. Clean. Prod.*, vol. 87, no. C, pp. 930–940, 2015, doi: 10.1016/j.jclepro.2014.10.027.
- [16] A. R. Nasution, A. Affandi, K. Umurani, R. Rahmatullah, and M. Refan, "Analysis of Cutting Fluid on Mass Loss of Carbide Insert in the Milling Process," *Media Mesin Maj. Tek. Mesin*, vol. 25, no. 1, pp. 31–40, 2024, doi: 10.23917/mesin.v25i1.2896.
- [17] Y. Rai, A. Neville, and A. Morina, "Transient processes of MoS₂ tribofilm formation under boundary lubrication," *Lubr. Sci.*, vol. 28, no. 7, pp. 449–471, 2016, doi: 10.1002/ls.1342.
- [18] U. Heisel *et al.*, "Application of minimum quantity cooling lubrication technology in cutting processes," *Prod. Eng.*, vol. II, no. 1, pp. 49–54, 1994, [Online]. Available: <http://elib.uni-stuttgart.de/opus/volltexte/2010/5072>