

BIBIOLOGRAPHY

- [1] J. Fleischer, R. Pabst, and S. Kelemen, "Heat flow simulation for dry machining of power train castings," *CIRP Ann. - Manuf. Technol.*, vol. 56, no. 1, pp. 117–122, 2007, doi: 10.1016/j.cirp.2007.05.030.
- [2] A. Mudjijanto, M., Destriyanto, H., & Achmadi, "Pengaruh Jenis Media Pendingin Terhadap Getaran Dan Nilai Kekasaran Permukaan Pada Pembubutan Material Baja AISI 1045.," *J. Crankshaft*, vol. 7(1), pp. 12–18, 2024.
- [3] H. Fadel, "Pengaruh Penambahan Nano Partikel MoS₂ Pada Minyak Sawit Sebagai Bahan Pelumas Terhadap Keausan Pada Ball Bearing.," 2024.
- [4] D. Teori, "Kajian Pustaka Tentang Keausan Pada Pahat Bubut," *Rotasi*, vol. 12, no. 2, pp. 38–41–41, 2010.
- [5] L. Čerče, F. Pušavec, and J. Kopač, "3D cutting tool-wear monitoring in the process," *J. Mech. Sci. Technol.*, vol. 29, no. 9, pp. 3885–3895, 2015, doi: 10.1007/s12206-015-0834-2.
- [6] D. Noerhamzah, "Pengaruh Gerak Makan Dan Putaran Spindel Terhadap Keausan Pahat Hss Pada Proses Pemesinan End Milling Komposit Berpenguat Serat Nenas Diajukan," 2019.
- [7] P. I. P. Sari, "Pengaruh Variasi Serat Tkks Dan Gerak Makan Terhadap Kekasaran Permukaan Dan Keausan Tepi Hasil Proses Pemesinan Bubut Pada Material Komposit," 2019.
- [8] Peterson M B and Winer W O, "Wear control handbook," ASME, 1980.
- [9] V. P. Astakhov dan S. Joksč, *Metalworking fluids (MWFs) for cutting and grinding: Fundamentals and recent advances*. 2012. doi: 10.1016/B978-0-85709-061-4.50011-6.
- [10] S. Anandita, "Aplication Of MoS₂ Based Cutting Fluids In Minimum Quantity Lubrication During Machinning Of Stainless Steel AISI 316L

Master of Technology In Production Engineering S Anandita Roll No : 212ME2289,” p. 79, 2014.

- [11] T. Sunil, M. Sandeep, R. Kumaraswami, and A. Shravan, “A critical review on solid lubricants,” *Int. J. Mech. Eng. Technol.*, vol. 7, no. 5, pp. 193–199, 2016.
- [12] R. R. Moura, M. B. da Silva, Á. R. Machado, and W. F. Sales, “The effect of application of cutting fluid with solid lubricant in suspension during cutting of Ti-6Al-4V alloy,” *Wear*, vol. 332–333, pp. 762–771, 2015, doi: 10.1016/j.wear.2015.02.051.
- [13] I. E. Uflyand, V. A. Zhinzhiro, and V. E. Burlakova, “Metal-containing nanomaterials as lubricant additives: State-of-the-art and future development,” *Friction*, vol. 7, no. 2, pp. 93–116, 2019, doi: 10.1007/s40544-019-0261-y.
- [14] M. Gulzar *et al.*, “Tribological performance of nanoparticles as lubricating oil additives,” *J. Nanoparticle Res.*, vol. 18, no. 8, p. 223, 2016, doi: 10.1007/s11051-016-3537-4.
- [15] A. R. Nasution, A. Affandi, K. Umurani, R. Rahmatullah, and M. Refan, “Analysis of Cutting Fluid on Mass Loss of Carbide Insert in the Milling Process,” *Media Mesin Maj. Tek. Mesin*, vol. 25, no. 1, pp. 31–40, 2024, doi: 10.23917/mesin.v25i1.2896.
- [16] Y. Rai, A. Neville, and A. Morina, “Transient processes of MoS₂ tribofilm formation under boundary lubrication,” *Lubr. Sci.*, vol. 28, no. 7, pp. 449–471, 2016, doi: 10.1002/ls.1342.
- [17] [1] J. Liu *et al.*, “Study on lubricating characteristic and tool wear with water vapor as coolant and lubricant in green cutting. 2007. [Online]. Available: <https://doi.org/10.1016/j.wear.2006.06.014>
- [2] D. P. M. Namb, “Influence of coolant in machinability of titanium alloy.” 2011.
- [3] J. C. M.C. Shaw, “Metal cutting principles Vol. 2.” Newyork, 2005.
- [4] R. R. Moura, M. B. da Silva, Á. R. Machado, and W. F. Sales, “The effect

- of application of cutting fluid with solid lubricant in suspension during cutting of Ti-6Al-4V alloy,” *Wear*, vol. 332–333, pp. 762–771, 2015, doi: 10.1016/j.wear.2015.02.051.
- [5] H. Z. A. Zailani, R. Hamidon, M. S. Hussin and S. S. Hadi, “*The influence of solid lubricant in machining.*” 2011.
 - [6] Z. Lu *et al.*, “MoS₂ Nanomaterials as Lubricant Additives: A Review,” *Lubricants*, vol. 11, no. 12, 2023, doi: 10.3390/lubricants11120527.
 - [7] C. Zhu, Z. He, L. Xiong, J. Li, Y. Wu, and L. Li, “Study on the Influence of the MoS₂ Addition Method on the Tribological and Corrosion Properties of Greases,” *Lubricants*, vol. 11, no. 12, 2023, doi: 10.3390/lubricants11120517.
 - [8] K. K. Singh, R. Prabhu B, S. Choudhary, C. Pramanik, and N. S. John, “Effect of Graphene and MoS₂ Flakes in Industrial Oils to Enhance Lubrication,” *ACS Omega*, vol. 4, no. 11, pp. 14569–14578, 2019, doi: 10.1021/acsomega.9b01799.
 - [9] C. Johan, “Karakteristik Keausan Pahat HSS Pada Pemesinan Baja St 60,” *J. Tek. Mesin*, pp. 1–5, 2018.
 - [10] J. H. Sudarto, “Mekanisme Keausan Pahat Pada Pemesinan,” *J. Momentum Jur. Tek. Mesin Politek. Negeri Semarang*, vol. 6, no. 1, pp. 9–16, 2010.
 - [11] V. P. Astakhov and J. P. Davim, “m, ‘Tools (Geometry and Material) and ToolWear’.”
 - [12] P. M. B. and W. W. O, ““Wear control handbook,”” *ASME*, 1980.
 - [13] Darmanto, “Mengenal Pelumas Pada Mesin,” *Momentum*, vol. 7, no. 1, pp. 5–10, 2011.
 - [14] F. Burhanuddin Muhammad, “Analisis Perbandingan Tipe Pelumas Berdasarkan Wujud pada Studi Kasus Pelumasan pada Gearbox Sepeda Motor,” *J. Rekayasa Mesin*, vol. 6, no. 2, pp. 111–118, 2015, doi: 10.21776/ub.jrm.2015.006.02.4.
 - [15] Y. Zhang, C. Li, D. Jia, D. Zhang, and X. Zhang, “Experimental evaluation of MoS₂ nanoparticles in jet MQL grinding with different types of vegetable oil as base oil,” *J. Clean. Prod.*, vol. 87, no. C, pp. 930–940, 2015, doi: 10.1016/j.jclepro.2014.10.027.
 - [16] A. R. Nasution, A. Affandi, K. Umurani, R. Rahmatullah, and M. Refan, “Analysis of Cutting Fluid on Mass Loss of Carbide Insert in the Milling Process,” *Media Mesin Maj. Tek. Mesin*, vol. 25, no. 1, pp. 31–40, 2024, doi: 10.23917/mesin.v25i1.2896.
 - [17] Y. Rai, A. Neville, and A. Morina, “Transient processes of MoS₂ tribofilm formation under boundary lubrication,” *Lubr. Sci.*, vol. 28, no. 7, pp. 449–

471, 2016, doi: 10.1002/ls.1342.

- [18] U. Heisel *et al.*, “Application of minimum quantity cooling lubrication technology in cutting processes,” *Prod. Eng.*, vol. II, no. 1, pp. 49–54, 1994.

