

DAFTAR PUSTAKA

- [1] T. Č. Prolić and A. Lepušić, “Effect of Foaming on the Antiwear,” pp. 38–46, 2012.
- [2] E. K. Ningsih, “Studi Eksperimen dan Analisa Keausan Journal Bearing Dry Contact Pada Rotary Valve Mesin Pembuat Pasta,” *J. Tek. ITS*, vol. 5, no. 1, pp. 58–64, 2016, doi: 10.12962/j23373539.v5i1.15207.
- [3] R. Rizaldy, N. Latief, and M. Agung, “Analisis Penggunaan Automatic Lubrication pada Reclaimer Silica di Rawmill V P . T . Semen Tonasa,” pp. 1–8, 2018.
- [4] R. M. Karina, M. Hanifuddin, and S. Wibowo, “Foaming Can Reduce Lubrication of Lubricants So Causing Wear,” *Sci. Contrib. Oil Gas*, vol. 41, no. 3, pp. 137–143, 2020, doi: 10.29017/scog.41.3.332.
- [5] N. D. Rizaldy and S. Johanes, “Analisa Perubahan Sifat Pelumas Terhadap Keausan Dan Performa Engine SAA12v140E-3 Komatsu HD785-7,” *J. Mater. Teknol. Proses War. Kemajuan Bid. Mater. Tek. Teknol. Proses*, vol. 2, no. 1, p. 6, 2021, doi: 10.22146/jmtp.66065.
- [6] DeltaLube, “Penyebab dan Solusi Foaming pada Oli Industri.” [Online]. Available: <https://www.deltalube.com/penyebab-dan-solusi-untuk-foaming-pada-oli-industri/#gsc.tab=0>
- [7] Eonchemicals, “foaming pada metalworking fluids,” p. 1, 2023. [Online]. Available: <https://www.eonchemicals.com/artikel/solusi-foaming-pada-metalworking-fluids/>
- [8] A. T. J. Hayward, “Methods of Measuring the Bubble Content of Bubbly Oil,” *Ind. Lubr. Tribol.*, vol. 13, no. 8, pp. 12–18, 1961, doi: 10.1108/eb052670.
- [9] M. Miftah Khoironi, N. Eka Mayangsari, and A. Setiawan, “Variasi Penambahan Asam Sulfat terhadap Kualitas Pelumas Hasil Pemurnian menggunakan Metode Acid-Clay Treatment,” vol. 5, no. 1, pp. 35–39, 2022.

- [10] M. F. Fibria and R. K. Rona Malam, “Analisis Kandungan Partikel Pengotor pada Minyak Lumas Kendaraan,” *Lembaran Publ. Miny. dan gas bumi*, vol. 44, no. 3, pp. 285–290, 2022, doi: 10.29017/lpmgb.44.3.170.
- [11] Petrolab, “Silicon pada Oil Analysis.” [Online]. Available: <https://petrolab.co.id/silicon-pada-oil-analysis/>
- [12] sefasgroup, “Kontaminasi Pelumas.” [Online]. Available: <https://sefasgroup.com/id/blog/kontaminasi-pelumas>
- [13] A. Gosalia and C. Sustainability, “Sustainability ...,” no. 82, pp. 2007–2012, 2012.
- [14] R. Siskayanti and M. E. Kosim, “Analisis Pengaruh Bahan Dasar Terhadap Indeks Viskositas Pelumas Berbagai Kekentalan,” *J. Rekayasa Proses*, vol. 11, no. 2, p. 94, 2018, doi: 10.22146/jrekpros.31147.
- [15] A. A. Pratama, P. T. Kimia, F. Teknik, and U. Negeri, “Proses Pembuatan Minyak Pelumas Mineral Dari Minyak Bumi,” *J. Kompetensi Tek.*, vol. 11, no. 1, pp. 19–24, 2019.
- [16] PT.Artomoro Sukses Abadi, “PERTAMINA Masri RG Iso VG 220.” [Online]. Available: <https://artomorosuksesabadi.co.id/pertamina-masri-rg-iso-vg-220/>
- [17] A. Zmitrowicz, “WEAR PATTERNS AND LAWS OF WEAR – A REVIEW Alfred Zmitrowicz,” no. 1803, pp. 219–253, 2006.
- [18] K. SaThierbach *et al.*, *ENGINEERING TRYBOLOGY*, vol. 3, no. 1. 2015. [Online]. Available: <http://dx.doi.org/10.1016/j.bpj.2015.06.056>
<https://academic.oup.com/bioinformatics/article-abstract/34/13/2201/4852827>
<https://semisupervised-3254828305/semisupervised.ppt>
<http://dx.doi.org/10.1016/j.str.2013.02.005>
<http://dx.doi.org/10.10>
- [19] K. P. Widiatmika, *On a Sliding Friction Model of Boundary Lubrication*, vol. 16, no. 2. 2015

