

DAFTAR PUSTAKA

- [1] Davim, J. P. (2011). *Machining of Hard Materials*. Springer
- [2] Dhar, N.R., Islam, S & Kamruzzaman, M. (2007). "Effect of Minimum Quantity Lubrication (MQL) on Tool Wear and Surface Roughness in Turning AISI-4340 Steel." *Journal of Materials Processing Technology*
- [3] NIOSH (National Institute for Occupational Safety and Health) (1998). "Criteria for a Recommended Standard: *Occupational Exposure to Metalworking Fluids*."
- [4] Srikant, R.R. & Rao, P.V. (2014). "Sustainable Machining Strategies for Cleaner Production." *Journal of Cleaner Production*,
- [5] Jayal, A.D., Balaji, A.K & Lin, H. (2010). "Sustainable Manufacturing: Modeling and Optimization Challenges at the Product, Process and System Levels." *CIRP Journal of Manufacturing Science and Technology*
- [6] Zhang, X., et al. (2023). "The use of water-based lubricants with MXene additives in machining processes."
- [7] Chen, L. & Liu, J. (2020). "The use of worn tools can increase surface roughness by up to 45% and dimensional deviation by up to 0.2 mm."
- [8] Liu, et al. (2023). "MXene has a thermal conductivity three times higher than graphene, superior lubricating properties with a friction coefficient of 0.1, and thermal stability up to 800°C."
- [9] Gasni, D, et al. (2023). "Kombinasi MXene (Ti_3C_2) dan CMC dalam pelumas nanofluida berbasis air meningkatkan stabilitas campuran serta viskositas hingga 46%."
- [10] Sevdiye Atakul Savrik, et al. (2021). "The use of Span 60 in spindle lubricants enables a more homogeneous distribution of nano zinc borate particles, prevents agglomeration, and enhances the stability of the mixture."

[11] Fikri, Ramadhan (2023). "Penggunaan grease dengan aplikator khusus untuk mengurangi suhu pemotongan pada proses membubut."

[12] Ifan Imbang Pangestu (2022). "Pemanfaatan minyak biji jarak sebagai cairan pendingin pada mesin bubut terhadap kekasaran dan kekerasan Aluminium 6061."

[13] Rochim, T. (1993). *Teori dan Teknologi Proses Pemesinan*. Bandung: Erlangga

[14] Kalpakjian, S. & Schmid, S. (2014). *Manufacturing Engineering and Technology*

[15] Sreejith, P. S., & Ngoi, B. K. A. (2000). *Dry Machining: Machining of the Future*. Journal of Materials Processing Technology.

[16] Groover, M.P. (2011). *Fundamentals of Modern Manufacturing: Materials, Processes, and Systems*. Wiley.

[17] Patel, K., & Sharma, A. (2015). *A Review on Effect of Cutting Fluids in Machining*. International Journal of Science and Research.

[18] Jawahir, I. S., et al. (2006). *Dry and Near-Dry Machining: Review of Feasibility*. Machining Science and Technology.

[19] Khan, M. M. A., et al. (2009). *Effect of Minimum Quantity Lubrication on Turning AISI 9310 Alloy Steel Using Vegetable Oil-Based Cutting Fluid*. Journal of Materials Processing Technology.

[20] Chandrashekhar, S., et al. (2018). *Performance of Nanofluids in Machining: A Review*. Journal of Manufacturing Processes

[21] Naguib, M., et al. (2011). "Two-dimensional transition metal carbides."

[22] Anasori, B., Lukatskaya, M. R., & Gogotsi, Y. (2017). *2D Metal Carbides and Nitrides (MXenes) for Energy Storage*. Nature Reviews Materials.

- [23] Ghasemi, H., Rezaei, M., & Ghanbari, M. (2022). *Effect of MXene nanoparticles on thermal and tribological properties of cutting fluid in turning of AISI 1045 steel*. Tribology International, 169, 107472.
- [24] Gao, Y., Zhang, Y., Xie, H., et al. (2021). *Recent advances of MXenes as new nanomaterials for thermal management applications*. Journal of Materials Chemistry C, 9(3), 786–802.
- [25] Sharma, V. S., et al. (2017). *Review of Coolant Techniques in Machining and Scope of Minimum Quantity Lubrication (MQL) System*. International Journal of Precision Engineering.
- [26] Chen, H., et al. (2021). *Tribological Performance of Ti_3C_2 MXene Nanosheets as Lubricant Additives*. Tribology International.
- [27] Zhao, Barber, & Zou (2002). *A study of flank wear in orthogonal cutting with internal cooling*. Wear 253. pp: 957-962
- [28] Bolashetty, and Mukkamala, 2018. *Nano-Cutting Fluid for Enhancement of Metal Cutting Performance*. ICESMART – 2015. Vol 3 (19)
- [29] Bhushan, (2022). *Effect of tool wear on surface roughness in machining of AA7075/ 10 wt.% SiC composite*, Composites Part C. Vol 8
- [30] Sönmez, (2023). *Machining of Hard-to-cut AISI 4462 Duplex Stainless Steel with an Environmentally Friendly Approach with Vortex Tube*. Journal of Mechanical Engineering. 69(7-8). pp: 308-316
- [31] Sun, & To. (2018). *Effect of Machining Parameters and Tool Wear on Surface Uniformity in Micro-Milling*. Micromachines (Basel). 9(6), pp: 268
- [32] Li, Lai, Li, Feng & Ni. (2008). *Modelling and experimental analysis of the effects of tool wear, minimum chip thickness and micro tool geometry on the surface roughness in micro-end-milling*. J. Micromech. Microeng. 18 . pp:12
- [33] Sönmez, Fikret. *"Analysis of tool wear and surface roughness in machining*

of AISI 4462 duplex stainless steel" Materials Testing, vol. 65, no. 10, 2023, pp. 1561-1570

