

## DAFTAR PUSTAKA

- [1] H. M. C. d. Azeredo, “Nanocomposites for food packaging applications,” *Food Res. Int.*, vol. 42, no. 9, pp. 1240–1253, 2009.
- [2] Y. S. L. Turng, R. Sabo, and C. Clemons, “Nanofibrillated cellulose (NFC) reinforced polyvinyl alcohol (PVOH) nanocomposites :properties , solubility of carbon dioxide , and foaming,” *springer*, pp. 1209–1223, 2012.
- [3] A. Dufresne, “Nanocellulose: A new ageless bionanomaterial,” *Mater. Today*, vol. 16, no. 6, pp. 220–227, 2013.
- [4] B. Soni, E. B. Hassan, and B. Mahmoud, “Chemical isolation and characterization of different cellulose nanofibers from cotton stalks,” *Carbohydr. Polym.*, vol. 134, pp. 581–589, 2015.
- [5] H. Wang, X. Zhang, Z. Jiang, W. Li, and Y. Yu, “A comparison study on the preparation of nanocellulose fibrils from fibers and parenchymal cells in bamboo (*Phyllostachys pubescens*),” *Ind. Crops Prod.*, vol. 71, pp. 80–88, 2015.
- [6] C. S. Julie Chandra, N. George, and S. K. Narayananakutty, “Isolation and characterization of cellulose nanofibrils from arecanut husk fibre,” *Carbohydr. Polym.*, vol. 142, pp. 158–166, 2016.
- [7] M. Asrofi *et al.*, “Isolation of Nanocellulose from Water Hyacinth Fiber (WHF) Produced via Digester-Sonication and Its Characterization,” *Fibers Polym.*, vol. 19, no. 8, pp. 1618–1625, 2018.
- [8] E. Syafri, A. Kasim, H. Abral, and A. Asben, “Cellulose nanofibers isolation and characterization from ramie using a chemical-ultrasonic treatment,” *Nat. Fibers*, vol. 00, no. 00, pp. 1–11, 2018.
- [9] M. Mahardika, S. Arief, A. Kasim, H. Abral, and M. Asrofi, “Production of Nanocellulose from Pineapple Leaf Fibers via High-Shear Homogenization and Ultrasonication,” *Fibers*, vol. 6, no. 2, p. 28, 2018.
- [10] H. Abral, V. Lawrensius, D. Handayani, and E. Sugiarti, “Preparation of nano-sized particles from bacterial cellulose using ultrasonication and their characterization,” *Carbohydr. Polym.*, vol. 191, no. February, pp. 161–167,

2018.

- [11] A. Alemdar and M. Sain, “Isolation and characterization of nanofibers from agricultural residues - Wheat straw and soy hulls,” *Bioresour. Technol.*, vol. 99, no. 6, pp. 1664–1671, 2008.
- [12] S. Koswara, “Khasiat Jahe,” *Ebookpangan.com*, 2008..
- [13] I. Stoilova, A. Krastanov, A. Stoyanova, P. Denev, and S. Gargova, “Antioxidant activity of a ginger extract (*Zingiber officinale*),” *Food Chem.*, vol. 102, no. 3, pp. 764–770, 2007.
- [14] S. Thomas, S. Gopi, J. Jacob, J. Haponiuk, and G. Peter, “Use of Ginger Nanofibers for the Preparation of Cellulose Nanocomposites and Their Antimicrobial Activities,” *Fibers*, vol. 6, no. 4, p. 79, 2018.
- [15] C. W. Irvin, C. C. Satam, J. C. Meredith, and M. L. Shofner, “Mechanical Reinforcement and Thermal Properties of PVA Tricomponent Nanocomposites with Chitin Nanofibers and Cellulose Nanocrystals,” *Compos. Part A*, 2018.
- [16] H. Abral, A. Hartono, F. Hafizulhaq, D. Handayani, E. Sugiarti, and O. Pradipta, “Characterization of PVA/cassava starch biocomposites fabricated with and without sonication using bacterial cellulose fiber loadings,” *Carbohydr. Polym.*, vol. 206, pp. 593–601, 2018.
- [17] J. Zhang *et al.*, “Enhancing the thermal and mechanical properties of polyvinyl alcohol ( PVA ) with boron nitride nanosheets and cellulose nanocrystals,” *Polymer (Guilderf.)*, vol. 148, pp. 101–108, 2018.
- [18] Z. Jahan, M. Bilal, K. Niazi, and yvind W. Gregersen, “Mechanical , thermal and swelling properties of Cellulose Nanocrystals / PVA nanocomposites membranes,” *Ind. Eng. Chem.*, vol. 57, pp. 113–124, 2017.
- [19] W. Li, J. Yue, and S. Liu, “Preparation of nanocrystalline cellulose via ultrasound and its reinforcement capability for poly(vinyl alcohol) composites,” *Ultrason. Sonochem.*, vol. 19, no. 3, pp. 479–485, 2012.
- [20] Z. Wang, X. Qiao, and K. Sun, “Rice straw cellulose nano fi brils reinforced poly ( vinyl alcohol ) composite fi lms,” vol. 197, no. April, pp. 442–450, 2018.
- [21] S. Xiao, R. Gao, L. K. Gao, and J. Li, “Poly(vinyl alcohol) films reinforced with

- nanofibrillated cellulose (NFC) isolated from corn husk by high intensity ultrasonication,” *Carbohydr. Polym.*, vol. 136, pp. 1027–1034, 2015.
- [22] G. B. Basim, “Properties of Materials EMA 6001 Section: 34H3,” pp. 1–7, 2018.
- [23] Hartono, *Hartono, Mohammad Rifai, and Handoko Subawi. Pengenalan Teknik Komposit. Deepublish, 2016.* .
- [24] J. William D. Callister and D. G. Rethwisch, “Materials science,” 2013.
- [25] F. C. A. Ticoalu, T. Aravinthan, “A review of current development in natural fiber composites for structural and infrastructure applications,” *Ed. Publ.*, vol. 130, no. 17, pp. 13-X1, 1997.
- [26] V. R. Raman Bharath, B. Vijaya Ramnath, and N. Manoharan, “Kenaf fibre reinforced composites: A review,” *ARP NJ Eng. Appl. Sci.*, vol. 10, no. 13, pp. 5483–5485, 2015.
- [27] J. Holbery and D. Houston, “Low-Cost Composites in Vehicle Manufacture,” *Nat. Polym. Compos. Automot. Appl.*, no. November, pp. 80–86, 2006.
- [28] E. T. Wardani, “Pengaruh ekstrak jahe (*Zingiber officinale Rosc.*) var. gajah terhadap kualitas spermatozoa mencit (*Mus musculus*) YANG terpapar 2-methoxyethanol,” *Dr. Diss.*
- [29] C. M. Hassan and N. A. Peppas, “Structure and morphology of freeze/thawed PVA hydrogels,” *Macromolecules*, vol. 33, no. 7, pp. 2472–2479, 2000.
- [30] R. Stevano, “Karakterisasi Plastik Biodegradable dari Campuran Kitosan dan Polivinil Alkohol Menggunakan Metode Tanpa Pelarut,” (*Skripsi*).
- [31] D. da Silva Perez, A. Dufresne, S. Tapin-Lingua, G. Siqueira, and J. Bras, “Mechanical properties of natural rubber nanocomposites reinforced with cellulosic nanoparticles obtained from combined mechanical shearing, and enzymatic and acid hydrolysis of sisal fibers,” *Cellulose*, vol. 18, no. 1, pp. 57–65, 2010.
- [32] M. de sá M. Souza Filho *et al.*, “Improvement of polyvinyl alcohol properties by adding nanocrystalline cellulose isolated from banana pseudostems,” *Carbohydr. Polym.*, vol. 112, pp. 165–172, 2014.
- [33] Z. Zhang *et al.*, “Mechanical properties, water swelling behavior, and

- morphology of swellable rubber compatibilized by PVA-g-PBA," *Polym. Eng. Sci.*, vol. 44, no. 1, pp. 72–78, 2004.
- [34] K. T. Shalumon, K. H. Anulekha, C. M. Girish, R. Prasanth, S. V. Nair, and R. Jayakumar, "Single step electrospinning of chitosan/poly(caprolactone) nanofibers using formic acid/acetone solvent mixture," *Carbohydr. Polym.*, vol. 80, no. 2, pp. 413–419, 2010.
- [35] D. M. Panaitescu, A. N. Frone, M. Ghiurea, and I. Chiulan, "Influence of storage conditions on starch/PVA films containing cellulose nanofibers," *Ind. Crops Prod.*, vol. 70, pp. 170–177, 2015.
- [36] A. S. Potulski, D. C., de Muniz, G. I. B., Klock, U., & de Andrade, "Influência da incorporação de celulose microfibrilada nas propriedades de resistência mecânicas do papel The influence of incorporation of microfibrillated cellulose on mechanical strength properties of paper.,," *Sci. For.*
- [37] W. Chen, H. Yu, Y. Liu, P. Chen, M. Zhang, and Y. Hai, "Individualization of cellulose nanofibers from wood using high-intensity ultrasonication combined with chemical pretreatments," *Carbohydr. Polym.*, vol. 83, no. 4, pp. 1804–1811, 2011.
- [38] P. A. Tipler, *FISIKA untuk Sains dan Teknik*. Erlangga.
- [39] N. . Yatarif, "Karakterisasi sinyal akustik untuk mendekripsi keabnormalan jaringan tubuh menggunakan ultrasonik," *Skripsi*, 2008.
- [40] B. . Hapsari, "Sintesis nanosfer berbasis ferrofluid dan poly lactic acid (PLA) dengan metode sonifikasi," *Skripsi*, 2009.
- [41] K. S. Suslick, *The chemistry of ultrasound from the yearbook of science and the future*. Chicago, USA: Encyclopedia Britannica, 1994.
- [42] A. M. Nafchi, A. K. Alias, S. Mahmud, and M. Robal, "Antimicrobial, rheological, and physicochemical properties of sago starch films filled with nanorod-rich zinc oxide," *J. Food Eng.*, vol. 113, no. 4, pp. 511–519, 2012.
- [43] ASTM, *Standard test method for tensile properties of plastic. D638-02a*. USA, 2002.
- [44] I. D. Mall, V. C. Srivastava, N. K. Agarwal, and I. M. Mishra, "Removal of

- congo red from aqueous solution by bagasse fly ash and activated carbon: Kinetic study and equilibrium isotherm analyses," *Chemosphere*, vol. 61, no. 4, pp. 492–501, 2005.
- [45] H. Abral *et al.*, "Mechanical properties of water hyacinth fibers - polyester composites before and after immersion in water," *Mater. Des.*, vol. 58, pp. 125–129, 2014.
- [46] H. S. Mansur, C. M. Sadahira, A. N. Souza, and A. A. P. Mansur, "FTIR spectroscopy characterization of poly (vinyl alcohol) hydrogel with different hydrolysis degree and chemically crosslinked with glutaraldehyde," *Mater. Sci. Eng. C*, vol. 28, no. 4, pp. 539–548, 2008.
- [47] X. Ma, P. R. Chang, and J. Yu, "Properties of biodegradable thermoplastic pea starch/carboxymethyl cellulose and pea starch/microcrystalline cellulose composites," *Carbohydr. Polym.*, vol. 72, no. 3, pp. 369–375, 2008.
- [48] A. Jokar, M. H. Azizi, Z. H. Esfehani, and S. Abbasi, "Effects of ultrasound time on the properties of methylcellulose-montmorillonite films," *Int. Nano Lett.*, vol. 7, no. 1, pp. 59–68, 2017.
- [49] H. Abral *et al.*, "Characterization of tapioca starch biopolymer composites reinforced with micro scale water hyacinth fibers," *starch*, vol. 70, no. 7–8, 2018.
- [50] R. Sakai, Y. Teramoto, and Y. Nishio, "Producing a magnetically anisotropic soft material: Synthesis of iron oxide nanoparticles in a carrageenan/PVA matrix and stretching of the hybrid gelatinous bulk," *Polym. J.*, vol. 50, no. 3, pp. 251–260, 2018.
- [51] M. M. Abudabbus *et al.*, "Biological activity of electrochemically synthesized silver doped polyvinyl alcohol/graphene composite hydrogel discs for biomedical applications," *Compos. Part B Eng.*, vol. 104, pp. 26–34, 2016.
- [52] D. Liu, X. Sun, H. Tian, S. Maiti, and Z. Ma, "Effects of cellulose nanofibrils on the structure and properties on PVA nanocomposites," *Cellulose*, vol. 20, no. 6, pp. 2981–2989, 2013.
- [53] J. Zhao, W. Zhang, X. Zhang, X. Zhang, C. Lu, and Y. Deng, "Extraction of

- cellulose nanofibrils from dry softwood pulp using high shear homogenization," *Carbohydr. Polym.*, vol. 97, no. 2, pp. 695–702, 2013.
- [54] J. George, K. V. Ramana, A. S. Bawa, and Siddaramaiah, "Bacterial cellulose nanocrystals exhibiting high thermal stability and their polymer nanocomposites," *Int. J. Biol. Macromol.*, vol. 48, no. 1, pp. 50–57, 2011.
- [55] F. Hafizulhaq, H. Abral, A. Kasim, S. Arief, and J. Affi, "Moisture Absorption and Opacity of Starch-Based Biocomposites Reinforced with Cellulose Fiber from Bengkoang," *Fibers*, vol. 6, no. 3, p. 62, 2018.
- [56] X. Li, C. Qiu, N. Ji, C. Sun, L. Xiong, and Q. Sun, "Mechanical , barrier and morphological properties of starch nanocrystals-reinforced pea starch films," vol. 121, pp. 155–162, 2015.
- [57] S. S. Wong, S. Kasapis, and Y. M. Tan, "Bacterial and plant cellulose modification using ultrasound irradiation," *Carbohydr. Polym.*, vol. 77, no. 2, pp. 280–287, 2009.
- [58] H. Nadia, M. C. Iqbal, and A. Ishak, "Physicochemical Properties and Characterization of Nata de Coco from Local Food Industries as a Source of Cellulose," *Sains Malaysiana*, vol. 41, no. 2, pp. 205–211, 2012.
- [59] H. Abral, A. S. Anugrah, F. Hafizulhaq, D. Handayani, E. Sugiarti, and A. N. Muslimin, "Effect of nanofibers fraction on properties of the starch based biocomposite prepared in various ultrasonic powers," *Int. J. Biol. Macromol.*, vol. 116, no. 2017, pp. 1214–1221, 2018.
- [60] Z. Q. Fu, L. J. Wang, D. Li, Q. Wei, and B. Adhikari, "Effects of high-pressure homogenization on the properties of starch-plasticizer dispersions and their films," *Carbohydr. Polym.*, vol. 86, no. 1, pp. 202–207, 2011.