

## DAFTAR PUSTAKA

- [1] T. S. Rappaport, *Wireless communications: principles and practice*, 2nd ed. in Prentice Hall communications engineering and emerging technologies series. Upper Saddle River, N.J: Prentice Hall PTR, 2002.
- [2] A. Stateczny, K. Gierlowski, and M. Hoeft, "Wireless Local Area Network Technologies as Communication Solutions for Unmanned Surface Vehicles," *Sensors*, vol. 22, no. 2, p. 655, Jan. 2022, doi: 10.3390/s22020655.
- [3] M. Viswanathan and V. Mathuranathan, *Wireless Communication Systems in Matlab: (Black & White Edition)*. Independently Published, 2018. [Online]. Available: <https://books.google.co.id/books?id=zry5uwEACAAJ>
- [4] E. Staudinger, R. Pöhlmann, A. Dammann, and S. Zhang, "Limits on Cooperative Positioning for a Robotic Swarm with Time of Flight Ranging over Two-Ray Ground Reflection Channel," *Electronics*, vol. 12, no. 9, p. 2139, May 2023, doi: 10.3390/electronics12092139.
- [5] Z. Liu, Q. Yao, Q. Li, L. Guo, and S. Hu, "Wireless Channel Model Based on Ray Tracing Algorithm in the Sea Environment," *Int. J. Antennas Propag.*, vol. 2024, pp. 1–14, Jan. 2024, doi: 10.1155/2024/3080895.
- [6] M. De Piante, M. Midrio, R. Rinaldo, I. Scagnetto, R. Specogna, and F. Trevisan, "Sub-Gigahertz *Path loss* Measurement Campaign in Marine Environment: A Case Study," *Sensors*, vol. 24, no. 8, p. 2582, Apr. 2024, doi: 10.3390/s24082582.
- [7] T. T. Oladimeji, P. Kumar, and N. O. Oyie, "Propagation *path loss* prediction modelling in enclosed environments for 5G networks: A review," *Heliyon*, vol. 8, no. 11, p. e11581, Nov. 2022, doi: 10.1016/j.heliyon.2022.e11581.
- [8] S. H. Triwibowo, E. Wahyudi, and S. Larasati, "Perbandingan Penggunaan Teknik Diversity pada Jaringan Gelombang Mikro di Lingkungan Danau," *J. Nas. Tek. Elektro Dan Teknol. Inf. JNTETI*, vol. 8, no. 3, p. 290, Aug. 2019, doi: 10.22146/jnteti.v8i3.525.
- [9] J. Yu, W. Chen, K. Yang, C. Li, F. Li, and Y. Shui, "*Path loss* Channel Model for Inland River Radio Propagation at 1.4 GHz," *Int. J. Antennas Propag.*, vol. 2017, pp. 1–15, 2017, doi: 10.1155/2017/5853724.
- [10] E. Eyuboglu, Z. Hasirci Tugcu, K. Kuzulugil, and I. H. Cavdar, "Modified REL-Based Piecewise *Path loss* Modeling Approach for Shore-to-Ship Communication at 5.6 GHz," *Appl. Sci.*, vol. 14, no. 22, p. 10324, Nov. 2024, doi: 10.3390/app142210324.
- [11] B. Yamamoto *et al.*, "Received Signal Strength Indication (RSSI) of 2.4 GHz and 5 GHz Wireless Local Area Network Systems Projected over Land and Sea for Near-Shore Maritime Robot Operations," *J. Mar. Sci. Eng.*, vol. 7, no. 9, p. 290, Aug. 2019, doi: 10.3390/jmse7090290.

- [12] J.-H. Lee, J. Choi, W.-H. Lee, J.-W. Choi, and S.-C. Kim, "Measurement and Analysis on Land-to-Ship Offshore Wireless Channel in 2.4 GHz," *IEEE Wirel. Commun. Lett.*, vol. 6, no. 2, pp. 222–225, Apr. 2017, doi: 10.1109/LWC.2017.2662380.
- [13] K. Udofia, "Determination Of *Path loss Exponent* And Shadowing For Wireless Network In Outdoor Environment," Aug. 2022.
- [14] S. Yi, "An Improved Two-Ray *Path loss* Model for Maritime Channels with Earth Curvature and Rough-Sea Effects," in *2026 9th International Conference on Advanced Electronic Technology, Computers and Software Engineering (AETCSE)*, Xi'an, China: IEEE, Mar. 2026, pp. 415–420. doi: 10.1109/AETCSE69203.2026.11504422.
- [15] J. Ge, T. Li, and T. Geng, "The Wireless Communications for Unmanned Surface Vehicle: An Overview," in *Intelligent Robotics and Applications*, vol. 10984, Z. Chen, A. Mendes, Y. Yan, and S. Chen, Eds., in Lecture Notes in Computer Science, vol. 10984. , Cham: Springer International Publishing, 2018, pp. 113–119. doi: 10.1007/978-3-319-97586-3\_10.
- [16] D. Sousa, D. Hernandez, F. Oliveira, M. Luís, and S. Sargento, "A Platform of Unmanned Surface Vehicle Swarms for Real Time Monitoring in Aquaculture Environments," *Sensors*, vol. 19, no. 21, p. 4695, Oct. 2019, doi: 10.3390/s19214695.
- [17] V. A. M. Jorge *et al.*, "A Survey on Unmanned Surface Vehicles for Disaster Robotics: Main Challenges and Directions," *Sensors*, vol. 19, no. 3, p. 702, Feb. 2019, doi: 10.3390/s19030702.
- [18] E. Pinto, P. Santana, and J. Barata, "On Collaborative Aerial and Surface Robots for Environmental Monitoring of Water Bodies," in *Technological Innovation for the Internet of Things*, vol. 394, L. M. Camarinha-Matos, S. Tomic, and P. Graça, Eds., in IFIP Advances in Information and Communication Technology, vol. 394. , Berlin, Heidelberg: Springer Berlin Heidelberg, 2013, pp. 183–191. doi: 10.1007/978-3-642-37291-9\_20.
- [19] J.-B. Wang, C. Zeng, C. Ding, H. Zhang, M. Lin, and J. Wang, "Unmanned Surface Vessel Assisted Maritime Wireless Communication Toward 6G: Opportunities and Challenges," *IEEE Wirel. Commun.*, vol. 29, no. 6, pp. 72–79, Dec. 2022, doi: 10.1109/MWC.008.2100554.
- [20] K. Ma, "Implementation And Evaluation Of Communication System For Autonomous Offshore Vehicles".
- [21] A. Kabanov and V. Kramar, "Marine Internet of Things Platforms for Interoperability of Marine Robotic Agents: An Overview of Concepts and Architectures," *J. Mar. Sci. Eng.*, vol. 10, no. 9, p. 1279, Sep. 2022, doi: 10.3390/jmse10091279.
- [22] H. Dinis, J. Rocha, T. Matos, L. M. Gonçalves, and M. Martins, "The Challenge of Long-Distance Over-the-Air Wireless Links in the Ocean: A

- Survey on Water-to-Water and Water-to-Land MIIOT Communication,” *Appl. Sci.*, vol. 12, no. 13, p. 6439, Jun. 2022, doi: 10.3390/app12136439.
- [23] N. Mehrnia and M. K. Ozdemir, “Novel maritime channel models for millimeter radiowaves,” in *2016 24th International Conference on Software, Telecommunications and Computer Networks (SoftCOM)*, Split, Croatia: IEEE, Sep. 2016, pp. 1–6. doi: 10.1109/SOFTCOM.2016.7772162.
- [24] Z. M. Kidane and W. Dargie, “Cross-technology interference: detection, avoidance, and coexistence mechanisms in the ISM bands,” *CCF Trans. Pervasive Comput. Interact.*, vol. 7, no. 3, pp. 356–375, Sep. 2025, doi: 10.1007/s42486-025-00185-0.
- [25] A. A. Eltholth, “Improved Spectrum Coexistence in 2.4 GHz ISM Band Using Optimized Chaotic Frequency Hopping for Wi-Fi and Bluetooth Signals,” *Sensors*, vol. 23, no. 11, p. 5183, May 2023, doi: 10.3390/s23115183.
- [26] R. E. C. Yunanta and T. Susyanto, “Analysis of WiFi Reliability at 2.4 GHz and 5 GHz Frequencies in the Environment of STMIK Sinar Nusantara Surakarta,” *MALCOM Indones. J. Mach. Learn. Comput. Sci.*, vol. 4, no. 3, pp. 1130–1138, Jul. 2024, doi: 10.57152/malcom.v4i3.1391.
- [27] J. Wang, X. Zhong, and S. Zhou, “Channel Allocation Algorithm Of Wi-Fi,” in *2023 International Conference on Computing, Networking and Communications (ICNC)*, Honolulu, HI, USA: IEEE, Feb. 2023, pp. 677–682. doi: 10.1109/ICNC57223.2023.10074461.
- [28] TEKON ELECTRONICS, “Line Of Sight - The Real Range Of Wireless Communications,” Tekon Electronics. Accessed: Aug. 02, 2026. [Online]. Available: <https://www.tekonelectronics.com/en/news/tekon-blog/line-of-sight-real-range-wireless-communications/>
- [29] F. Huang, X. Liao, and Y. Bai, “Multipath Channel Model for Radio Propagation over Sea Surface,” *Wirel. Pers. Commun.*, vol. 90, no. 1, pp. 245–257, Sep. 2016, doi: 10.1007/s11277-016-3343-4.
- [30] J. D. Parsons and J. D. Parsons, *The mobile radio propagation channel*, 2. ed., Repr. Chichester Weinheim: Wiley, 2001.
- [31] A. Gutiérrez-Gómez *et al.*, “A Propagation Study of LoRa P2P Links for IoT Applications: The Case of Near-Surface Measurements over Semitropical Rivers,” *Sensors*, vol. 21, no. 20, p. 6872, Oct. 2021, doi: 10.3390/s21206872.
- [32] J. Joo, H.-J. Jeong, and D. S. Han, “Verification of Fresnel Zone Clearance for Line-of-sight Determination in 5.9 GHz Vehicle-to-Vehicle Communications,” *Wirel. Pers. Commun.*, vol. 101, no. 1, pp. 239–249, Jul. 2018, doi: 10.1007/s11277-018-5685-6.
- [33] F. Huang, X. Liao, and Y. Bai, “Multipath Channel Model for Radio Propagation over Sea Surface,” *Wirel. Pers. Commun.*, vol. 90, no. 1, pp. 245–257, Sep. 2016, doi: 10.1007/s11277-016-3343-4.
- [34] A. Coelho, M. Lopes, B. Ferreira, R. Campos, and M. Ricardo, “Experimental evaluation of shore to unmanned surface vehicle Wi-Fi communications,” in



- 2018 *Wireless Days (WD)*, Dubai: IEEE, Apr. 2018, pp. 86–91. doi: 10.1109/WD.2018.8361699.
- [35] I. Shayea *et al.*, “Rain attenuation and worst month statistics verification and modeling for 5G radio link system at 26 GHz in Malaysia,” *Trans. Emerg. Telecommun. Technol.*, vol. 30, no. 12, p. e3697, Dec. 2019, doi: 10.1002/ett.3697.
- [36] M. G. Gaitan *et al.*, “Wireless radio link design to improve near-shore communication with surface nodes on tidal waters,” in *OCEANS 2021: San Diego – Porto*, San Diego, CA, USA: IEEE, Sep. 2021, pp. 1–8. doi: 10.23919/OCEANS44145.2021.9706046.
- [37] A. Goldsmith, “WIRELESS COMMUNICATIONS”.
- [38] A. F. Molisch, *Wireless communications*, 2nd ed. Chichester, West Sussex, U.K.: Wiley : IEEE, 2011.
- [39] N. H. Ranchagoda, K. Sithamparanathan, M. Ding, A. Al-Hourani, and K. M. Gomez, “Elevation-angle based two-ray *path loss* model for Air-to-Ground wireless channels,” *Veh. Commun.*, vol. 32, p. 100393, Dec. 2021, doi: 10.1016/j.vehcom.2021.100393.
- [40] E. Zochmann, K. Guan, and M. Rupp, “Two-ray models in mmWave communications,” in *2017 IEEE 18th International Workshop on Signal Processing Advances in Wireless Communications (SPAWC)*, Sapporo: IEEE, Jul. 2017, pp. 1–5. doi: 10.1109/SPAWC.2017.8227681.
- [41] H. Mohsin, K. Abdulameer, and Z. N. Khudhair, “Study and performance analysis of received signal strength indicator (RSSI) in wireless communication systems,” *Int. J. Eng. Technol.*, vol. 6, pp. 195–200, Jan. 2017, doi: 10.14419/ijet.v6i4.29558.
- [42] D. E. Houssaini, S. Khriji, K. Besbes, and O. Kanoun, “Performance Analysis of Received Signal Strength and Link Quality in Wireless Sensor Networks,” in *2018 15th International Multi-Conference on Systems, Signals & Devices (SSD)*, Hammamet: IEEE, Mar. 2018, pp. 173–178. doi: 10.1109/SSD.2018.8570634.
- [43] F. Zafari, A. Gkelias, and K. K. Leung, “A Survey of *Indoor* Localization Systems and Technologies,” *IEEE Commun. Surv. Tutor.*, vol. 21, no. 3, pp. 2568–2599, 2019, doi: 10.1109/COMST.2019.2911558.
- [44] S. Sadowski and P. Spachos, “RSSI-Based *Indoor* Localization With the Internet of Things,” *IEEE Access*, vol. 6, pp. 30149–30161, 2018, doi: 10.1109/ACCESS.2018.2843325.
- [45] R. M. Sandoval, A.-J. Garcia-Sanchez, and J. Garcia-Haro, “Improving RSSI-Based Path-Loss Models Accuracy for Critical Infrastructures: A Smart Grid Substation Case-Study,” *IEEE Trans. Ind. Inform.*, vol. 14, no. 5, pp. 2230–2240, May 2018, doi: 10.1109/TII.2017.2774838.
- [46] R. Gulia, “*Path loss* Model for 2.4GHZ *Indoor* Wireless Networks with Application to Drones”.

- [47] J. Luomala and I. Hakala, "Analysis and evaluation of adaptive RSSI-based ranging in outdoor wireless sensor networks," *Ad Hoc Netw.*, vol. 87, pp. 100–112, May 2019, doi: 10.1016/j.adhoc.2018.10.004.
- [48] S. Kurt and B. Tavli, "Path-Loss Modeling for Wireless Sensor Networks: A review of models and comparative evaluations," *IEEE Antennas Propag. Mag.*, vol. 59, no. 1, pp. 18–37, Feb. 2017, doi: 10.1109/MAP.2016.2630035.
- [49] Y. A. Zakaria, E. K. I. Hamad, A. S. Abd Elhamid, and K. M. El-Khatib, "Propagation Measurements and Calculation of *Path loss Exponent* for Outdoor Cellular Communication Systems at 3.5 GHz," *Radioelectron. Commun. Syst.*, vol. 64, no. 5, pp. 247–254, May 2021, doi: 10.3103/S0735272721050034.
- [50] D. P. Grabowsky, J. M. Conrad, and A. F. Browne, "Limited Log-*Distance Path loss Model Path loss Exponent* Estimation using Deep Deterministic Policy Gradient," in *SoutheastCon 2021*, Atlanta, GA, USA: IEEE, Mar. 2021, pp. 1–6. doi: 10.1109/SoutheastCon45413.2021.9401929.
- [51] T. S. Rappaport, G. R. MacCartney, M. K. Samimi, and S. Sun, "Wideband Millimeter-Wave Propagation Measurements and Channel Models for Future Wireless Communication System Design," *IEEE Trans. Commun.*, vol. 63, no. 9, pp. 3029–3056, Sep. 2015, doi: 10.1109/TCOMM.2015.2434384.
- [52] X. Li, H. Song, and C. Liu, "*Path loss* Modeling for Wireless Network Deployment in Water Surface Environments," *IEEE Antennas Wirel. Propag. Lett.*, vol. 21, no. 6, pp. 1090–1094, Jun. 2022, doi: 10.1109/LAWP.2022.3157834.
- [53] E. Maria, E. Budiman, Havaluddin, and M. Taruk, "Measure *distance* locating nearest public facilities using *Haversine* and *Euclidean* Methods," *J. Phys. Conf. Ser.*, vol. 1450, no. 1, p. 012080, Feb. 2020, doi: 10.1088/1742-6596/1450/1/012080.
- [54] O. Montenbruck and P. Teunissen, Eds., *Springer Handbook of Global Navigation Satellite Systems*, 1st ed. 2017. in Springer Handbooks. Cham: Springer International Publishing : Imprint: Springer, 2017. doi: 10.1007/978-3-319-42928-1.
- [55] A. Vazquez-Rodas, F. Astudillo-Salinas, C. Sanchez, B. Arpi, and L. I. Minchala, "Experimental evaluation of RSSI-based positioning system with low-cost LoRa devices," *Ad Hoc Netw.*, vol. 105, p. 102168, Aug. 2020, doi: 10.1016/j.adhoc.2020.102168.
- [56] İ. Musayev and M. Gojamanov, "Geodetic Errors Arising From The Differences Between Sk-42 And Wgs-84 Coordinate Systems When Implemented In Modern Weapons Systems," *Konya J. Eng. Sci.*, vol. 9, no. 2, pp. 306–313, Jun. 2021, doi: 10.36306/konjes.788599.
- [57] A. Makar, "Limitations of Multi-GNSS Positioning of USV in Area with High Harbour Infrastructure," *Electronics*, vol. 12, no. 3, p. 697, Jan. 2023, doi: 10.3390/electronics12030697.

- [58] R. Agramanisti Azdy and F. Darnis, "Use of *Haversine* Formula in Finding *Distance* Between Temporary Shelter and Waste End Processing Sites," *J. Phys. Conf. Ser.*, vol. 1500, no. 1, p. 012104, Apr. 2020, doi: 10.1088/1742-6596/1500/1/012104.
- [59] P. Ranacher, R. BRunauer, W. Trutschnig, S. C. V. der Spek, and S. Reich, "Why GPS makes *distances* bigger than they are," Jul. 14, 2015, *arXiv*: arXiv:1504.04504. doi: 10.48550/arXiv.1504.04504.
- [60] E. Maria, E. Budiman, Haviluddin, and M. Taruk, "Measure *distance* locating nearest public facilities using *Haversine* and *Euclidean* Methods," *J. Phys. Conf. Ser.*, vol. 1450, no. 1, p. 012080, Feb. 2020, doi: 10.1088/1742-6596/1450/1/012080.
- [61] J. Van Sickle, *Basic GIS coordinates*, Third edition. Boca Raton London New York: CRC Press, 2017.
- [62] M. M. N. Ríos, L. G. G. Albán, V. Defaz, L. O. J. Alarcón, and P. Samaniego, "Application Of The Equation Of *Distance* Between Two Points Focused On The Closure Of Polygons In Land Navigation, In The Career Of Technology In Military Sciences, Dual Modality," *Int. J. Appl. Math.*, vol. 38, no. 7, 2025.
- [63] K. Krivoruchko and A. Gribov, "*Distance* metrics for data interpolation over large areas on Earth's surface," *Spat. Stat.*, vol. 35, p. 100396, Mar. 2020, doi: 10.1016/j.spasta.2019.100396.
- [64] N. Faruk *et al.*, "Large-scale radio propagation *path loss* measurements and predictions in the VHF and UHF bands," *Heliyon*, vol. 7, no. 6, p. e07298, Jun. 2021, doi: 10.1016/j.heliyon.2021.e07298.
- [65] T. Jawhly and R. C. Tiwari, "*Path loss* modeling: A GIS-based approach," Mar. 17, 2023. doi: 10.36227/techrxiv.22211029.v1.
- [66] O. G. Esenbuga, "Comparison Of Principal Geodetic *Distance* Calculation Methods For Automated Province Assignment In Turkey," presented at the 16th International Multidisciplinary Scientific GeoConference SGEM2016, Jun. 2016. doi: 10.5593/SGEM2016/B22/S09.019.
- [67] S. Bisnath, "Relative Positioning and Real-Time Kinematic (RTK)," in *Position, Navigation, and Timing Technologies in the 21st Century*, 1st ed., Y. T. J. Morton, F. Diggelen, J. J. Spilker, B. W. Parkinson, S. Lo, and G. Gao, Eds., Wiley, 2020, pp. 481–502. doi: 10.1002/9781119458449.ch19.
- [68] A. Abdelmoaty, G. Dahman, G. Poitau, and F. Gagnon, "Assessing the Range of Radio Maritime Links in Different Waterbodies: Effect of Antenna height and Band Diversities," in *2021 IEEE 94th Vehicular Technology Conference (VTC2021-Fall)*, Norman, OK, USA: IEEE, Sep. 2021, pp. 1–7. doi: 10.1109/VTC2021-Fall52928.2021.9625350.
- [69] A. A. Olsen, *Introduction to Celestial Navigation*, 1st ed. in Springer Series on Naval Architecture, Marine Engineering, Shipbuilding and Shipping Series, no. v. 15. Cham: Springer, 2024.



- [70] I. E. Elmutasim, "Refining the Dual-Slope *Path loss* Model with a *Distance-Adaptive Exponent* and *Multi-Breakpoint Calibration*," *Int. J. Comput. Methods Exp. Meas.*, vol. 13, no. 2, pp. 251–257, Jun. 2025, doi: 10.18280/ijcmem.130204.
- [71] J. Wang, Y. Hao, and C. Yang, "The Current Progress and Future Prospects of *Path loss* Model for Terrestrial Radio Propagation," *Electronics*, vol. 12, no. 24, p. 4959, Dec. 2023, doi: 10.3390/electronics12244959.
- [72] Y. O. Imam-Fulani *et al.*, "A Comparative Study of *Path loss* Models for 5G Networks Across 28, 36, and 48 GHz in Urban Environments," in *Connected Objects, Artificial Intelligence, Telecommunications and Electronics Engineering*, vol. 1584, Y. Mejdoub, A. Elamri, and M. Kardouchi, Eds., in *Lecture Notes in Networks and Systems*, vol. 1584. , Cham: Springer Nature Switzerland, 2026, pp. 916–927. doi:10.1007/978-3-032-01536-5\_137.

