

Daftar Pustaka

- [1] O. H. Chin, C. K. Lai, C. Y. Choo, C. S. Wong, R. M. Nor, and K. L. Thong, "Atmospheric pressure dielectric barrier discharges for sterilization and surface treatment," *AIP Conf. Proc.*, vol. 1657, no. May, p. 9, 2015, doi: 10.1063/1.4915158.
- [2] M. M. Hollick, M. Arjomandi, and B. S. Cazzolato, "An investigation into the sensory application of DBD plasma actuators for pressure measurement," *Sensors Actuators, A Phys.*, vol. 171, no. 2, pp. 102–108, 2011, doi: 10.1016/j.sna.2011.07.011.
- [3] Y. Zhou *et al.*, "Pulsed filament current characteristics in dielectric barrier discharge," *Proc. 2015 IEEE Pulsed Power Conf.*, vol. 204, no. 2, pp. 2–5, 2024.
- [4] I Biganzoli, "Experimental investigation of Lissajous figure shapes in planar and surface dielectric barrier discharges Experimental investigation of Lissajous figure shapes in planar and surface dielectric barrier discharges," *J. Phys. Conf. Ser.*, vol. 550, no. 1, p. 11, 2014, doi: 10.1088/1742-6596/550/1/012039.
- [5] N. Jidenko, M. Petit, J. Borra, N. Jidenko, M. Petit, and J. B. Electrical, "Electrical characterization of microdischarges produced by dielectric barrier discharge in dry air at atmospheric pressure To cite this version : HAL Id: hal-03245460 Electrical characterization of microdischarges produced by dielectric barrier discharge," *J. Phys. Conf. Ser.*, vol. 550, no. 1, p. 22, 2021.
- [6] M. Hołub, "On the measurement of plasma power in atmospheric pressure DBD plasma reactors," *Int. J. Appl. Electromagn. Mech.*, vol. 39, no. 1–4, pp. 81–87, 2015, doi: 10.3233/JAE-2012-1446.
- [7] J. O. Pacheco-Sotelo *et al.*, "A universal resonant converter for equilibrium and nonequilibrium plasma discharges," *IEEE Trans. Plasma Sci.*, vol. 32, no. 5, pp. 2105–2112, 2004, doi: 10.1109/TPS.2004.835968.

- [8] A. Junaidi, "Pengukuran dan Analisis High Frequency Current Transformer Pendeteksi Partial Discharge," *Kilat*, vol. 10, no. 1, pp. 53–59, 2021, doi: 10.33322/kilat.v10i1.983.
- [9] charis munajib, Asep yoyo wardaya, Zaenul muhlisin, and isnain gunadi, "Plasma Lucutan Korona Dc Positif Dengan Konfigurasi," *Berk. Fis.*, vol. 25, no. 4, p. 9, 2022.
- [10] G. Luo and D. Zhang, "Study On Performance Of Developed And Industrial HFCT Sensors," *NTU*, vol. 39, no. 4, p. 5, 2016.
- [11] Y. Lanjun and Q. E. S. Jia, "Design of a Rogowski Coil with a Magnetic Core Used for Measurements of Nanosecond Current Pulses *," *Plasma Sci. Technol.*, vol. 8, no. 4, pp. 8–11, 2006.
- [12] J. Bong, L. C. Ha, D. K. H. Lee, and H. June, "A Study on the Dielectric Barrier Discharges Plasmas of Flat Atmospheric Pressure Using an AC Pulse Voltage," *Int. J. Eng. Sci.*, vol. 61, no. 5, pp. 717–720, 2012.
- [13] J. Wang, N. Leoni, H. Birecki, O. Gila, and M. J. Kushner, "Characteristics of a radio-frequency micro-dielectric barrier discharge array," *IOP Publ.*, vol. 22, no. 4, p. 10, 2013, doi: 10.1088/0963-0252/22/2/025015.
- [14] N. Seddaoui, M. Ouali, and Y. Lagmich, "Atmospheric pressure plasma jet based on the dielectric barrier discharge," *Int. J. Appl. Electromagn. Mech.*, vol. 39, no. 1–4, p. 208, 2022, doi: 10.1051/itmconf/20224802008.
- [15] N. Dumitrascu, I. Topala, and G. Popa, "Dielectric barrier discharge technique in improving the wettability and adhesion properties of polymer surfaces," *IEEE Trans. Plasma Sci.*, vol. 33, no. 5 II, pp. 1710–1714, 2005, doi: 10.1109/TPS.2005.856335.
- [16] J. Creemers, "Experimental study of a novel micro-wire dielectric barrier discharge," *IEEE Trans. Dielectr. Electr. Insul.*, vol. 8, no. 4, p. 2, 2012.
- [17] M. Dobbelaar *et al.*, "Electrical Parameters of Nanosecond Dielectric Barrier Discharges (nsDBD) To cite this version : Electrical Parameters of Nanosecond Dielectric Barrier Discharges (nsDBD)," *IEEE Trans. Dielectr. Electr. Insul.*, vol. 50, no. 4, p. 11, 2022.

- [18] D. E. Ashpis, M. C. Laun, and E. L. Griebeler, "Progress Toward Accurate Measurements of Power Consumptions of DBD Plasma Actuators," *Int. J. Appl. Electromagn. Mech.*, vol. 39, no. 1–4, pp. 81–87, 2012.
- [19] O. Ayranov, "The accurate measurement of load currents provided by high-voltage DC power supplies," *Meas. Sci. Technol.*, vol. 10, no. 4, pp. 51–54, 1999.
- [20] L. Shulin, "Design of a Current Sensing Circuit without Power Loss for DC-DC Converter," *J. Power Electron.*, vol. 16, no. 2, pp. 354–361, 2015, doi: 10.2991/meic-15.2015.231.
- [21] M. H. Samimi, A. Mahari, and M. A. Farahnakian, "The Rogowski Coil Principles and Applications : A Review," *IEEE Sens. J.*, vol. 15, no. 2, pp. 651–658, 2015.
- [22] Guangdong, "Investigation of High Frequency Current Transformers Used for Partial Discharge Detection," *Proc. 4th Int. Conf. Inf. Technol. Manag. Innov. (ICITMI 2015)*, vol. 22, pp. 247–253, 2015.
- [23] X. Hu, W. H. Siew, M. D. Judd, and X. Peng, "Transfer function characterization for HFCTs used in partial discharge detection," *IEEE Trans. Dielectr. Electr. Insul.*, vol. 24, no. 2, pp. 1088–1096, 2017, doi: 10.1109/TDEI.2017.006115.
- [24] G. Luo and D. Zhang, "Study on performance of HFCT and UHF sensors in partial discharge detection," *2010 9th Int. Power Energy Conf. IPEC 2010*, pp. 630–635, 2010, doi: 10.1109/IPEC2010.5697070.
- [25] Istiqomah, Muhammad Nur, and Fajar Arianto, "Karakterisasi reaktor plasma lucutan berpenghalang dielektrik berkonfigurasi elektroda spiral-silinder dengan sumber udara bebas," *J. Fis. Indones.*, vol. 6, no. 3, pp. 235–241, 2017.