

DAFTAR PUSTAKA

- [1] L. Hu, Y. Wang, and Y. Tian, "Partial Discharge Monitoring Method in Switchgear with Bushing High-Voltage Sensor," *J. Phys. Conf. Ser.*, vol. 2417, no. 1, p. 012039, Dec. 2022, doi: 10.1088/1742-6596/2417/1/012039.
- [2] H. Wen, Abu Talip, Mohamad Sofian., "Advanced Signal Processing Methods for Partial Discharge Analysis: A Review," *Sensors*, vol. 25, no. 23, p. 7318, Dec. 2025, doi: 10.3390/s25237318.
- [3] N. A. Akashah, Rohani, Rosmi I., "A review: Partial discharge detection using acoustic sensor on high voltage transformer," *J. Phys. Conf. Ser.*, vol. 1432, no. 1, p. 012004, Jan. 2020, doi: 10.1088/1742-6596/1432/1/012004.
- [4] E. D. Fylladitakis, M. P. Theodoridis, and A. X. Moronis, "Review on the history, research, and applications of electrohydrodynamics," *IEEE Transactions on Plasma Science*, vol. 42, no. 2, pp. 358–375, Feb. 2014, doi: 10.1109/TPS.2013.2297173.
- [5] A. Solihin, J. M. Nainggolan, and D. Despa, "Karakteristik Peluahan Sebagian (Partial Discharge) Pada Isolasi Karet Silikon (Silicone Rubber) Menggunakan Sensor Emisi Akustik," *J. Inform. Dan Tek. Elektro Terap.*, vol. 4, no. 2, Apr. 2016, doi: 10.23960/jitet.v4i2.541.
- [6] M. Fikri, C. Christiono, and I. G. Mulyana K., "Clustering Fenomena Corona discharge berdasarkan Suara menggunakan Metode LPC dan Euclidean Distance," *ELKOMIKA J. Tek. Energi Elektr. Tek. Telekomun. Tek. Elektron.*, vol. 10, no. 3, p. 689, Jul. 2022, doi: 10.26760/elkomika.v10i3.689.
- [7] M. Nakajima, D. Basu, A. V. Melnikov, D. McColl, and C. Xiao, "Development of an interactive code for quick data analyses between STOR-M tokamak experimental plasma discharges," Jun. 16, 2022, *arXiv:arXiv:2206.08458*. doi: 10.48550/arXiv.2206.08458.
- [8] A. F. Abdurrahman, P. Manurung, I. Firdaus, and D. Asmi, "Corona discharge Sebagai Teknologi Sterilisasi Ramah Lingkungan Untuk Pengendalian Bakteri," vol. 3, no. 2, 2018.
- [9] Z. Ma, L. Yang, H. Bian, M. S. Bhutta, and P. Xu, "An Improved IPM for Life Estimation of XLPE Under DC Stress Accounting for Space-Charge Effects," *IEEE Access*, vol. 7, pp. 157892–157901, 2019, doi: 10.1109/ACCESS.2019.2946521.
- [10] M. Mohammad, O. Ibryaeva, V. Sinitsin, and V. Ereemeeva, "A Computationally Efficient Method for the Diagnosis of Defects in Rolling Bearings Based on Linear Predictive Coding," *Algorithms*, vol. 18, no. 2, p. 58, Jan. 2025, doi: 10.3390/a18020058.

- [11] T. Radil, P. M. Ramos, F. M. Janeiro, and A. Cruz Serra, "PQ Monitoring System for Real-Time Detection and Classification of Disturbances in a Single-Phase Power System," *IEEE Trans. Instrum. Meas.*, vol. 57, no. 8, pp. 1725–1733, Aug. 2008, doi: 10.1109/TIM.2008.925345.
- [12] M. P. Tcheou, Michel P., Lovisolo., "The Compression of Electric Signal Waveforms for Smart Grids: State of the Art and Future Trends," *IEEE Trans. Smart Grid*, vol. 5, no. 1, pp. 291–302, Jan. 2014, doi: 10.1109/TSG.2013.2293957.
- [13] C. Widyastuti and I. N. B. Y. Dharma, "Dampak Korona pada SUTET 500 kV Terhadap Radio Interference," *Energi Kelistrikan*, vol. 11, no. 2, pp. 87–97, Dec. 2019, doi: 10.33322/energi.v11i2.842.
- [14] D. Oleh, S. Hidayat, and S. Si, "Text Book Deteksi *Corona discharge* Dengan Menggunakan Analisa Emisi Acoustic Pada Kubikel Medium-Voltage".
- [15] F. Merazka and D. Berkani, "Robust Split Vector Quantization of LSP Parameters at Low Bit Rates," *The Arabian Journal for Science and Engineering*, vol. 29, no. 1B, pp. 31–47, Apr. 2004.
- [16] T. Radil and P. M., "Methods for Estimation of Voltage Harmonic Components," in *Power Quality*, A. Eberhard, Ed., InTech, 2011. doi: 10.5772/14195.
- [17] Y. Wang, Q. Chen, C. Kang, Q. Xia, and M. Luo, "Sparse and Redundant Representation-Based Smart Meter Data Compression and Pattern Extraction," *IEEE Trans. Power Syst.*, vol. 32, no. 3, pp. 2142–2151, May 2017, doi: 10.1109/TPWRS.2016.2604389.
- [18] N. Pasra, M. Fikri, K. T. Mauriraya, T. Rijanto, and I. G. P. A. Buditjahjanto, "Deteksi Suara *Corona discharge* berdasarkan Noise menggunakan Metode LPC dan Euclidean Distance," *ELKOMIKA J. Tek. Energi Elektr. Tek. Telekomun. Tek. Elektron.*, vol. 11, no. 1, p. 72, Jan. 2023, doi: 10.26760/elkomika.v11i1.72.
- [19] I. A. Dewi, A. Zulkarnain, and A. A. Lestari, "Identifikasi Suara Tangisan Bayi menggunakan Metode LPC dan Euclidean Distance," *ELKOMIKA J. Tek. Energi Elektr. Tek. Telekomun. Tek. Elektron.*, vol. 6, no. 1, p. 153, Apr. 2018, doi: 10.26760/elkomika.v6i1.153.
- [20] S. T. Prihatnolo, Pengukuran Tegangan Tembus Dielektrik Udara pada Berbagai Sel dan Bentuk Elektroda dengan Variasi Temperatur Sekitar, Undergraduate Thesis, Dept. of Electrical Engineering, Universitas Diponegoro, Semarang, Indonesia, 2012.
- [21] A. Z. Abdullah, M. Isa, M. N. K. H. Rohani, S. A. S. Jamalil, A. N. N. Abdullah, and N. Azizan, "Development of smart online partial discharge monitoring system for medium voltage power cable," *Int. J. Power Electron. Drive Syst. IJPEDS*, vol. 10, no. 4, p. 2190, Dec. 2019, doi: 10.11591/ijpeds.v10.i4.pp2190-2197.

- [22] M. Fikri, Miftahul, Christiono., "Optimization Objective Function *Corona discharge* Acoustic Using Fuzzy c-Means (FcM)," *ELKHA*, vol. 15, no. 2, p. 84, Oct. 2023, doi: 10.26418/elkha.v15i2.63601.
- [23] S. Carrato, Chatterjee, Cicuttin., "A scalable High Voltage Power Supply System with system on chip control for Micro Pattern Gaseous Detectors," *Nucl. Instrum. Methods Phys. Res. Sect. Accel. Spectrometers Detect. Assoc. Equip.*, vol. 963, p. 163763, May 2020, doi: 10.1016/j.nima.2020.163763.
- [24] B. S. Atal, "The history of linear prediction," *IEEE Signal Process. Mag.*, vol. 23, no. 2, pp. 154–161, Mar. 2006, doi: 10.1109/MSP.2006.1598091.
- [25] R. Masareng, L. S. Patras, and H. Tumaliang, "Efek Korona pada Saluran Transmisi Gardu Induk Tello Sulawesi Selatan," *Jurnal Teknik Elektro dan Komputer*, vol. 5, no. 2, pp. 67–74, May–Aug. 2016.
- [26] R. M. Gray, *Linear Predictive Coding and the Internet Protocol: part 1: A survey of linear predictive coding ; part 2: A history of realtime digital speech on packet networks*. in Foundations and trends in signal processing, no. 3,3/4. Boston, Mass. Delft: Now Publ, 2010.
- [27] M. Wahyudi, N. A. Setiawan, and B. Sugiyantoro, "Detection of Partial Discharge in An Oil Filled- Tank Using Acoustic in Audio Frequency Range," vol. 5, no. 1, 2021.
- [28] S. Helmiyah, I. Riadi, R. Umar, A. Hanif, A. Yudhana, and A. Fadlil, "Identifikasi Emosi Manusia Berdasarkan Ucapan Menggunakan Metode Ekstraksi Ciri LPC dan Metode Euclidean Distance," *J. Teknol. Inf. Dan Ilmu Komput.*, vol. 7, no. 6, p. 1177, Dec. 2020, doi: 10.25126/jtiik.2020722693.
- [29] M. Shafiq, K. Kauhaniemi, G. Robles, M. Isa, and L. Kumpulainen, "Online condition monitoring of MV cable feeders using Rogowski coil sensors for PD measurements," *Electr. Power Syst. Res.*, vol. 167, pp. 150–162, Feb. 2019, doi: 10.1016/j.epsr.2018.10.038.
- [30] Murata Manufacturing Co., Ltd., "MA40S4S/MA40S4R Ultrasonic Sensor: Application Note," Doc. No. DM-U16-483 Rev.2, 2021. [Online].