

DAFTAR PUSTAKA

- [1] N. Jeyaprakash dan C.-H. Yang, "Friction, Lubrication, and Wear," dalam *Tribology in Materials and Manufacturing - Wear, Friction and Lubrication*, IntechOpen, 2021. doi: 10.5772/intechopen.93796.
- [2] B. Kumar, R. Chandp, dan B. Kumarp, "Environmental Hazards of Oil and Lubricants Oil and Lubricant Hazard Effects on Human Health," 2017. [Daring]. Tersedia pada: www.ijiset.com
- [3] M. H. Rahman, H. Warneke, H. Webert, J. Rodriguez, E. Austin, K. Tokunaga, D. P. Rajak, dan P. L. Menezes, "Water-based lubricants: Development, properties, and performances," 1 Agustus 2021, *MDPI AG*. doi: 10.3390/lubricants9080073.
- [4] W. Wijanarko, H. Khanmohammadi, dan N. Espallargas, "Ionic Liquid Additives in Water-Based Lubricants for Bearing Steel – Effect of Electrical Conductivity and pH on Surface Chemistry, Friction and Wear," *Front. Mech. Eng.*, vol. 7, Jan 2022, doi: 10.3389/fmech.2021.756929.
- [5] L. Hao, W. Hao, P. Li, G. Liu, H. Li, A. Aljabri, Z. Xie, "Friction and Wear Properties of a Nanoscale Ionic liquid-like GO@SiO₂ Hybrid as a Water-Based Lubricant Additive," *Lubricants*, vol. 10, no. 6, Jun 2022, doi: 10.3390/lubricants10060125.
- [6] I. Garcia, S. Guerra, J. de Damborenea, dan A. Conde, "Reduction of the Coefficient of friction of steel-steel tribological contacts by Novel Graphene-Deep Eutectic Solvents (DESs) lubricants," *Lubricants*, vol. 7, no. 4, Apr 2019, doi: 10.3390/lubricants7040037.
- [7] K. Aristizabal, A. Tayrac, A. Katzensteiner, A. Bachmaier, dan S. Suarez, "Friction and tribo-chemical behavior of SPD-processed CNT-reinforced composites," *Lubricants*, vol. 7, no. 9, Sep 2019, doi: 10.3390/lubricants7090075.
- [8] Nippon Chemical Industrial Co., Ltd., *Ionic Liquids General Catalog*, 6th ed. Tokyo, Japan: Nippon Chemical Industrial Co., Ltd., n.d.
- [9] Syafa'at. I, "Tribologi, Daerah Pelumasan dan Keausan," *Majalah Ilmiah Momentum*, vol. 4, no. 2, pp. 21–26, Oct. 2008, doi: 10.36499/jim.v4i2.611.
- [10] M. Bahar Fitrianto, I. Syafa'at, dan Darmanto, "Pengujian Koefisien Gesek Permukaan Plat Baja ST 37 Pada Bidang Miring terhadap Viskositas Pelumas dan Kekasaran Permukaan," *Momentum*, vol. 11, no. 1, hlm. 13–18, 2015.
- [11] M. G. Algafari, "Pengaruh Foaming Pada Minyak Pelumas Berbahan Dasar Minyak Kelapa Sawit Terhadap Laju Keausan," *Tugas Akhir, Universitas Andalas*, Padang, 2025.
- [12] B. Setiyana, L. Perancangan, dan D. Tribologi, "Identifikasi Sifat Tribologi Dari Karet Vulkanisir Dengan Menggunakan Metode Uji Pin on Disk," in *Prosiding*

Seminar Nasional Sains dan Teknologi (SNaST), Semarang, Indonesia, 2019, pp. 41–46, doi: 10.36499/psnst.v1i1.2818.

- [13] U. Abdulwahab, M. B. Ndaliman, O. A. Olugboji, dan & K. C. Bala, “Design and Fabrication of a Dual Condition Pin On Disk Automated Wear Testing Machine,” in *Proceedings of the 7th North American International Conference on Industrial Engineering and Operations Management (IEOM)*, Orlando, FL, USA, Jun. 2022, pp. 2038–2047.
- [14] M. A. Hanafi, “Pengaruh Foaming Pada Minyak Pelumas Berbahan Dasar Minyak Nabati Terhadap Koefisien Gesek,” Tugas Akhir, Universitas Andalas, Padang 2025
- [15] U. Abdulwahab, M. B. Ndaliman, O. A. Olugboji, dan & K. C. Bala, “Design and Fabrication of a Dual Condition PIN-ON-DISC Automated Wear Testing Machine,” 2022.
- [16] B. R. Zalni, “Pengaruh Penambahan Multi Walled Carbon Nanotubes Pada Water Deionized Lubricant Terhadap Koefisien Gesek, Sifat Fisik, Dan Sifat Kimia Pada Alat Uji Pin-On-Disc,” Tugas Akhir, Universitas Andalas, Padang, 2025.
- [17] W. W. F. Chong, S. H. Hamdan, K. J. Wong, dan S. Yusup, “Modelling transitions in regimes of lubrication for rough surface contact,” *Lubricants*, vol. 7, no. 9, Sep 2019, doi: 10.3390/lubricants7090077.
- [18] I. Ganesh, “BMIM-BF₄ RTIL: Synthesis, Characterization and Performance Evaluation for Electrochemical CO₂ Reduction to CO over Sn and MoSi₂ Cathodes,” *C (Basel)*, vol. 6, no. 3, hlm. 47, Jul 2020, doi: 10.3390/c6030047.
- [19] J. Zhang dan Y. Meng, “Boundary lubrication by adsorption film,” 1 Juni 2015, Tsinghua University Press. doi: 10.1007/s40544-015-0084-4.
- [20] R. I. Taylor, “Rough Surface Contact Modelling—A Review,” 1 Mei 2022, MDPI. doi: 10.3390/lubricants10050098.
- [21] P. V. Moghaddam, J. Hardell, E. Vuorinen, dan B. Prakash, “Effect of retained austenite on adhesion-dominated wear of nanostructured carbide-free bainitic steel,” *Tribol. Int.*, vol. 150, Okt 2020, doi: 10.1016/j.triboint.2020.106348.