

DAFTAR PUSTAKA

- [1] M. Kenisarin, K. Mahkamov, F. Kahwash, and I. Makhkamova, "Enhancing thermal conductivity of paraffin wax 53–57 °C using expanded graphite," *Solar Energy Materials and Solar Cells*, vol. 200, p. 110026, Sep. 2019, doi: 10.1016/J.SOLMAT.2019.110026.
- [2] M. TabkhPaz, S. Shajari, M. Mahmoodi, D. Y. Park, H. Suresh, and S. S. Park, "Thermal conductivity of carbon nanotube and hexagonal boron nitride polymer composites," *Compos. B Eng.*, vol. 100, pp. 19–30, Sep. 2016, doi: 10.1016/J.COMPOSITESB.2016.06.036.
- [3] A. Chibani *et al.*, "A strategy for enhancing heat transfer in phase change material-based latent thermal energy storage unit via nano-oxides addition: A study applied to a shell-and-tube heat exchanger," *J. Environ. Chem. Eng.*, vol. 9, no. 6, p. 106744, Dec. 2021, doi: 10.1016/J.JECE.2021.106744.
- [4] F. Mebarek-Oudina and I. Chabani, "Review on Nano Enhanced PCMs: Insight on nePCM Application in Thermal Management/Storage Systems," Feb. 01, 2023, *MDPI*. doi: 10.3390/en16031066.
- [5] M. A. Amidu, M. Ali, A. K. Alkaabi, and Y. Addad, "A critical assessment of nanoparticles enhanced phase change materials (NePCMs) for latent heat energy storage applications," *Sci. Rep.*, vol. 13, no. 1, Dec. 2023, doi: 10.1038/s41598-023-34907-0.
- [6] T. N. Narasimhan, "Fourier's Heat Conduction Equation: History, Influence, and Connections," May 1998.
- [7] Sansanorth, "Illustration of physic Heat Transfer Methods," Shutter Stock.
- [8] Z. Chen *et al.*, "Optimization Design and Performance Study of a Heat Exchanger for an Oil and Gas Recovery System in an Oil Depot," *Energies*, vol. 17, no. 11, May 2024, doi: 10.3390/en17112631.
- [9] O. Levenspiel, "THE THREE MECHANISMS OF HEAT TRANSFER: CONDUCTION, CONVECTION, AND RADIATION," in *Engineering Flow and Heat Exchange*, New York: Plenum Press, 1984, ch. 9.
- [10] E. Yantovski, "Exergonomics in education," *Energy*, vol. 25, no. 10, pp. 1021–1031, Oct. 2000, doi: 10.1016/S0360-5442(00)00027-X.
- [11] J. Mathisson, "Plant and Equipment: Heat Exchangers," in *Reference Module in Food Science*, Sweden: Elsevier, 2016. doi: 10.1016/b978-0-08-100596-5.01006-4.

- [12] G. Sidebotham, "Convection Fundamentals. In: Heat Transfer Modeling.," Springer, Cham, 2015.
- [13] H. and L. Zhao *et al.*, "State-of-the-Art Shaped Profile Windings and Their Integrated Cooling Configurations Enabled by Additive Manufacturing Technology," *IEEE Transactions on Transportation Electrification*, vol. 11, pp. 10988–11003, 2025.
- [14] J. Hwang and K. Cho, "Numerical prediction of frost properties and performance of fin–tube heat exchanger with plain fin under frosting," *International Journal of Refrigeration*, vol. 46, pp. 59–68, Oct. 2014, doi: 10.1016/J.IJREFRIG.2014.04.026.
- [15] M. Muneeshwaran, G. Srinivasan, P. Muthukumar, and C. C. Wang, "Role of hybrid-nanofluid in heat transfer enhancement – A review," *International Communications in Heat and Mass Transfer*, vol. 125, May 2021, doi: 10.1016/j.icheatmasstransfer.2021.105341.
- [16] W. N. Septiadi, I. A. N. T. Trisnadewi, N. Putra, and I. Setyawan, "Synthesis of hybrid nanofluid with two-step method," *E3S Web of Conferences*, vol. 67, Nov. 2018, doi: 10.1051/e3sconf/20186703057.
- [17] F. Asaduzzaman and S. Salmon, "Enzyme immobilization: polymer–solvent–enzyme compatibility," *Mol. Syst. Des. Eng.*, vol. 7, no. 11, pp. 1385–1414, Nov. 2022, doi: 10.1039/d2me00140c.
- [18] Z. Li and Y. Ye, "Two-dimensional materials," in *Nanoscale Semiconductor Lasers*, Beijing: Elsevier, 2019, ch. 7, pp. 165–189. doi: 10.1016/B978-0-12-814162-5.00007-8.
- [19] I. W. Almanassra, A. D. Manasrah, U. A. Al-Mubaiyedh, T. Al-Ansari, Z. O. Malaibari, and M. A. Atieh, "An experimental study on stability and thermal conductivity of water/CNTs nanofluids using different surfactants: A comparison study," *J. Mol. Liq.*, vol. 304, p. 111025, Apr. 2020, doi: 10.1016/J.MOLLIQ.2019.111025.
- [20] M. M. Alshaikh, W. Abdussalam-Mohammed, and A. Bhattarai, "Review of thermal conductivity of gold nanoparticle composites," Jan. 01, 2026, *Walter de Gruyter GmbH*. doi: 10.1515/ntrev-2025-0258.
- [21] P. Van Trinh *et al.*, "Experimental study on the thermal conductivity of graphene–carbon nanotube–silver nanoparticle ternary hybrid nanofluids," *RSC Adv.*, vol. 16, no. 4, pp. 3753–3764, 2026, doi: 10.1039/d5ra03763h.

- [22] A. Venkataraman, E. V. Amadi, Y. Chen, and C. Papadopoulos, "Carbon Nanotube Assembly and Integration for Applications," *Nanoscale Res. Lett.*, vol. 14, no. 1, 2019, doi: 10.1186/s11671-019-3046-3.
- [23] M. Rizwan, A. Shoukat, A. Ayub, B. Razzaq, and M. B. Tahir, "Types and classification of nanomaterials," *Nanomaterials: Synthesis, Characterization, Hazards and Safety*, pp. 31–54, Jan. 2021, doi: 10.1016/B978-0-12-823823-3.00001-X.
- [24] H. Hassanloo, S. Sadeghzadeh, and R. Ahmadi, "A new approach to dispersing and stabilizing graphene in aqueous nanofluids of enhanced efficiency of energy-systems," *Sci. Rep.*, vol. 10, no. 1, Dec. 2020, doi: 10.1038/s41598-020-64600-5.
- [25] B. F. Monea, E. I. Ionete, S. I. Spiridon, D. Ion-Ebrasu, and E. Petre, "Carbon nanotubes and carbon nanotube structures used for temperature measurement," Jun. 01, 2019, *MDPI AG*. doi: 10.3390/s19112464.
- [26] K. Y. Leong, K. Z. Ku Ahmad, H. C. Ong, M. J. Ghazali, and A. Baharum, "Synthesis and thermal conductivity characteristic of hybrid nanofluids – A review," *Renewable and Sustainable Energy Reviews*, vol. 75, pp. 868–878, Aug. 2017, doi: 10.1016/J.RSER.2016.11.068.
- [27] E. García-Macías, L. Rodríguez-Tembleque, R. Castro-Triguero, and A. Sáez, "Eshelby-Mori-Tanaka approach for post-buckling analysis of axially compressed functionally graded CNT/polymer composite cylindrical panels," *Compos. B Eng.*, vol. 128, pp. 208–224, Jul. 2017, doi: 10.1016/j.compositesb.2017.07.016.
- [28] M. Choi, W. K. Choi, C. H. Jung, and S. B. Kim, "The surface modification and characterization of SiO₂ nanoparticles for higher foam stability," *Sci. Rep.*, vol. 10, no. 1, Dec. 2020, doi: 10.1038/s41598-020-76464-w.
- [29] Y. Huang *et al.*, "Silica nanoparticles: Biomedical applications and toxicity," May 17, 2022, *Elsevier Masson s.r.l.* doi: 10.1016/j.biopha.2022.113053.
- [30] F. E. Berger Bioucas, M. H. Rausch, J. Schmidt, A. Bück, T. M. Koller, and A. P. Fröba, "Effective Thermal Conductivity of Nanofluids: Measurement and Prediction," *Int. J. Thermophys.*, vol. 41, no. 5, Mar. 2020, doi: 10.1007/s10765-020-2621-2.
- [31] S. Li, P. Shen, H. Zhou, S. Du, Y. Zhang, and J. Yan, "Synergistic effects of CNTs/SiO₂ composite fillers on mechanical properties of cement

- composites,” *RSC Adv.*, vol. 12, no. 42, pp. 27253–27266, Sep. 2022, doi: 10.1039/d2ra04127h.
- [32] S. B. Mousavi, “Enhancing Heat Transfer in Industrial Heat Exchangers with Water-Based GO Nanofluids: Comprehensive Analysis and Performance Optimization,” Dec. 2023. doi: 10.21203/rs.3.rs-3746366/v1.
- [33] B. Mahmoud, H. P. Rice, L. Mortimer, M. Fairweather, J. Peakall, and D. Harbottle, “Acoustic Method for Determination of the Thermal Properties of Nanofluids,” *Ind. Eng. Chem. Res.*, vol. 58, no. 42, pp. 19719–19731, Nov. 2019, doi: 10.1021/acs.iecr.9b02983.
- [34] W. Yu and S. U. S. Choi, “The role of interfacial layers in the enhanced thermal conductivity of nanofluids: A renovated Hamilton-Crosser model,” *Journal of Nanoparticle Research*, no. 6, pp. 355–361, 2004.
- [35] K. Apmann, R. Fulmer, A. Soto, and S. Vafaei, “Thermal conductivity and viscosity: Review and optimization of effects of nanoparticles,” *Materials*, vol. 14, no. 5, pp. 1–71, Mar. 2021, doi: 10.3390/ma14051291.
- [36] M. Amani, P. Amani, A. Kasaeian, O. Mahian, I. Pop, and S. Wongwises, “Modeling and optimization of thermal conductivity and viscosity of MnFe₂O₄ nanofluid under magnetic field using an ANN,” *Sci. Rep.*, vol. 7, no. 1, Dec. 2017, doi: 10.1038/s41598-017-17444-5.
- [37] A. Sharma, V. V. Tyagi, C. R. Chen, and D. Buddhi, “Review on thermal energy storage with phase change materials and applications,” Feb. 2009. doi: 10.1016/j.rser.2007.10.005.
- [38] M. K. Rathod and J. Banerjee, “Experimental investigations on latent heat storage unit using paraffin wax as phase change material,” *Experimental Heat Transfer*, vol. 27, no. 1, pp. 40–55, Jan. 2014, doi: 10.1080/08916152.2012.719065.
- [39] M. A. Abd El-Baky and M. M. Mohamed, “Heat pipe heat exchanger for heat recovery in air conditioning,” *Appl. Therm. Eng.*, vol. 27, no. 4, pp. 795–801, Mar. 2007, doi: 10.1016/j.applthermaleng.2006.10.020.
- [40] A. Sciacovelli, F. Gagliardi, and V. Verda, “Maximization of performance of a PCM latent heat storage system with innovative fins,” *Appl. Energy*, vol. 137, pp. 707–715, Jan. 2015, doi: 10.1016/j.apenergy.2014.07.015.
- [41] A. K. Gupta, B. Gupta, J. Bhalavi, P. Baredar, H. Parmar, and R. Senthil, “CFD study on heat transfer and pressure drop of nanofluids (SiO₂/H₂O, Al₂O₃/H₂O, CNTs/H₂O) in a concentric tube heat exchanger,”

International Journal of Ambient Energy, vol. 43, no. 1, pp. 4578–4593, Apr. 2021, doi: 10.1080/01430750.2021.1913222.

- [42] A. M. Alklaibi, K. V. V. Chandra Mouli, and L. Syam Sundar, “Experimental and support vector machine predictions of entropy generations and exergy efficiency of Fe₃O₄–SiO₂/Water hybrid nanofluid in a plate heat exchanger,” *Heliyon*, vol. 9, no. 11, Oct. 2023, doi: 10.1016/j.heliyon.2023.e21730.
- [43] J. M. Mahdi and E. C. Nsofor, “Melting enhancement in triplex-tube latent thermal energy storage system using nanoparticles-fins combination,” *Int. J. Heat Mass Transf.*, vol. 109, pp. 417–427, 2017, doi: 10.1016/j.ijheatmasstransfer.2017.02.016.
- [44] S. U. S. Choi, and J. A. Eastman, “ENHANCING THERMAL CONDUCTIVITY OF FLUIDS WITH NANOPARTICLES* ENHANCING THERMAL CONDUCTIVITY OF FLUIDS WITH NANOPARTICLES,” San Francisco, Nov. 1995.
- [45] H. Xie, W. Yu, Y. Li, and L. Chen, “Discussion on the thermal conductivity enhancement of nanofluids,” *Nanoscale Res. Lett.*, vol. 6, no. 1, 2011, doi: 10.1186/1556-276X-6-124.
- [46] I. Maia *et al.*, “Thermal Conductivity of Nanofluids: A Review on Prediction Models, Controversies and Challenges,” *Applied Sciences*, vol. 11, p. 2525, Mar. 2021, doi: 10.3390/app11062525.

