

## DAFTAR PUSTAKA

- [1] V. Gill, “‘Mengerikan’, sampah plastik sebanyak 1,3 miliar ton akan mencemari lingkungan pada 2040,” 2020. <https://www.bbc.com/indonesia/majalah-53522290> (accessed Sep. 20, 2020).
- [2] H. M. C. d. Azeredo, “Nanocomposites for food packaging applications,” *Food Res. Int.*, vol. 42, no. 9, pp. 1240–1253, 2009, doi: 10.1016/j.foodres.2009.03.019.
- [3] A. Dufresne, “Nanocellulose: A new ageless bionanomaterial,” *Mater. Today*, vol. 16, no. 6, pp. 220–227, 2013, doi: 10.1016/j.mattod.2013.06.004.
- [4] W. Chen, H. Yu, Y. Liu, P. Chen, M. Zhang, and Y. Hai, “Individualization of cellulose nanofibers from wood using high-intensity ultrasonication combined with chemical pretreatments,” *Carbohydr. Polym.*, vol. 83, no. 4, pp. 1804–1811, 2011, doi: 10.1016/j.carbpol.2010.10.040.
- [5] H. Wang, X. Zhang, Z. Jiang, W. Li, and Y. Yu, “A comparison study on the preparation of nanocellulose fibrils from fibers and parenchymal cells in bamboo (*Phyllostachys pubescens*),” *Ind. Crops Prod.*, vol. 71, pp. 80–88, 2015, doi: 10.1016/j.indcrop.2015.03.086.
- [6] C. S. Julie Chandra, N. George, and S. K. Narayanankutty, “Isolation and characterization of cellulose nanofibrils from arecanut husk fibre,” *Carbohydr. Polym.*, vol. 142, pp. 158–166, 2016, doi: 10.1016/j.carbpol.2016.01.015.
- [7] M. Mahardika, H. Abrial, A. Kasim, S. Arief, and M. Asrofi, “Production of nanocellulose from pineapple leaf fibers via high-shear homogenization and ultrasonication,” *Fibers*, vol. 6, no. 2, pp. 1–12, 2018, doi: 10.3390/fib6020028.
- [8] E. Syafri, A. Kasim, H. Abrial, and A. Asben, “Cellulose nanofibers isolation and characterization from ramie using a chemical-ultrasonic treatment,” *Nat. Fibers*, vol. 00, no. 00, pp. 1–11, 2018, doi: 10.1080/15440478.2018.1455073.

- [9] M. T. Parizi, A. Habibolahzadeh, and G. R. Ebrahimi, "Microstructure evaluations and mechanical properties of rheo-cast AZ80/Ca/Al<sub>2</sub>O<sub>3</sub> nanocomposite after extrusion process," *Mater. Sci. Eng. A*, vol. 693, no. February, pp. 33–41, 2017, doi: 10.1016/j.msea.2017.03.086.
- [10] K. Vaezi, G. Asadpour, and H. Sharifi, "Effect of ZnO nanoparticles on the mechanical, barrier and optical properties of thermoplastic cationic starch/montmorillonite biodegradable films," *Int. J. Biol. Macromol.*, vol. 124, pp. 519–529, 2019, doi: 10.1016/j.ijbiomac.2018.11.142.
- [11] X. Zhang, G. Xiao, Y. Wang, Y. Zhao, H. Su, and T. Tan, "Preparation of chitosan-TiO<sub>2</sub> composite film with efficient antimicrobial activities under visible light for food packaging applications," *Carbohydr. Polym.*, vol. 169, pp. 101–107, 2017, doi: 10.1016/j.carbpol.2017.03.073.
- [12] G. B. Basim, "Properties of Materials EMA 6001 Section: 34H3," pp. 1–7, 2018.
- [13] N. Nayiroh, "Teknologi Material Komposit," [Online]. Available: [http://www.ghbook.ir/index.php?name=سراسری اندیشی هم دومین مقالات مجموعه و تلویزیون رسانه و سسکولاریسم&option=com\\_dbook&task=readonline&book\\_id=13629&page=108&chckhashk=03C706812F&Itemid=218&lang=fa&tmpl=component](http://www.ghbook.ir/index.php?name=سراسری اندیشی هم دومین مقالات مجموعه و تلویزیون رسانه و سسکولاریسم&option=com_dbook&task=readonline&book_id=13629&page=108&chckhashk=03C706812F&Itemid=218&lang=fa&tmpl=component).
- [14] W. D. Callister, "Materials science and engineering: An introduction (2nd edition)," *Mater. Des.*, vol. 12, no. 1, p. 59, 1991, doi: 10.1016/0261-3069(91)90101-9.
- [15] V. R. Raman Bharath, B. Vijaya Ramnath, and N. Manoharan, "Kenaf fibre reinforced composites: A review," *ARNP J. Eng. Appl. Sci.*, vol. 10, no. 13, pp. 5483–5485, 2015, doi: 10.1016/j.matdes.2011.04.008.
- [16] R. Zuluaga, J. L. Putaux, J. Cruz, J. Vélez, I. Mondragon, and P. Gañán, "Cellulose microfibrils from banana rachis: Effect of alkaline treatments on structural and morphological features," *Carbohydr. Polym.*, vol. 76, no. 1, pp. 51–59, 2009, doi: 10.1016/j.carbpol.2008.09.024.
- [17] L. Liu, J. Yu, L. Cheng, and W. Qu, "Mechanical properties of poly(butylene

- succinate) (PBS) biocomposites reinforced with surface modified jute fibre,” *Compos. Part A Appl. Sci. Manuf.*, vol. 40, no. 5, pp. 669–674, 2009, doi: 10.1016/j.compositesa.2009.03.002.
- [18] H. Abrial *et al.*, “Characterization of tapioca starch biopolymer composites reinforced with micro scale water hyacinth fibers,” *starch*, vol. 70, no. 7–8, 2018.
- [19] M. S. Islam, M. M. Islam, and K. N. Islam, “The Effect of CaCO<sub>3</sub> Nanoparticles and Chitosan on the Properties of PLA Based Biomaterials for Biomedical Applications,” *Encycl. Renew. Sustain. Mater.*, pp. 736–745, 2020, doi: 10.1016/b978-0-12-803581-8.11576-0.
- [20] S. Tang, P. Zou, H. Xiong, and H. Tang, “Effect of nano-SiO<sub>2</sub> on the performance of starch/polyvinyl alcohol blend films,” *Carbohydr. Polym.*, vol. 72, no. 3, pp. 521–526, 2008, doi: 10.1016/j.carbpol.2007.09.019.
- [21] C. Paladiya and A. Kiani, “Nano structured sensing surface: Significance in sensor fabrication,” *Sensors Actuators, B Chem.*, vol. 268, pp. 494–511, 2018, doi: 10.1016/j.snb.2018.04.085.
- [22] H. Kargarzadeh, N. Johar, and I. Ahmad, “Starch biocomposite film reinforced by multiscale rice husk fiber,” *Compos. Sci. Technol.*, vol. 151, pp. 147–155, 2017, doi: 10.1016/j.compscitech.2017.08.018.
- [23] H. Yousefi, M. Faezipour, S. Hedjazi, M. M. Mousavi, Y. Azusa, and A. H. Heidari, “Comparative study of paper and nanopaper properties prepared from bacterial cellulose nanofibers and fibers/ground cellulose nanofibers of canola straw,” *Ind. Crops Prod.*, vol. 43, no. 1, pp. 732–737, 2013, doi: 10.1016/j.indcrop.2012.08.030.
- [24] H. Tibolla, F. M. Pelissari, J. T. Martins, A. A. Vicente, and F. C. Menegalli, “Cellulose nanofibers produced from banana peel by chemical and mechanical treatments: Characterization and cytotoxicity assessment,” *Food Hydrocoll.*, vol. 75, pp. 192–201, 2018, doi: 10.1016/j.foodhyd.2017.08.027.
- [25] K. Das, D. Ray, N. R. Bandyopadhyay, S. Sahoo, A. K. Mohanty, and M. Misra, “Physico-mechanical properties of the jute micro/nanofibril

- reinforced starch/polyvinyl alcohol biocomposite films,” *Compos. Part B Eng.*, vol. 42, no. 3, pp. 376–381, 2011, doi: 10.1016/j.compositesb.2010.12.017.
- [26] W. Cheng, J. Chen, D. Liu, X. Ye, and F. Ke, “Impact of ultrasonic treatment on properties of starch film-forming dispersion and the resulting films,” *Carbohydr. Polym.*, vol. 81, no. 3, pp. 707–711, 2010, doi: 10.1016/j.carbpol.2010.03.043.
- [27] H. Abral, G. J. Putra, M. Asrofi, J. W. Park, and H. J. Kim, “Effect of vibration duration of high ultrasound applied to bio-composite while gelatinized on its properties,” *Ultrason. Sonochem.*, vol. 40, pp. 697–702, 2018, doi: 10.1016/j.ultsonch.2017.08.019.
- [28] P. A. Tipler, *FISIKA untuk Sains dan Teknik*. Erlangga.
- [29] N. . Yatarif, “Karakterisasi sinyal akustik untuk mendeteksi keabnormalan jaringan tubuh menggunakan ultrasonik,” *Skripsi*, 2008.
- [30] B. . Hapsari, “Sintesis nanosfer berbasis ferrofluid dan poly lactic acid (PLA) dengan metode sonikasi,” *Skripsi*, 2009.
- [31] K. S. Suslick, *The chemistry of ultrasound from the yearbook of science and the future*. Chicago, USA: Encyclopedia Britannica, 1994.
- [32] C. M. Hassan and N. A. Peppas, “Structure and morphology of freeze/thawed PVA hydrogels,” *Macromolecules*, vol. 33, no. 7, pp. 2472–2479, 2000, doi: 10.1021/ma9907587.
- [33] R. Stevano, “Karakterisasi Plastik Biodegradable dari Campuran Kitosan dan Polivinil Alkohol Menggunakan Metode Tanpa Pelarut,” (*Skripsi*).
- [34] D. da Silva Perez, A. Dufresne, S. Tapin-Lingua, G. Siqueira, and J. Bras, “Mechanical properties of natural rubber nanocomposites reinforced with cellulosic nanoparticles obtained from combined mechanical shearing, and enzymatic and acid hydrolysis of sisal fibers,” *Cellulose*, vol. 18, no. 1, pp. 57–65, 2010, doi: 10.1007/s10570-010-9463-1.
- [35] Z. Zhang *et al.*, “Mechanical properties, water swelling behavior, and

morphology of swellable rubber compatibilized by PVA-g-PBA,” *Polym. Eng. Sci.*, vol. 44, no. 1, pp. 72–78, 2004, doi: 10.1002/pen.20006.

- [36] E. T. Wardani, “Pengaruh ekstrak jahe (*Zingiber officinale* Rosc.) var. gajah terhadap kualitas spermatozoa mencit (*Mus musculus*) YANG terpapar 2-methoxyethanol,” *Dr. Diss.*
- [37] S. Thomas, S. Gopi, J. Jacob, J. Haponiuk, and G. Peter, “Use of Ginger Nanofibers for the Preparation of Cellulose Nanocomposites and Their Antimicrobial Activities,” *Fibers*, vol. 6, no. 4, p. 79, 2018, doi: 10.3390/fib6040079.
- [38] S. Ni, H. Zhang, P. M. Godwin, H. Dai, and H. Xiao, “ZnO nanoparticles enhanced hydrophobicity for starch film and paper,” *Mater. Lett.*, vol. 230, no. July, pp. 207–210, 2018, doi: 10.1016/j.matlet.2018.07.075.
- [39] W. Kurniawan, “Karakterisasi Material Komposit Jerami-Epoksi Yang Dibuat Dengan Proses Vacuum Bag,” *Skripsi*, 2013.

