

DAFTAR PUSTAKA

- (1) Science, M. Multiferroic Materials for Sensors, Transducers and Memory Devices. *Arch. Acoust.* **2008**, *260*, 243–260.
- (2) Axelsson, A. K.; Le Goupi, F.; Valant, M.; Alford, N. M. N. Electrocaloric Effect in Lead-Free Aurivillius Relaxor Ferroelectric Ceramics. *Acta Mater.* **2017**, *124*, 120–126.
- (3) Dai, L.; Bao, S.; Zeng, H.; Liu, J. Investigation of Domain Retention Behaviors of La³⁺-Doped SrBi₂Ta₂O₉ Thin Films. *Mater. Lett.* **2005**, *59* (5), 603–606.
- (4) Kennedy, B. J.; Zhou, Q.; Ismunandar; Kubota, Y.; Kato, K. Cation Disorder and Phase Transitions in the Four-Layer Ferroelectric Aurivillius Phases ABi₄Ti₄O₁₅ (A=Ca, Sr, Ba, Pb). *J. Solid State Chem.* **2008**, *181* (6), 1377–1386.
- (5) Suresh, M. B.; Ramana, E. V.; Babu, S. N.; Suryanarayana, S. Comparison of Electrical and Dielectric Properties of BLSF Materials in Bi-Fe-Ti-O and Bi-Mn-Ti-O Systems. *Ferroelectrics* **2006**, *332*, 57–63.
- (6) Kannan, B. R.; Venkataraman, B. H. Influence of Samarium Doping on Structural and Dielectric Properties of Strontium Bismuth Tantalate Ceramics Derived by Molten Salt Synthesis Route. *J. Mater. Sci. Mater. Electron.* **2014**, *25* (11), 4943–4948.
- (7) Kannan, B. R.; Venkataraman, B. H. Dielectric and Electrical Conductivity Characteristics of Undoped and Samarium Doped Ferroelectric SrBi₂Ta₂O₉ Ceramics Derived from Molten Salt Synthesis Route. *Ferroelectrics* **2016**, *493* (1), 110–119.
- (8) Jennet, D. Ben; Marchet, P.; El Maaoui, M.; Mercurio, J. P. From Ferroelectric to Relaxor Behaviour in the Aurivillius-Type Bi₄-XBaxTi₃-XNb_xO₁₂ (0≤x≤1.4) Solid Solutions. *Mater. Lett.* **2005**, *59* (2–3), 376–382.
- (9) Axelsson, A. K.; Le Goupi, F.; Valant, M.; Alford, N. M. N. Optimisation of SrBi₂(Nb,Ta)2O₉ Aurivillius Phase for Lead-Free Electrocaloric Cooling. *J. Eur. Ceram. Soc.* **2018**, *38* (16), 5354–5358.
- (10) Khokhar, A.; Goyal, P. K.; Thakur, O. P.; Shukla, A. K.; Sreenivas, K. Influence of Lanthanum Distribution on Dielectric and Ferroelectric Properties of BaBi₄-XLaxTi₄O₁₅ Ceramics. *Mater. Chem. Phys.* **2015**, *152*, 13–25.
- (11) Reddyprakash, M.; Rout, S. K.; Satapathy, A.; Sinha, T. P.; Sariful, S. M. Dielectric and Ferroelectric Properties of Samarium Substituted BaBi₄Ti₄O₁₅ Aurivillius Oxides. *Ceram. Int.* **2016**, *42* (7), 8798–8803.
- (12) Xiang, P. H.; Kinemuchi, Y.; Watari, K. Synthesis of Layer-Structured

- Ferroelectric Bi₃NbTiO₉ Plate-like Seed Crystals. *Mater. Lett.* **2005**, *59* (14–15), 1876–1879.
- (13) Kimura, T. Molten Salt Synthesis of Ceramic Powders. *Adv. Ceram. - Synth. Charact. Process. Specif. Appl.* **2011**.
- (14) Kumar, S.; Ochoa, D. a; Garcia, J. E. Relaxor Ferroelectric Behavior and Structural Aspects of SrNaBi₂Nb₃O₁₂ Ceramics. *J. Am. Ceram. Soc.* **2012**, *95*, 1–18.
- (15) Zulhadjri, Z.; Ramadhani, R.; Billah, A. A.; Arief, S. Sintesis Senyawa Aurivillius Ca₁-XBi_{3,5+x}La_{0,5}Ti₄-XMnxO₁₅: Struktur Dan Sifat Dielektrik. **2018**, *14* (1), 143–151.
- (16) Nayak, P.; Singh, A. K. Correlation between Orthorhombic Distortion with Relaxation and Conduction Mechanism of Gd₃+Modi Fi Ed SrBi₄Ti₄O₁₅ Ceramics. *Ceram. Int.* **2018**, *44* (18), 22840–22849.
- (17) Xiao, J.; Zhang, H.; Xue, Y.; Lu, Z.; Chen, X.; Su, P.; Yang, F.; Zeng, X. The Influence of Ni-Doping Concentration on Multiferroic Behaviors in Bi₄NdTi₃FeO₁₅ Ceramics. *Ceram. Int.* **2015**, *41* (1), 1087–1092.
- (18) Ashok, K.; Suresh, M. B.; Sarah, P. Electrical Properties of Li And Nd Doped SrBi₄Ti₄O₁₅ Ceramics. *Int. J. Eng. Res. Technol.* **2013**, *2* (6), 3299–3307.
- (19) Moure, A. Review and Perspectives of Aurivillius Structures as a Lead-Free Piezoelectric System. *Appl. Sci.* **2018**, *8* (1).
- (20) Wang, W.; Rao, J.; Ke, H.; Meng, X.; Jia, D.; Zhou, Y. Domain Structures in Hot-Press Sintered SrBi₂Ta_{1.6}Nb_{0.4}O₉ and SrBi₂Ta₂O₉ Ferroelectric Ceramics. *Ceram. Int.* **2012**, *38* (5), 3963–3967.
- (21) Li, Y.; Chen, G.; Zhang, H.; Li, Z.; Sun, J. Electronic Structure and Photocatalytic Properties of ABi₂Ta₂O₉ (A = Ca, Sr, Ba). *J. Solid State Chem.* **2008**, *181* (10), 2653–2659. <https://doi.org/10.1016/j.jssc.2008.05.020>.
- (22) Gupta, H. C.; Archana; Luthra, V. A Lattice Dynamical Investigation of the Raman and the Infrared Wavenumbers of SBT (SrBi₂Ta₂O₉). *J. Mol. Struct.* **2010**, *984* (1–3), 204–208.
- (23) Coondoo, I.; Panwar, N.; Puli, V. S.; Katiyar, R. S. Ferroelectric and Piezoelectric Studies on MoSubstituted SrBi₂Ta₂O₉ Ferroelectric Ceramics. *Integr. Ferroelectr.* **2011**, *124* (1), 1–9.
- (24) Ahda, S.; Mardiyanto; Mahyudin, A. . . Aplikasi Metode Molten Salt Untuk Sintesis Bahan Piezoelektrik Bi_{0,5}(Na_{0,75}K_{0,25})_{0,5}TiO₃. *J Sci Mater Ina* **2013**, *4* (14), 284 – 289.

- (25) Chi, Z. H.; Xiao, C. J.; Feng, S. M.; Li, F. Y.; Jin, C. Q.; Wang, X. H.; Chen, R. Z.; Li, L. T. Manifestation of Ferroelectromagnetism in Multiferroic BiMnO₃. *J. Appl. Phys.* **2005**, *98* (10), 1–5.
- (26) Noguchi, Y.; Goto, T.; Miyayama, M.; Hoshikawa, A.; Kamiyama, T. Ferroelectric Distortion and Electronic Structure in Bi₄Ti₃O₁₂. *J. Electroceramics* **2008**, *21* (1-4 SPEC. ISS.), 49–54.
- (27) Shimakawa, Y.; Kubo, Y.; Nakagawa, Y.; Kamiyama, T.; Asano, H.; Izumi, F. Crystal Structures and Ferroelectric Properties of SrBi₂Ta₂O₉ and Sr_{0.8}Bi_{2.2}Ta₂O₉. *Appl. Phys. Lett.* **1999**, *74* (13), 1904–1906.
- (28) Porob, D. G.; Maggard, P. A. Synthesis of Textured Bi₅Ti₃FeO₁₅ and LaBi₄Ti₃FeO₁₅ Ferroelectric Layered Aurivillius Phases by Molten-Salt Flux Methods. *Mater. Res. Bull.* **2006**, *41* (8), 1513–1519.
- (29) Fuentes, L.; García, M.; Bueno, D.; Fuentes, M.; Muñoz, A. Magnetoelectric Effect in Bi₅Ti₃FeO₁₅ Ceramics Obtained by Molten Salts Synthesis. *Ferroelectrics* **2006**, *336*, 81–89.
- (30) Xia, F.; Wang, X.; Zhang, L.; Yao, X. Dielectric and Piezoelectric Properties of PMN-PT Ceramics Prepared by Molten Salt Synthesis. *Ferroelectrics* **1998**, *215* (1), 181–186.
- (31) Wendari, T. P.; Arief, S.; Mufti, N.; Baas, J.; Blake, G. R.; Zulhadjri. Ratio Effect of Salt Fluxes on Structure, Dielectric and Magnetic Properties of La,Mn-Doped PbBi₂Nb₂O₉ Aurivillius Phase. *Ceram. Int.* **2020**, *46* (10), 14822–14827.
- (32) Ramos Guivar, J. A.; Sanches, E. A.; Bruns, F.; Sadrollahi, E.; Morales, M. A.; López, E. O.; Litterst, F. J. Vacancy Ordered γ-Fe₂O₃ Nanoparticles Functionalized with Nanohydroxyapatite: XRD, FTIR, TEM, XPS and Mössbauer Studies. *Appl. Surf. Sci.* **2016**, *389*, 721–734.
- (33) Rusli, R. Petunjuk Refinement Analisis Pola Difraksi Sinar-X Serbuk Menggunakan Metode Le Bail Pada Program Rietrica. **2011**, No. May 2011.
- (34) Whatmore, R. Springer Handbook of Electronic and Photonic Materials. In *Springer Handbook of Electronic and Photonic Materials*; 2017; pp 589–614.
- (35) Wallace, R. M. Springer Handbook of Electronic and Photonic Materials. In *Springer Handbook of Electronic and Photonic Materials*; 2017; pp 615–644.
- (36) Swain, S.; Kumar, P.; Choudhary, R. B. Electrical and Ferroelectric Studies of the 2-Layered SrBi₂Ta₂O₉ Based Ceramics. *Phys. B Condens. Matter* **2015**, *477*, 56–63.
- (37) Wicaksono, D. D.; Setiawan, N. I.; Wilopo, W.; Harijoko, A. Teknik Preparasi

- Sampel Dalam Analisis Mineralogi Dengan XRD Di Departemen Teknik Geologi, Fakultas Teknik, Universitas Gadjah Mada. In *Seminar Nasional Kebumian ke-10*; 2017; pp 1864–1880.
- (38) Cao, Z. P.; Wang, C. M.; Zhao, T. L.; Yu, S. L.; Wu, H. Z.; Wang, Y. M.; Wang, Q.; Liang, Y.; Wei, Y. N.; Zhang, Y.; Liu, Y.; Tang, X. S. Piezoelectric Properties and Thermal Stabilities of Strontium Bismuth Titanate ($\text{SrBi}_4\text{Ti}_4\text{O}_{15}$). *Ceram. Int.* **2015**, *41* (10), 13974–13982.
- (39) Sridarane, R.; Subramanian, S.; Janani, N.; Murugan, R. Investigation on Microstructure, Dielectric and Impedance Properties of $\text{Sr}_1\text{X}\text{Bi}_2+(2/3)\text{x}(\text{VxTa}_{1-\text{x}})_2\text{O}_9$ [$\text{x} = 0, 0.1$ and 0.2] Ceramics. *J. Alloys Compd.* **2010**, *492* (1–2), 642–648.
- (40) Wendari, T. P.; Arief, S.; Mufti, N.; Suendo, V.; Prasetyo, A.; Ismunandar; Baas, J.; Blake, G. R.; Zulhadjri. Synthesis, Structural Analysis and Dielectric Properties of the Double-Layer Aurivillius Compound $\text{Pb}_1-2\text{xBi}_{1.5+2\text{x}}\text{La}_0.5\text{Nb}_2\text{-XMn}_x\text{O}_9$. *Ceram. Int.* **2019**, *45* (14), 17276–17282.
- (41) Zulhadjri; Prijamboedi, B.; Nugroho, A. A.; Mufti, N.; Fajar, A.; Palstra, T. T. M.; Ismunandar. Aurivillius Phases of $\text{PbBi}_4\text{Ti}_4\text{O}_15$ Doped with Mn 3 Synthesized by Molten Salt Technique: Structure, Dielectric, and Magnetic Properties. *J. Solid State Chem.* **2011**, *184* (5), 1318–1323.
- (42) Lawita, P.; Siriprapa, P.; Watcharapason, A.; Jiansirisomboon, S. Effects of Pb Concentration on Phase, Microstructure and Electrical Properties of $\text{Bi}_{3.25}\text{La}_{0.75}\text{Ti}_3\text{O}_{12}$ Ceramics. *Mater. Chem. Phys.* **2012**, *134* (2–3), 932–937.
- (43) Senthil, V.; Panigrahi, S. Dielectric, Ferroelectric, Impedance and Photocatalytic Water Splitting Study of Y^{3+} Modified $\text{SrBi}_2\text{Ta}_2\text{O}_9$ Ferroelectrics. *Int. J. Hydrogen Energy* **2019**, *44* (33), 18058–18071.
- (44) Coondoo, I.; Jha, A. K.; Agarwal, S. K. Enhancement of Dielectric Characteristics in Donor Doped Aurivillius $\text{SrBi}_2\text{Ta}_2\text{O}_9$ Ferroelectric Ceramics. *J. Eur. Ceram. Soc.* **2007**, *27* (1), 253–260.
- (45) Kumar, S.; Varma, K. B. R. Dielectric, Ferroelectric and Relaxor Behavior of $\text{BaLaxBi}_{4-x}\text{Ti}_4\text{O}_{15}$ Ceramics. *Adv. Sci. Lett.* **2010**, *3* (1).
- (46) Zulhadjri; Wendari, T. P.; Septiani, U.; Arief, S. Investigation on Structure, Dielectric and Magnetic Properties of the Four-Layer Aurivillius Phase $\text{Pb}_1-\text{XBi}_{3.5+\text{x}}\text{Nd}_{0.5}\text{Ti}_4\text{-XMn}_x\text{O}_{15}$ Prepared via Molten Salt Method. *J. Solid State Chem.* **2020**, *292* (August), 121723.
- (47) Moret, M.; Zallen, R.; Newnham, R. Infrared Activity in the Aurivillius Layered

- Ferroelectric SrBi₂Ta₂O₉. *Phys. Rev. B - Condens. Matter Mater. Phys.* **1998**, 57 (10), 5715–5723.
- (48) Diao, C. L.; Zheng, H. W.; Gu, Y. Z.; Zhang, W. F.; Fang, L. Structural and Electrical Properties of Four-Layers Aurivillius Phase BaBi_{3.5}Nd_{0.5}Ti₄O₁₅ Ceramics. *Ceram. Int.* **2014**, 40 (4), 5765–5769.
<https://doi.org/10.1016/j.ceramint.2013.11.015>.
- (49) Sivakumar, T.; Itoh, M. Ferroelectric Phase Transitions in New Aurivillius Oxides: Bi_{2+2x}Sr_{1-2x}Nb_{2-X}Sc_xO₉. *J. Mater. Chem.* **2011**, 21 (29), 10865–10870.
- (50) Amorín, H.; Shvartsman, V. V.; Kholkin, A. L.; Costa, M. E. V. Ferroelectric and Dielectric Anisotropy in High-Quality SrBi₂Ta₂O₉ Single Crystals. *Appl. Phys. Lett.* **2004**, 85 (23), 5667–5669.

