

REFERENCE

- [1] A. Oryan, S. Monazzah, and A. Bigham-Sadegh, “Bone Injury and Fracture Healing Biology,” *Biomed. Environ. Sci.*, vol. 28, no. 1, pp. 57–71, 2015, doi: 10.3967/bes2015.006.
- [2] C Cooper and S. Ferrari, *IOF Compendium of Osteoporosis*. 2017.
- [3] K. Prasad *et al.*, “Metallic biomaterials: Current challenges and opportunities,” *Materials (Basel)*., vol. 10, no. 8, 2017, doi: 10.3390/ma10080884.
- [4] J. J. Noël, N. Ebrahimi, and D. W. Shoesmith, “Corrosion of Titanium and Titanium Alloys,” *Encycl. Interfacial Chem.*, no. January, pp. 192–200, 2018, doi: 10.1016/b978-0-12-409547-2.13834-x.
- [5] Y. Xie, X. Liu, P. K. Chu, X. Zheng, and C. Ding, “Bioactive titanium-particle-containing dicalcium silicate coating,” *Surf. Coatings Technol.*, vol. 200, no. 5–6, pp. 1950–1953, 2005, doi: 10.1016/j.surfcoat.2005.08.070.
- [6] M. Akram, R. Ahmed, I. Shakir, W. A. W. Ibrahim, and R. Hussain, “Extracting hydroxyapatite and its precursors from natural resources,” *J. Mater. Sci.*, vol. 49, no. 4, pp. 1461–1475, 2014, doi: 10.1007/s10853-013-7864-x.
- [7] S. Fujibayashi, M. Neo, H. M. Kim, T. Kokubo, and T. Nakamura, “A comparative study between in vivo bone ingrowth and in vitro apatite formation on Na₂O-CaO-SiO₂ glasses,” *Biomaterials*, vol. 24, no. 8, pp. 1349–1356, 2003, doi: 10.1016/S0142-9612(02)00511-2.
- [8] T. Sozen, L. Ozisik, and N. Calik Basaran, “An overview and management of osteoporosis,” *Eur. J. Rheumatol.*, vol. 4, no. 1, pp. 46–56, 2017, doi: 10.5152/eurjrheum.2016.048.
- [9] World Health Organization, “Who Scientific Group on the Assessment of Osteoporosis At Primary Health,” *World Health*, vol. May, no. May 2004, pp. 1–13, 2007, doi: 10.1016/S0140-6736(02)08761-5.
- [10] J. Black, “Biologic performance of tantalum,” *Clin. Mater.*, vol. 16, no. 3, pp. 167–173, 1994, doi: 10.1016/0267-6605(94)90113-9.
- [11] W. Cao and L. L. Hench, “Bioactive materials,” *Ceram. Int.*, vol. 22, no. 6, pp. 493–507, 1996, doi: 10.1016/0272-8842(95)00126-3.
- [12] V. Guarino, M. G. Raucci, A. Ronca, V. Cirillo, and L. Ambrosio, *Multifunctional scaffolds for bone regeneration*. Woodhead Publishing Limited, 2014.
- [13] J. Biswas, S. Karmakar, S. Majumder, P. S. Banerjee, S. Saha, and A. Roychowdhury, “Optimization of spinal implant screw for lower vertebra

- through finite element studies,” *J. Long. Term. Eff. Med. Implants*, vol. 24, no. 2–3, pp. 99–108, 2014, doi: 10.1615/JLongTermEffMedImplants.2014006264.
- [14] V. K. Goel, M. M. Panjabi, A. G. Patwardhan, A. P. Dooris, and H. Serhan, “Test protocols for evaluation of spinal implants,” *J. Bone Jt. Surg. - Ser. A*, vol. 88, no. SUPPL. 2, pp. 103–109, 2006, doi: 10.2106/JBJS.E.01363.
- [15] M. Nakai, M. Niinomi, X. Zhao, and X. Zhao, “Self-adjustment of Young’s modulus in biomedical titanium alloys during orthopaedic operation,” *Mater. Lett.*, vol. 65, no. 4, pp. 688–690, 2011, doi: 10.1016/j.matlet.2010.11.006.
- [16] M. Farrokhi-Rad and T. Shahrabi, “Effect of triethanolamine on the electrophoretic deposition of hydroxyapatite nanoparticles in isopropanol,” *Ceram. Int.*, vol. 39, no. 6, pp. 7007–7013, 2013, doi: 10.1016/j.ceramint.2013.02.038.
- [17] K. Sangeetha, A. V. Jisha Kumari, J. Venkatesan, A. Sukumaran, S. Aisverya, and P. N. Sudha, *Degradable metallic biomaterials for cardiovascular applications*. Elsevier Ltd, 2018.
- [18] K. W. K. Yeung and K. H. M. Wong, “Biodegradable metallic materials for orthopaedic implantations: A review,” *Technol. Heal. Care*, vol. 20, no. 5, pp. 345–362, 2019, doi: 10.3233/thc-2012-0685.
- [19] Q. Qu, L. Wang, Y. Chen, L. Li, Y. He, and Z. Ding, “Corrosion behavior of titanium in artificial saliva by lactic acid,” *Materials (Basel)*, vol. 7, no. 8, pp. 5528–5542, 2014, doi: 10.3390/ma7085528.
- [20] D. R. Rao, K. Hariharan, and K. R. Vijayalakshmi, “Synthesis of L [U-¹⁴C] α,β diaminopropionic acid,” *Indian J. Biochem. Biophys.*, vol. 11, no. 3, pp. 265–266, 1974.
- [21] M. Farrokhi-Rad, S. K. Loghmani, T. Shahrabi, and S. Khanmohammadi, “Electrophoretic deposition of hydroxyapatite nanostructured coatings with controlled porosity,” *J. Eur. Ceram. Soc.*, vol. 34, no. 1, pp. 97–106, 2014, doi: 10.1016/j.jeurceramsoc.2013.07.022.
- [22] T. Kokubo and H. Takadama, “How useful is SBF in predicting in vivo bone bioactivity?,” *Biomaterials*, vol. 27, no. 15, pp. 2907–2915, 2006, doi: 10.1016/j.biomaterials.2006.01.017.
- [23] T. Laonapakul, A. Rakngarm Nimkerdphol, Y. Otsuka, and Y. Mutoh, “Failure behavior of plasma-sprayed HA_p coating on commercially pure titanium substrate in simulated body fluid (SBF) under bending load,” *J. Mech. Behav. Biomed. Mater.*, vol. 15, pp. 153–166, 2012, doi: 10.1016/j.jmbbm.2012.05.017.
- [24] B. A. Shaw and R. G. Kelly, “What is corrosion?,” *Electrochem. Soc. Interface*, vol. 15, no. 1, pp. 24–26, 2006, doi: 10.1149/2.f06061if.