

DAFTAR PUSTAKA

- [1] F. M. Al-Oqla and S. M. Sapuan, “Natural fiber reinforced polymer composites in industrial applications: Feasibility of date palm fibers for sustainable automotive industry,” *J. Clean. Prod.*, vol. 66, pp. 347–354, 2014, doi: 10.1016/j.jclepro.2013.10.050.
- [2] M. Haddad, R. Zitoune, F. Eyma, and B. Castanie, “Study of the surface defects and dust generated during trimming of CFRP: Influence of tool geometry, machining parameters and cutting speed range,” *Compos. Part A Appl. Sci. Manuf.*, vol. 66, pp. 142–154, 2014, doi: 10.1016/j.compositesa.2014.07.005.
- [3] J.Y. Sheikh-Ahmad, “Machining ofPolymer Composites,” 2009, doi: 10.1007/978-0-387-68619-6.
- [4] A. B. Prasetiyo, “APLIKASI METODE TAGUCHI PADA OPTIMASI PARAMETER PERMESINAN TERHADAP KEKASARAN PERMUKAAN DAN KEAUSAN PAHAT HSS PADA PROSES BUBUT MATERIAL ST 37 Keywords : Abstract ;,” *Mekanika*, vol. 13, no. 2008, pp. 86–97, 2015.
- [5] A. D. I. Nugroho, “Pengaruh gerak makan dan sudut potong utama terhadap hasil kesilindrisan permukaan benda kerja pada proses bubut silindris,” 2009.
- [6] M. Yanis, “Menggunakan Mesin Bubut Cnc.”
- [7] T. Rochim, “Taufiq Rochim, ‘Teori & Teknologi Proses Pemesinan,’ Inst. Teknol. Bandung, p. 2007, 1993,” p. 293, 2011.
- [8] P. Geometeri, P. Bubut, P. Proses, P. Model, and P. Propeller, “PEMBENTUKAN GEOMETRI PAHAT BUBUT PADA PROSES Formation Geometry Lathe Chisel on Operate a Lathe Process Model

- Propeller Shaft,” pp. 13–18, 2013.
- [9] P. J. Pahat, S. Pahat, and D. A. N. Kedalaman, “Terhadap Tingkat Kekasaran Dan Kekerasan Pada Proses Bubut Rata Baja St 42,” vol. 01, pp. 56–64, 2013, [Online]. Available: Pandhu Pramawata, Yunus.
- [10] S. R. Schmid, “MANUFACTURING ENGINEERING Illinois Institute of Technology.”
- [11] D. Angle, D. Mata, D. Process, M. Strut, and M. Guruh, “MENENTUKAN SUDUT PUNCAK MATA BOR PADA PROSES Determining Angle Drill Mata Peak In the Drilling Process Models Strut,” 2013.
- [12] E. Schmid, “Contribution to the Physics and Metallography of Magnesium,” *Zeit fur Electrochemie*, vol. 37. pp. 447–459, 1931.
- [13] G. Zamfirova and A. Dimitrova, “Some methodological contributions to the Vickers microhardness technique,” *Polym. Test.*, vol. 19, no. 5, pp. 533–542, 2000, doi: 10.1016/S0142-9418(99)00023-9.
- [14] K. Palanikumar, “Application of Taguchi and response surface methodologies for surface roughness in machining glass fiber reinforced plastics by PCD tooling,” *Int. J. Adv. Manuf. Technol.*, vol. 36, no. 1–2, pp. 19–27, 2008, doi: 10.1007/s00170-006-0811-0.
- [15] W. H. Yang and Y. S. Tarng, “Design optimization of cutting parameters for turning operations based on the Taguchi method,” *J. Mater. Process. Technol.*, vol. 84, no. 1–3, pp. 122–129, 1998, doi: 10.1016/S0924-0136(98)00079-X.
- [16] P. H. Sankar, Y. Venkata, M. Reddy, and K. H. Reddy, “Polyester / Vinylester Polymer Hybrid Blended Nanocomposites : Effect of Nano on Mechanical and Thermal Properties,” vol. 16, no. 2, pp. 443–448, 2015, doi: 10.1007/s12221-015-0443-9.
- [17] H. Ardhyananta *et al.*, “Mechanical and Thermal Properties of Unsaturated

Polyester/Vinyl Ester Blends Cured at Room Temperature," *IOP Conf. Ser. Mater. Sci. Eng.*, vol. 202, no. 1, 2017, doi: 10.1088/1757-899X/202/1/012088.

- [18] A. Malik, F. Fawwazi, and D. Putra, "Effect of the Cutting Parameters and the Cutting Edge Angle of Turning Process on Product Geometry of Composite," *Pros. SNTTM XVIII*, pp. 9–10, 2019.
- [19] H. Abral *et al.*, "Mechanical properties of water hyacinth fibers - polyester composites before and after immersion in water," *Mater. Des.*, vol. 58, pp. 125–129, 2014, doi: 10.1016/j.matdes.2014.01.043.
- [20] Y. Quan and B. Ye, "The effect of machining on the surface properties of SiC/Al composites," *J. Mater. Process. Technol.*, vol. 138, no. 1–3, pp. 464–467, 2003, doi: 10.1016/S0924-0136(03)00119-5.
- [21] H. K. Toenshoff and E. Brinksmeier, "Determination of the Mechanical and Thermal Influences on Machined Surfaces By Microhardness and Residual Stress Analysis.,," *CIRP Ann. - Manuf. Technol.*, vol. 29, no. 2, pp. 519–530, 1980, doi: 10.1016/s0007-8506(16)30145-7.