

## DAFTAR PUSTAKA

- [1] Murdock dan Brooks, "BAB II Tinjauan Pustaka Anemia," *Univ. Muhammadiyah Surakarta*, pp. 6–25, 1979, [Online]. Available: [http://repository.unpas.ac.id/37105/1/BAB II.pdf](http://repository.unpas.ac.id/37105/1/BAB%20II.pdf).
- [2] D. E. S. Arifin and M. Zainuri, "Karakterisasi Sifat Separator Komposit PVDF/poli(dimetilsiloksan) Dengan Metode Pencampuran Membran (Blending Membrane)," *J. Sains dan Seni Pomits*, vol. 3, no. 2, pp. 36–40, 2014.
- [3] E. Zaidar, "Emma zaidar 088103004," 2017.
- [4] H. Abral *et al.*, "Characterization of compressed bacterial cellulose nanopaper film after exposure to dry and humid conditions," *J. Mater. Res. Technol.*, vol. 11, pp. 896–904, 2021, doi: 10.1016/j.jmrt.2021.01.057.
- [5] A. N. Fauza, M. M. Mardiyati, and S. Steven, "Pembuatan Dan Karakterisasi Separator Baterai Berbahan Selulosa Alga *Cladophora*," *J. Teknol. Bahan dan Barang Tek.*, vol. 9, no. 2, p. 69, 2019, doi: 10.37209/jtbtt.v9i2.135.
- [6] C. Huang *et al.*, "TEMPO-oxidized bacterial cellulose nanofiber membranes as high-performance separators for lithium-ion batteries," *Carbohydr. Polym.*, vol. 230, p. 115570, 2020, doi: 10.1016/j.carbpol.2019.115570.
- [7] J. Michael, Z. Qifeng, and W. Danling, "Titanium carbide MXene: Synthesis, electrical and optical properties and their applications in sensors and energy storage devices," *Nanomater. Nanotechnol.*, vol. 9, pp. 1–9, 2019, doi: 10.1177/1847980418824470.
- [8] Z. Zhan, Q. Song, Z. Zhou, and C. Lu, "Ultrastrong and conductive MXene/cellulose nanofiber films enhanced by hierarchical nano-architecture and interfacial interaction for flexible electromagnetic interference shielding," *J. Mater. Chem. C*, vol. 7, no. 32, pp. 9820–9829, 2019, doi: 10.1039/c9tc03309b.
- [9] A. Tron, A. Nosenko, Y. D. Park, and J. Mun, "Enhanced ionic conductivity of the

solid electrolyte for lithium-ion batteries,” *J. Solid State Chem.*, vol. 258, no. October 2017, pp. 467–470, 2018, doi: 10.1016/j.jssc.2017.11.020.

- [10] M. Amadri, “BAB II Dasar Teori,” *Libr. Politek. Negeri Bandung*, vol. 1937, pp. 5–45, 2013, [Online]. Available: <http://digilib.polban.ac.id/files/disk1/96/jbptppolban-%0Agdl-mochamadri-4787-3-bab2--8.pdf%0A>.
- [11] S. Yesica, “SINTESIS DAN KARAKTERISASI NANOKOMPOSIT TiO<sub>2</sub>/ZEOLIT ALAM MALANG DENGAN VARIASI WAKTU PEMERAMAN,” 2016.
- [12] B. A. B. Ii and T. Pustaka, “5 Institut Teknologi Nasional,” pp. 5–34, 1994.
- [13] R. J. Moon, A. Martini, J. Nairn, J. Simonsen, and J. Youngblood, *Cellulose nanomaterials review: Structure, properties and nanocomposites*, vol. 40, no. 7. 2011.
- [14] B. A. B. Ii, “Serat Alam,” pp. 6–24.
- [15] E. Malvianie, Y. Pratama, and S. Salafudin, “Fermentasi Sampah Buah Nanas menggunakan Sistem Kontinu dengan bantuan Bakteri *Acetobacter Xylinum*,” *Reka Lingkungan.*, vol. 2, no. 1, pp. 1–11, 2014.
- [16] X. Diffraction, F. T. Infrared, and S. E. Microscope, “DENGAN PENAMBAHAN KITOSAN Tutiek Rahayu dan Eli Rohaeti Abstrak Selulosa bakteri adalah selulosa yang diproduksi oleh bakteri asam asetat dan memiliki beberapa keunggulan dibandingkan selulosa yang berasal dari Keunggulan tersebut di antaranya memiliki ke,” no. 1.
- [17] E. Apriani, “Pengaruh Rasio Urea Dan Npk Pada Proses Pembuatan Bioetanol Dari Mahkota Buah Nenas,” pp. 3–4, 2015.
- [18] Morgan, “Pembuatan Carboxymethyl Cellulose Dari Limbah Eceng Gondok Dengan Perlakuan Menggunakan Metode Delignifikasi,” *J. Chem. Inf. Model.*, vol. 53, no. 9, pp. 1689–1699, 2019.
- [19] R. Sarwono *et al.*, “Menjadi Glukosa Dengan Proses Hidrotermal,” pp. 63–71, 2016.
- [20] Nuraini, “No Title PENGOLAHAN NATA DE COCO,” *Farmasi*, pp. 4–16, 2015.

- [21] A. H. Saputra and H. N. Anindita, "Synthesis of nata de coco fiber composite with conductive filler as an eco-friendly semiconductor material," *Int. J. Technol.*, vol. 6, no. 7, pp. 1198–1204, 2015, doi: 10.14716/ijtech.v6i7.1772.
- [22] P. Rachtanapun *et al.*, "Carboxymethyl bacterial cellulose from nata de coco: Effects of NaOH," *Polymers (Basel)*, vol. 13, no. 3, pp. 1–17, 2021, doi: 10.3390/polym13030348.
- [23] S. K. Hwang, S. M. Kang, M. Rethinasabapathy, C. Roh, and Y. S. Huh, "MXene: An emerging two-dimensional layered material for removal of radioactive pollutants," *Chem. Eng. J.*, vol. 397, no. March, p. 125428, 2020, doi: 10.1016/j.cej.2020.125428.
- [24] M. Han *et al.*, "Beyond Ti<sub>3</sub>C<sub>2</sub>T<sub>x</sub>: MXenes for Electromagnetic Interference Shielding," *ACS Nano*, vol. 14, no. 4, pp. 5008–5016, 2020, doi: 10.1021/acsnano.0c01312.
- [25] G. Song *et al.*, "Highly flexible few-layer Ti<sub>3</sub>C<sub>2</sub>MXene/cellulose nanofiber heat-spreader films with enhanced thermal conductivity," *New J. Chem.*, vol. 44, no. 17, pp. 7186–7193, 2020, doi: 10.1039/d0nj00672f.
- [26] K. Maleski and M. Alhabeb, "Top-down MXene synthesis (selective etching)," *2D Met. Carbides Nitrides Struct. Prop. Appl.*, pp. 69–87, 2019, doi: 10.1007/978-3-030-19026-2\_5.
- [27] A. Iqbal *et al.*, "Anomalous absorption of electromagnetic waves by 2D transition metal carbonitride Ti<sub>3</sub>CNT<sub>x</sub> (MXene) Downloaded from," *Science (80-. )*, vol. 369, no. July, pp. 446–450, 2020, [Online]. Available: <http://science.sciencemag.org/>.
- [28] W. Liu *et al.*, "Rapid Continuous Multimaterial Extrusion Bioprinting," *Adv. Mater.*, vol. 29, no. 3, pp. 1–8, 2017, doi: 10.1002/adma.201604630.
- [29] D. Muliadi, "Universitas Sumatera Utara 7," pp. 7–37, 2015.
- [30] A. Isogai, T. Saito, and H. Fukuzumi, "TEMPO-oxidized cellulose nanofibers," *Nanoscale*, vol. 3, no. 1, pp. 71–85, 2011, doi: 10.1039/c0nr00583e.
- [31] J. Fisika and F. Universitas, "291672889.Pdf," vol. 2, no. 3, pp. 2011–2014, 2013.

- [32] W. D. Hill, "Battery," *English J.*, vol. 69, no. 5, p. 55, 1980, doi: 10.2307/817656.
- [33] L. N. Putri, R. R. Alhakim, A. Rochim, A. Ichwan, and E. Retno, "Review : Separator Baterai Ion Litium Dengan Penambahan Filler Dalam Membran PVDF / Selulosa," pp. 169–176.
- [34] E. S. Choi and S. Y. Lee, "Particle size-dependent, tunable porous structure of a SiO<sub>2</sub>/poly(vinylidene fluoride-hexafluoropropylene)-coated poly(ethylene terephthalate) nonwoven composite separator for a lithium-ion battery," *J. Mater. Chem.*, vol. 21, no. 38, pp. 14747–14754, 2011, doi: 10.1039/c1jm12246k.
- [35] W. Chen, Y. Liu, Y. Ma, and W. Yang, "Improved performance of lithium ion battery separator enabled by co-electrospinning polyimide/poly(vinylidene fluoride-co-hexafluoropropylene) and the incorporation of TiO<sub>2</sub>-(2-hydroxyethyl methacrylate)," *J. Power Sources*, vol. 273, pp. 1127–1135, 2015, doi: 10.1016/j.jpowsour.2014.10.026.
- [36] A. Arya and A. L. Sharma, *Polymer electrolytes for lithium ion batteries: a critical study*, vol. 23, no. 3. Ionics, 2017.
- [37] D. Hidayat, R. Zulianto, B. M. Wibawa, and B. Y. Tumbelaka, "Pengembangan Pengukuran Sheet Resistance Film Tipis Menggunakan Metode Four Point Probe," no. November, pp. 26–27, 2016.
- [38] A. Lindgren and S. Wennberg, "Preparation of Nanofibers from Pulp Fibers. Master thesis, Chalmers University of Technology, Goteborg, Sweden," p. 56, 2010.