

DAFTAR PUSTAKA

- [1] J. C. Brody and J. W. Gillespie, “The effects of a thermoplastic polyester perform binder on vinyl ester resin,” *J. Thermoplast. Compos. Mater.*, vol. 18, no. 3, pp. 157–179, 2005, doi: 10.1177/0892705705043535.
- [2] D. S. Longnecker, “Background and perspective,” *Acad. Press. INC*, vol. 9781441964, 2013.
- [3] I. K. Suarsana, “Pengetahuan Material Teknik Universitas Udayana,” pp. 01–71, 2017.
- [4] J. Y. Sheikh-Ahmad, *Machining of polymer composites*. 2009.
- [5] A. Malik, “Kajian Keutuhan Permukaan Proses Mengisar,” Universiti Teknologi Malaysia (UTM), 1999.
- [6] R. Kartini, H. Darmasetiawan, A. K. Karo, and Sudirman, “Pembuatan dan Karakterisasi Komposit Polimer Berpenguat Serat Alam,” *J. Sains Mater. Indones.*, vol. 3, no. 3, pp. 30–38, 2002.
- [7] J. Oroh, F. P. Sappu, and R. Lumintang, “Analisis sifat mekanik material komposit dari serat sabut kelapa,” *J. Poros Tek. Mesin Unsrat*, vol. 1, no. 1, pp. 1–10, 2012.
- [8] I. Bambang and A. Harsojuwono, “Teknologi Polimer Industri Pertanian,” *Teknol. Polim.*, p. 108, 2015.
- [9] Daryanto, “Ilmu Bahan Mesin Perkakas Bengkel,” *Jakarta*, 1991.
- [10] A. Y. Aminy, R. Ilyas, Y. By, and H. Abbas, “Keefektifan Kondisi Pemotongan Terhadap Getaran dan Kekasaran Permukaan Dalam Proses Gurdi,” no. November, pp. 21–23, 2006.
- [11] Widarto, *TEKNIK PEMESINAN JILID 2 SMK Direktorat Pembinaan Sekolah Menengah Kejuruan*. 2010.
- [12] N. Tosun, “Determination of optimum parameters for multi-performance characteristics in drilling by using grey relational analysis,” *Int. J. Adv. Manuf. Technol.*, vol. 28, no. 5–6, pp. 450–455, 2006, doi: 10.1007/s00170-004-2386-y.
- [13] M. A. Amran *et al.*, “Effects of machine parameters on surface roughness using response surface method in drilling process,” *Procedia Eng.*, vol. 68,

pp. 24–29, 2013, doi: 10.1016/j.proeng.2013.12.142.

- [14] Am. Mufarrih, “Pengaruh Parameter Proses Gurdı Terhadap Kekasaran Permukaan Pada Material CFRP Komposit,” *Semin. Nas. Inov. Teknol.*, pp. 403–410, 2017.
- [15] W. H. Yang and Y. S. Tarng, “Design optimization of cutting parameters for turning operations based on the Taguchi method,” *J. Mater. Process. Technol.*, vol. 84, no. 1–3, pp. 122–129, 1998, doi: 10.1016/S0924-0136(98)00079-X.
- [16] S. A. N. Mohamed, E. S. Zainudin, S. M. Sapuan, M. D. Azaman, and A. M. T. Arifin, *Introduction to Natural Fiber Reinforced Vinyl Ester and Vinyl Polymer Composites*. Elsevier Ltd, 2018.
- [17] H. Ardhyananta *et al.*, “Mechanical and Thermal Properties of Unsaturated Polyester/Vinyl Ester Blends Cured at Room Temperature,” *IOP Conf. Ser. Mater. Sci. Eng.*, vol. 202, no. 1, 2017, doi: 10.1088/1757-899X/202/1/012088.
- [18] M. B. Launikitis, *Handbook of Composites*. New York, 1982.
- [19] T. Rochim, “Spesifikasi, metrologi & kontrol kualitas geometrik oleh taufiq rochim,” p. 293, 2011.
- [20] R. Ismail, B. F. T. K, and D. J. Schipper, “Mild Wear Study on Running-in of Rolling-Sliding Contacts,” no. 1989, pp. 58–65, 2007.
- [21] Bhushan, “Surface Roughness Analysis and Measurement Techniques,” *Ohio State Univ.*, 2001.
- [22] A. Zubaidi, I. Syafa’at, and Darmanto., “Analisis Pengaruh Kecepatan Putar Dan Kecepatan Pemakanan Terhadap Kekasaran Permukaan Material Fcd 40 Pada Mesin Bubut Cnc,” *Jur. Tek. Mesin*, vol. 8, no. 1, pp. 40–47, 2012.